Accessories and control

Distribution joint kits



2-Pipe ME2 for outdoor units (up to 68,0 kW).	2-Pipe ME2 for outdoor units (from 68,0 kW to 168,0 kW).	2-Pipe ME2 and Mini ECOi for indoor units (up to 22,4 kW*).
 CZ-P680PH2BM	CZ-P1350PH2BM	 CZ-P224BK2BM
2-Pipe ME2 for indoor units (from 22,4 kW to 68,0 kW*).	2-Pipe ME2 for indoor units (from 68,0 kW to 168,0 kW*).	3-Pipe MF3 for outdoor units (up to 68,0 kW).
 CZ-P680BK2BM	CZ-P1350BK2BM	CZ-P680PJ2BM
3-Pipe MF3 for outdoor units (from 68,0 kW to 135,0 kW).	3-Pipe MF3 for indoor units (up to 22,4 kW).	3-Pipe MF3 for indoor units (from 22,4 kW to 68,0 kW).
CZ-P1350PJ2BM	CZ-P224BH2BM	 CZ-P680BH2BM
3-Pipe MF3 for indoor units (up to 68,0 kW).	2-Pipe ME2 header pipe.	3-Pipe MF3 header pipe.
CZ-P1350BH2BM	 CZ-P4HP4C2BM	CZ-P4HP3C2BM

^{*} In case the total capacity of indoor units connected after distribution exceeds the total capacity of the outdoor units, select the distribution piping size for the total capacity of the outdoor units.

Heat recovery box





3-Pipe control Solenoid valve kit (up to 5,6 kW).

CZ-P56HR3 + CZ-CAPE2.

KIT-P56HR3

3-Pipe control Solenoid valve kit (from 5,6 to 16,0 kW).

CZ-P160HR3 + CZ-CAPE2.

KIT-P160HR3



Solenoid valve kit (up to 5,6 kW).

CZ-P56HR3

Solenoid valve kit (from 5,6 kW to 16,0 kW).

CZ-P160HR3



3-Pipe control PCB.

CZ-CAPE2

3-Pipe control PCB for wall-mounted.

CZ-CAPEK2



4 ports 3 pipe box (up to 5,6 kW per port).

CZ-P456HR3


4 ports 3 pipe box (up to 16,0 kW per port).

CZ-P4160HR3



6 ports 3 pipe box (up to 5,6 kW per port).

CZ-P656HR3



8 ports 3 pipe box (up to 5,6 kW per port).

CZ-P856HR3

Panels



Standard panel for 4 way 90x90 cassette, white (RAL9003).

CZ-KPU3



Econavi panel for 4 way 90x90 cassette, white (RAL9003).

CZ-KPU3A



NEW Standard panel for 4 way 90x90 cassette, graphite black (RAL9011).

CZ-KPU3B



Panel for 4 way 60x60 cassette - MY3.

CZ-KPY4





Panel for ML1 22 to 56.

CZ-02KPL2

Panel for ML1 73.

CZ-03KPL2



CZ-KPD2

Sensors









Econavi energy saving sensor.

CZ-CENSC1

Remote temperature sensor.

CZ-CSRC3

Fresh air-intake kit.

CZ-FDU3+CZ-ATU2

R32 safety measures



Leak detector for 4 way 90x90 cassette, 4 way 60x60 cassette, and wall-mounted units.

CZ-CGLSC2



R32 refrigerant leak alarm for adaptive duct and slim duct units.

CZ-CGLALC1



2-pipe safety valve kit.

CZ-P1160SVK



External 16 V power supply.

PAW-16DC-ALC1

IAQ filter for adaptive ducted unit





BION air pollutant filter for MF3 15 to 56.

PAW-APF800F

BION air pollutant filter for MF3 60 and 73.

PAW-APF1000F

BION air pollutant filter for MF3 90 to 160.

PAW-APF1400F

Plenums



Air outlet plenum for MF3 15, 22, 28, 36, 45 and 56.

CZ-56DAF2

Air outlet plenum for MF3 60, 73 and 90.

CZ-90DAF2

Air outlet plenum for MF3 112, 140 and 160.

CZ-106DAF2



Air outlet plenum for S-224ME1E5.

CZ-TREMIESPW705

Air outlet plenum for S-280ME1E5.

CZ-TREMIESPW706



Valves

External valve for MK3 15 to 73.

CZ-P73SVK3*

External valve for MK3 106.

CZ-P106SVK3

Rap valve kit.

CZ-P160RVK2

^{*} A 3/8" to 1/4" reducer is required when combining the S-73MK3E with ECOi EX R410A outdoor units (ME2 and MF3).

VRF Smart Connectivity+





Remote controller Panasonic Net Con, RH, No PIR, R1/R2.

SER8150R0B1194

Remote controller Panasonic Net Con, RH, PIR, R1/R2.

SER8150R5B1194



Wireless ZigBee® Pro module / Green Com card.

VCM8000V5094P



Door/window wireless sensor.

SED-WDC-G-5045



Wall/ceiling motion/temperature/humidity sensor.

SED-MTH-G-5045



CO₂ sensor.

SED-C02-G-5045



Sensor with room temperature and humidity.

SED-TRH-G-5045



Water leakage sensor.

SED-WLS-G-5045



Cover frame. Silver.

FAS-00



Cover frame. White.

FAS-01



Cover frame. Glossy translucent

white.

FAS-03



Cover frame. Light tan wood.

FAS-05



Cover frame. Dark brown wood.

FAS-06



Cover frame. Dark black wood.

FAS-07



Cover frame. Brushed steel finish.

FAS-10

Controller and touch controllers for hotels with dry contacts





Modbus RS-485 touch room controller with I/O, white.

PAW-RE2C4-MOD-WH

Touch display control with 2 digital inputs, white.

PAW-RE2D4-WH



Modbus RS-485 touch room controller with I/O, black.

PAW-RE2C4-MOD-BK

Touch display control with 2 digital inputs, black.

PAW-RE2D4-BK

Hotel sensors for dry contacts



Wall silent motion sensor 24 V.

PAW-WMS-DC

Wall silent motion sensor 240 V

PAW-WMS-AC



Ceiling silent motion sensor

24 V.

PAW-CMS-DC

Ceiling silent motion sensor

240 V AC.

PAW-CMS-AC



Power supply 24 V.

PAW-24DC



Door or window contact.

PAW-DWC

Centralised controls



System controller for 64 indoor units with weekly timer.

CZ-64ESMC3



Central ON / OFF controller, up to 16 groups, 64 indoor units.

CZ-ANC3



Intelligent controller (touch screen/web server) to control up to 256 indoors with included load distribution ratio (LDR).

CZ-256ESMC3

Centralised controls. BMS system. PC base





P-AIMS core software: Centralised software to control up to 1024 indoor units.

CZ-CSWKC2

P-AIMS communication adaptor.

CZ-CFUNC2

P-AIMS consumption calculation extension.

P-AIMS BACnet extension.

CZ-CSWBC2

P-AIMS layout display extension.

CZ-CSWGC2

CZ-CSWAC2

P-AIMS web application extension.

CZ-CSWWC2

Panasonic AC Smart Cloud





ALL REFERENCES RELATED TO AC SMART **CLOUD IS IN THE DEDICATED PAGE**

Panasonic AC Smart Cloud. Cloud internet control. Up to 128 groups. Controls 128 units.

CZ-CFUSCC1

BMS interface with S-Link





A unified interface supporting Modbus, BACnet, and KNX protocols for up to 16 indoor units.

PAW-AC2-BMS-16

A unified interface supporting Modbus, BACnet, and KNX protocols for up to 64 indoor units.

PAW-AC2-BMS-64

A unified interface supporting Modbus, BACnet, and KNX protocols for up to 128 indoor units.

PAW-AC2-BMS-128

Accessories interfaces





Commercial Wi-Fi Adaptor.

CZ-CAPWFC2



KNX interface (Intesis).

PAW-RC2-KNX-1i



Modbus RTU interface (Intesis).

PAW-RC2-MBS-1



Modbus RTU interface to control 4 indoor/groups (Intesis).

PAW-RC2-MBS-4



BACnet IP and MSTP (Intesis).

PAW-RC2-BAC-1



KNX interface (Airzone).

PAW-AZRC-KNX-1



Modbus RTU interface (Airzone).

PAW-AZRC-MBS-1



BACnet IP and MSTP interface (Airzone).

PAW-AZRC-BAC-1



RAC interface adapter for integration into S-Link, plus external input and alarm/ status output.

CZ-CAPRA1



CZ-CLNC2



LonWorks® Interface controls up to 16

groups and 64 indoor units.

384

Centralised controls. Connection with general equipment



Adaptor for ON / OFF control of external devices.

CZ-CAPC3



Demand control for Mini ECOi (LZ2. LE2).

CZ-CAPDC3



Mini series parallel device controlling indoor units, maximum 1 group and 8 indoor unit.

CZ-CAPBC2



Communication Adaptor. Up to 128 groups. Controls 128 units.

CZ-CFUNC2

Individual controls



CONEX wired remote controller (non-wireless), white.

CZ-RTC6W



CONEX wired remote controller with Bluetooth®, white.

CZ-RTC6WBL



CONEX wired remote controller with Wi-Fi and Bluetooth®, white.

CZ-RTC6WBLW2*



CONEX wired remote controller (non-wireless), black.

CZ-RTC6



CONEX wired remote controller with Bluetooth®, black.

CZ-RTC6BL



CONEX wired remote controller with Wi-Fi and Bluetooth®. black.

CZ-RTC6BLW2*



Design wired remote controller with Econavi function.

CZ-RTC5B



Infrared remote controller and receiver for 4 way 60x60 cassette - MY3 with panel.

CZ-RWS3 + CZ-RWRY3











Infrared remote controller and receiver for 4 way 90x90 cassette.

CZ-RWS3 + CZ-RWRU3



CZ-RWS3 + CZ-RWRL3

Infrared remote controller and receiver for 1 way cassette.

CZ-RWS3 + CZ-RWRD3



Infrared remote controller and receiver for ceiling.

CZ-RWS3 + CZ-RWRT3



Infrared remote controller for wall-mounted and floor console.

CZ-RWS3



Infrared remote controller and receiver for all indoor units.

CZ-RWS3 + CZ-RWRC3

* Available for indoor unit types MY3, MF3, MM2, and MK3.

Accessories PCB




T10 interface PCB with digital and relay connections.

PAW-T10

PCB for fan speed control of external EC Fan.

PAW-ECF

R-22 Replacement Kit




Replacement kit for R-22.

CZ-SLK2

Accessories cables





Cable for all the T10 functions.

CZ-T10



Cable to operate external EC fan.

PAW-FDC



Cable for all option monitoring signals.


PAW-0CT



Cable with force thermo OFF/ leakage detection.

PAW-EXCT

Water heat exchanger accessories



Stacking kit for vertically stacking up to 3 WHE (4 pieces per Kit).

PAW-3WSK

Advanced energy recovery ventilation - ZY Series accessories



Replacement high efficiency filter for FV-15ZY1G.

FV-FP15ZY1G

Replacement high efficiency filter for FV-35ZY1G.

FV-FP35ZY1G

Replacement high efficiency filter for FV-65ZY1G.

FV-FP65ZY1G

Replacement high efficiency filter for FV-1KZY1G and FV-2KZY1G $^{1\mathrm{J}}.$

FV-FP1KZY1G

Replacement high efficiency filter for FV-25ZY1G.

FV-FP25ZY1G

Replacement high efficiency filter for FV-50ZY1G.

FV-FP50ZY1G

Replacement high efficiency filter for FV-80ZY1G and FV-1HZY1G $^{1)}$.

FV-FP80ZY1G

IAQ Controller.

PAW-ERV-IAQCT

^{1) 2} sets of filters required for those models.