


PAC*i*

Panasonic Commercial air to air

Panasonic has developed an impressive range of highly efficient Commercial Air Conditioners. This range confirms our commitment to the environment, with our highly efficient Inverter compressor technology to optimise performance.

Highlighted features	→ 156
Product quality and safety	→ 158
PACi NX Series	→ 160
PACi NX Series 4	→ 162
CONEX. Devices and apps	→ 164
Commercial Wi-Fi Adaptor	→ 165
Bringing nature's balance indoors	→ 166
PACi NX 4 way 90x90 cassette - PU3	→ 168
PACi NX adaptive ducted unit - PF3	→ 170
PACi NX wall-mounted, 4 way 60x60 cassette and ceiling	→ 172
Solutions for server rooms applications	→ 174
Commercial units range	→ 176
Wall-mounted Professional Inverter -25 °C	→ 178
Elite - Standard wall-mounted · R32	→ 180
Elite - Standard 4 way 60x60 cassette · R32	→ 184
Elite - Standard 4 way 90x90 cassette · R32	→ 186
Elite - Standard ceiling · R32	→ 190
Elite - Standard adaptive ducted unit · R32	→ 194
High static pressure hide-away 20,0-25,0 kW · R32	→ 198

Commercial PACi NX Multi	→ 200
Commercial twin, triple and double-twin systems · R32	→ 202
Hydronic PACi	
PRO-HT Tank Series for PACi	→ 206
Panasonic PACi with Water Heat Exchanger	→ 210
R22 Renewal. Fast, easy to install and cost effective	→ 214
Accessories and control	→ 218



Highlighted features

PACi: Commercial air to air. The compact and high efficiency solution for shops, restaurants, offices or residential applications.



Great savings and improved comfort. Panasonic has developed an impressive range of highly efficient Commercial air conditioners, with our highly efficient Inverter compressor technology to optimise performance.

A wide range for industry, office or residential application. With configuration from 1:1 to 4:1, Panasonic can offer the most comfortable climate with solutions designed for every environment.

The diverse array of connectivity and control systems allows you to manage your units whether locally or remotely. Receive real-time status updates and maintenance alerts, while optimising costs and energy usage.

Energy saving



R32 refrigerant.

Our heat pumps containing R32 refrigerant show a drastic reduction in the value of Global Warming Potential (GWP). An important step to reduce greenhouse gases. R32 is also a component refrigerant, making it easy to recycle.



Exceptional seasonal cooling efficiency based on the ErP regulation.

Higher SEER ratings mean greater efficiency and year-round cooling savings!



Exceptional seasonal heating efficiency based on the ErP regulation.

Higher SCOP ratings mean greater efficiency and year-round heating savings!



Econavi.

Intelligent human activity sensor and sunlight sensor technologies that can detect and reduces the waste of energy by optimising air conditioner operation according to room conditions. With just one touch of a button, you can save energy.



Inverter Plus system.

Inverter Plus system classification highlights Panasonic's highest performing systems.



Inverter.

The Inverter range provides greater efficiency and comfort. Provides more precise temperature control, without highs and lows, and keeps the ambient temperature constant with lower energy consumption and a significant reduction in noise and vibration levels.



High efficiency compressor.

Panasonic Big PACi has compressors that operate with a wider Hz range realize a more efficient operation throughout the year.



Panasonic R2 rotary compressor.

Designed to withstand extreme conditions, it delivers high performance and efficiency.



Better efficiency and value for domestic hot water.

PRO-HT tank energy efficiency class up to A+ in a scale from A+ to F.



Better efficiency and value for low temperature applications.

On an energy efficiency scale from D to A++, both the PACi Water Heat Exchanger and the PRO-HT provide A++ rated heating.

High performance and indoor air quality



Down to -20 °C in cooling mode.

The air conditioner works in cooling mode when the outdoor temperature of -20 °C.



Down to -20 °C in heating mode.

The air conditioner works in heat pump mode when the outdoor temperature is as low as -20 °C.



nanoe™ X.

Technology with the benefits of hydroxyl radicals has the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise.



Super Quiet.

With Super Quiet technology our devices are quieter than a library (30 dB(A)).



DC fan.

Safe and precise.



Filter included.

Hide-away with filter included.



High temperature.

With PRO-HT Tank, maximum water outlet temperature up to 65 °C.



Bluefin.

Panasonic Big PACi has extended the life of its condensers with an original anti-rust coating.



Large fan.

Panasonic Big PACi large fan provides larger air flow rate and very quiet operation at low speed.



More comfort with Aerowings.

Wall-mounted YKEA direct air flow to the ceiling, creating a shower cooling effect with built-in twin flap.



DHW.

With PRO-HT Tank you can also heat your domestic hot water at a very low cost with the optional hot water cylinder.



-20 °C operating range.

The PRO-HT Tanks work with an outdoor temperature as low as -20 °C.



Up to 46 °C in cooling mode.

PACi with Water Heat Exchanger system works in cooling mode at outdoor temperature up to 46 °C.



R410A/R22 renewal.

The Panasonic renewal system allows good quality existing R410A or R22 pipe work to be re-used whilst installing high efficiency R32 systems.



5 Years compressor warranty.

We guarantee the outdoor unit compressors in the entire range for five years.

High connectivity



Panasonic AC Smart Cloud.

The AC Smart Cloud from Panasonic allows you to have complete control of all your installations. In a simple click, receive status updates from all your units in real-time, preventing breakdowns and optimising costs.



Internet control.

A next generation system providing user-friendly remote control of air conditioning or heat pump units from everywhere, using a simple Android™ or iOS smartphone, tablet or PC via the internet.



BMS connectivity.

The communication port can be integrated into the indoor unit and provides easy connection to, and control of, your Panasonic heat pump to your home or building management system.



Domestic integration to S-Link - CZ-CAPRA1.

Can connect RAC range to S-Link. Full control is now possible.



Advanced control.

A touch screen remote controller is included as a standard. Clean design, easy operation and quick access to all menus.

Product quality and safety

All Panasonic air conditioners undergo strict quality and safety tests before sale. This rigorous process includes obtaining all necessary safety approvals, to ensure that all air conditioners we sell are not only built to the highest market standards, but are also completely safe.



Professional air conditioners with R32 refrigerant.

Panasonic recommends R32, with lower Global Warming Potential (GWP). Compared to R22 and R410A, R32 has a low potential impact on global warming.

Panasonic takes action in helping to protect the environment. In line with the European countries participating in the Montreal Protocol, protecting the ozone layer and preventing global warming, Panasonic is leading the switch to R32.

1 Installation innovation

- Extremely easy to install, practically the same as R410A
- Single substance refrigerant, which makes it easier to recycle and reuse

2 Environmental innovation

- Zero impact on the ozone layer
- 75% less impact on global warming

3 Economic and energy consumption innovation

- Lower cost and greater savings
- Higher energy efficiency than R410A



PACi NX Elite: Top-tier commercial air conditioning

Outstanding performance at extreme ambient temperatures with very high energy efficiency both in heating and cooling. Fans, fan motors, compressors and heat exchangers engineered for maximum savings result in higher seasonal efficiencies, which ranks as one of the best in the industry, ensuring reduced CO₂ emissions, energy consumption and operating costs.

From 3,6 to 14,0 kW.

- Meeting all necessary approvals to ensure quality and safety
- Top class SEER: 8,9 A+++ / SCOP: 5,1 A+++ at 3,6 kW (in 90x90 cassette)

- Cooling operation is possible with outdoor temperature as high as 48 °C (for 7,1 kW and higher capacities)
- Precise control with DC Inverter technology for even more energy saving
- Cooling operation at -20 °C (10,0 kW to 14,0 kW with 30 m maximum pipe length)
- Heating operation at ambient temperature as low as -20 °C
- Compact outdoor units
- Auto restart after power outage
- Twin, triple and double-twin connections

PACi NX Standard: For economy and value

With high quality design and engineering, the PACi NX Standard are the perfect solutions for projects which demand quality on a limited budget. In addition, compact and lightweight design makes them ideal for installations with limited space including small commercial and residential applications. The slim and lightweight outdoor unit design enables installation even in very challenging locations.

From 2,5 to 14,0 kW.

- Extended range of outdoor units starting from 2,5 kW

- Great balance of system cost and performance
- Top class SEER / SCOP in the standard Inverter category SEER: 8,1 A++ / SCOP: 4,8 A++ at 3,6 kW (in 90x90 cassette)
- Variety of individual and central controllers which provides full flexibility
- Compact outdoor units, small footprint and lightweight
- Twin connection possible from 10,0 to 14,0 kW
- Cooling operation down to -10 °C and heating operation down to -15 °C

Big PACi Elite R32

20,0 – 25,0 kW is ideally suited for small and mid retail applications.

In addition to its lightweight, split-able, compact body, the hide-away unit enables easy installation and pipe work within a narrow void.

Panasonic Big PACi: Environmental friendly, strong and flexible.

- High efficiency with Panasonic compressor as the driving force

- Compact and light indoor body
- Easy pipe work with split-able hide-away indoor design
- Separable indoor unit allows for flexible installation to fit in narrow void
- Water heat exchanger and AHU connection compatibility
- Bluefin anti-corrosion coating of the heat exchanger as standard
- Wide range of controls including Cloud Control compatibility

PACi NX Series. The next generation is here


NX Series with R32 refrigerant has been developed to meet the demand of easy refurbishment with 3 wire method.

Integrated with IoT solutions and includes nanoe™ X function as standard.




1 PACi NX Series for absolute ease of refurbishment

This series have been developed with 3 wire power and communication. It makes it simple and easy to replace old systems with 3 wire connections, which is prevalent in many systems.



2 CONEX with IoT integration

The wired remote controller series is fully integrated with IoT solutions developed by Panasonic. Detailed operation, maintenance setting and service operation are all possible with smartphone or tablet.




3 Let Panasonic take care of indoor air quality

Thanks to the nanoe™ X properties, several types of pollutants can be inhibited such as certain types of bacteria, viruses, mould, allergens, pollen and certain hazardous substances. This unique technology is equipped to provide better air quality whether residential or commercial.



7 effects of nanoe™ X – Panasonic unique technology.



The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect. nanoe™ X is not medical device, local regulations on building design and sanitary recommendations must be followed.

REFER TO PAGE 10 FOR MORE DETAILS AND VALIDATION DATA

4 Increasing the efficiency

The PACi NX Series have improved seasonal efficiencies in both heating and cooling versus the previous generation.

Energy class ¹⁾ and seasonal efficiency value ($\eta_{s,c} / \eta_{s,h}$) ²⁾																
Wall-mounted - PK3					4 way cassette - PY3		4 way cassette - PU3			Ceiling - PT3				Adaptive ducted - PF3		
Elite		Standard			Elite		Standard			Elite		Standard		Elite		
kW	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
2,5																
3,6	A++	A++	A++	A+	A++	A++	A++	A+	A+++	A+++	A++	A++	A++	A++	A+	A+
5,0	A++	A++	A++	A+	A++	A++	A++	A+	A++	A++	A++	A++	A++	A++	A+	A+
6,0	A++	A++	A++	A++	A++	A+	A++	A+	A++	A++	A++	A++	A++	A++	A++	A++
7,1	A++	A++	A+	A+					A++	A++	A++	A++	A++	A++	A+	A+
10,0	A++	A+	A++	A					A++	A++	A++	A+	A++	A++	A+	A+
12,5									304,3%	186,0%	267,0%	157,0%	278,4%	181,0%	241,7%	147,4%
14,0									286,6%	181,2%	257,0%	152,2%	263,3%	178,0%	228,8%	145,3%


1) Energy label scale from A+++ to D for models below 12,0 kW (EU regulation 626/2011). 2) $\eta_{s,c} / \eta_{s,h}$ values for models above 12,0 kW (EN 14826).

New PACi NX Elite Series 4




The compact chassis newly designed with one fan up to 14,0 kW, will fit in limited installation space
The slim and lightweight outdoor units can be installed in a number of compact situations.
With the unit weighting only 66 kg*, it is easy to carry and easy to install.

* For model 7,1 kW.




Highly efficient performance in a compact body

One fan outdoor units keep the excellent seasonal performance optimising three layers heat exchanger. As a result, PZH4 series provide the equivalent high seasonal performance to conventional 2 fan models.




New Elite PZH4 Series.



Conventional model with two fans.

PZH series seasonal performance.




Extended operation range up to 52 °C in cooling and down to -20 °C in heating

Upgraded PACi NX Elite Series are capable of working even in the challenging ambient conditions. Cooling operation is possible when outdoor temperature is as low as -20 °C* or as high as 52 °C.
Heating operation can also be utilized at outdoor temperatures down to -20 °C when outdoor temperature is as low as -20 °C.

* For models 10,0 ~ 14,0 kW with pipe length up to 30 m.


Cooling design operation conditions.



Long piping allowance maximum 100 m*


Increased piping length gives great design flexibility to adapt various building types and sizes.
Piping length: 100 m (10,0 to 14,0 kW), 60 m (7,1 kW)

* For models 10,0 ~ 14,0 kW.



CONEX. Devices and apps

CONEX provides comfort and control for varying user needs. Accessible, flexible and scalable with different controllers and apps. Perfectly meeting requirements of modern controls for end user, installer and service. With nanoe™ X function, technology with the benefits of hydroxyl radicals.



1 Intuitive control with stylish design

- Simple operation at a glance
- Clean face with full flat and LCD display
- Compact body, only 86x86 mm

2 Control comfort with your smartphone

- Flexible control options with IoT integration
- Panasonic H&C Control App for daily remote control operation
- Panasonic Comfort Cloud App for remote operation 24/7/365

3 Easy maintenance with service support app

- Quick and easy app set-up for system setting
- Panasonic H&C Diagnosis App enables the user to obtain detailed system operation data

* The use of apps depends on the remote controller model.


CONEX with IoT integration

CONEX

The wired remote controller series is fully integrated with IoT solutions developed by Panasonic. Detailed operation, maintenance setting and service operation are all possible with smartphone or tablet.



https://youtu.be/_USzG_9f6bk




1) A service checker interface is required when this app is used from outdoor location. Wired remote controller [CZ-RTC6WBL, CZ-RTC6BL] or CZ-RTC6BLW is required when this app is used from indoor location. Compatible with P23 and PZH3 outdoor units. 2) CZ-RTC6WBL, CZ-RTC6BL, CZ-RTC6WBLW or CZ-RTC6BLW required. 3) CZ-RTC6WBL or CZ-RTC6BLW required.

White model ¹⁾	CZ-RTC6W	CZ-RTC6WBL	CZ-RTC6WBLW
Black model	CZ-RTC6	CZ-RTC6BL	CZ-RTC6BLW
Wired connection compatible with	PACi, PACi NX, ECOi, GHP	PACi, PACi NX, ECOi, GHP	PACi NX only
Wireless functions	No wireless capability	Bluetooth®	Bluetooth® + Wi-Fi
App compatibility			
Panasonic Comfort Cloud App	—	—	✓
Panasonic H&C Control App	—	✓ PACi, PACi NX, ECOi, GHP	✓ PACi NX only
Panasonic H&C Diagnosis App ²⁾	—	✓ PACi NX only ³⁾	✓ PACi NX only ³⁾
Outdoor unit settings (remote controller connected to indoor unit)	✓ PACi NX only ³⁾	✓ PACi NX only ³⁾	✓ PACi NX only ³⁾

1) Available in Autumn 2023. 2) Compatible with U-71/100/125/140PZH3E5/8 and U-100/125/140PZ3E5/8. 3) When connected to PACi NX indoor and outdoor unit combination.

Commercial Wi-Fi Adaptor

Panasonic CZ-CAPWFC1 interface adaptor, allows connection of one or a group of indoor units to Panasonic Comfort Cloud App, which provides control, monitoring, scheduling and error alerts.



1 From 1 to 200 units

User can control up to 10 different sites, with up to 20 units / groups per site. Additionally, one adaptor can be connected to 1 indoor or to a group of up to 8 indoors.

4 Easy scheduling

Complex weekly scheduling made simple. Not only for one unit, but across multiple sites and from a smartphone.

2 Voice control compatible

When registering the unit to Panasonic Comfort Cloud App makes it compatible with most popular voice assistants.

5 Energy monitor

See the estimated power consumption and compare with other periods, to see how energy consumption can be reduced even more. Check list of units that provides consumption*.

* Function available depending on the model.

Advanced smartphone control

Control PACi, ECOi and ECO G indoor units with your smartphone from wherever and whenever you are, by using Panasonic Comfort Cloud App and Commercial Wi-Fi Adaptor. This scalable solution is ideal for one system, one site or multiple locations. Coupling the adapter with the already feature rich systems, makes it an ideal solution for residential and commercial applications.

3 Multi user


The Panasonic Comfort Cloud App allows multi-user access control. Restrict user access to specific units.

6 Error codes

Error code notification through the App, provides early notification and allows for faster repair.

Connection Diagram

Commercial Wi-Fi Adaptor wiring length is 1,9 m and connects to indoor unit via T10 connector and R1/R2 terminal connectors.



Download free app:
Panasonic Comfort Cloud App.

Other hardware requirements: Router and Internet (purchase and subscribe separately).

Panasonic Cloud Server is designed, operated and managed by Panasonic.



Input Voltage	DC 12 V (supplied from T10 connector)
Power Consumption	Maximum 2,4 W
Size (H x W x D)	120 x 70 x 25 mm
Weight	190 g (including communications lines)
Interface	1 x Wireless LAN
Wireless LAN Standard	IEEE 802,11 b/g/n
Frequency Range	2,4 GHz band
Operating range	0 ~ 55 °C, 20 ~ 80 RH%
Connectable indoor unit	1 unit
Length of communication line	1,9 m (included)

Bringing nature's balance indoors



nanoe™ X, technology with the benefits of hydroxyl radicals.

Abundant in nature, hydroxyl radicals (also known as OH radicals) have the capacity to inhibit pollutants, viruses, and bacteria to clean and deodorise. nanoe™ X technology can bring these incredible benefits indoors so that hard surfaces, soft furnishings, and the indoor environment can be a cleaner and more pleasant place to be, whether at home, work, or visiting hotels, shops and restaurants etc.



Panasonic's nanoe™ X technology takes this a step further and brings nature's detergent – hydroxyl radicals – indoors to help create an ideal environment

Thanks to the nanoe™ X properties, several types of pollutants can be inhibited such as certain types of bacteria, viruses, mould, allergens, pollen and certain hazardous substances.



1 | nanoe™ X reliably reaches pollutants.




2 | Hydroxyl radicals denature pollutants' proteins.



3 | Pollutants activity is inhibited.

What is unique about nanoe™ X?

Effective on fabrics and surfaces.



1 | At one billionth of a metre, nanoe™ X is much smaller than steam and can deeply penetrate cloth fabrics to deodorise.

Longer lifespan.



2 | Contained in tiny water particles, nanoe™ X has a long lifespan, which is about 600 seconds, to spread easily around the room.

Huge quantity.



3 | nanoe X Generator Mark 2 produces 9,6 trillion hydroxyl radicals per second. Greater amounts of hydroxyl radicals contained in nanoe™ X lead to higher performance on inhibition of pollutants.

Maintenance-free.



The image shows nanoe X Generator Mark 3.

4 | No service and maintenance required. nanoe™ X is a filter free solution that does not require maintenance, as its atomisation electrode is enveloped with water during its generation process and it is made with Titanium.

7 effects of nanoe™ X – Panasonic unique technology

Deodorises	Capacity to inhibit 5 types of pollutants	Moisturises
Odours	Bacteria and viruses	Skin and hair
Mould	Allergens	Pollen
Hazardous substances	Hazardous substances	Hazardous substances

* Refer to <https://aircon.panasonic.eu> for more details and validation data.

nanoe™ X, internationally-validated technology in testing facilities.

The effectiveness of nanoe™ X technology has been tested by 3rd party laboratories in Germany, France, Denmark, Japan and China.

The nanoe™ X performance varies depending on the room size, environment and usage and it may take several hours to reach the full effect. nanoe™ X is not medical device, local regulations on building design and sanitary recommendations must be followed. Test results conducted under controlled laboratory conditions. Performance of nanoe™ X might differ in real life environment.

	Tested contents	Generator	Result	Capacity	Time	Testing organisation	Report No.
Airborne	Virus	Influenza (H1N1)	Mark 2	98,3% inhibited	30 m³	1,5 h	China Electronic Product Reliability and Environmental Testing Research Institute
		Bacteriophage ΦX174	Mark 1	99,7% inhibited	Approx. 25 m³	6 h	Kitasato Research Center for Environmental Science
	Bacteria	Staphylococcus aureus	Mark 1	99,9% inhibited	Approx. 25 m³	4 h	Kitasato Research Center for Environmental Science
Adhering	Virus	SARS-CoV-2	Mark 1	91,4% inhibited	6,7 m³	8 h	Texcell (France)
		SARS-CoV-2	Mark 1	99,9% inhibited	45 L	2 h	Texcell (France)
		Bacteriophage ΦX174	Mark 1	99,8% inhibited	Approx. 25 m³	8 h	Japan Food Research Laboratories
		Xenotropic murine leukemia virus	Mark 1	99,999% inhibited	45 L	6 h	Charles River Biopharmaceutical Services GmbH
		Coxsackie virus (CA16)	Mark 2	99,9% inhibited	30 m³	4 h	China Electronic Product Reliability and Environmental Testing Research Institute
	Bacteria	Staphylococcus aureus	Mark 1	99,9% inhibited	20 m³	8 h	Danish Technological Institute
Pollen	Cedar	Mark 2	99% inhibited	23 m³	12 h	Panasonic Product Analysis Center	
	Ambrosia pollen	Mark 1	99,4% inhibited	20 m³	8 h	Danish Technological Institute 868988	
Odours	Cigarette smoke odour	Mark 1	Odour intensity reduced by 2,4 levels	Approx. 23 m³	0,2 h	Panasonic Product Analysis Center	4AA33-160615-N04


First nanoe™ device was developed by Panasonic in 2003

Generator: nanoe™

2003

480 billion hydroxyl radicals/sec

Ion particle structure



Hydroxyl radicals

Generator: nanoe™ X

Mark 1 - 2016

4,8 trillion hydroxyl radicals/sec


Mark 2 - 2019

9,6 trillion hydroxyl radicals/sec


NEW Mark 3 - 2022

48 trillion hydroxyl radicals/sec


10x times




20x times



100x times



nanoe™ X: improving protection 24/7



Acts to clean your air, so that the indoor environment can be a cleaner and more pleasant place to be all day long. nanoe™ X works together with heating or cooling function when you are at home and can work independently when you are away.

Give the air conditioning the strength to increase the protection at home with nanoe™ X technology and convenient control via the Panasonic Comfort Cloud App.



Cleans the air when you are away.

Leave the nanoe™ mode ON to inhibit certain pollutants and deodorise before you return home.

Improves your environment when you are at home.

Enjoy a cleaner, comfortable space with loved ones.

Panasonic Heating & Cooling Solutions is incorporating nanoe™ technology in a wide range of equipment



Wall-mounted.
Built-in nanoe X Generator Mark 2.



Ceiling.
Built-in nanoe X Generator Mark 2.



4 Way 60x60 cassette.
Built-in nanoe X Generator Mark 2.



Adaptive ducted unit.
Built-in nanoe X Generator Mark 2.



4 Way 90x90 cassette.
Built-in nanoe X Generator Mark 1.



Ceiling mounted air-e nanoe X Generator.
Built-in nanoe X Generator Mark 1.

PACi NX 4 way 90x90 cassette - PU3

These cassettes offer upgraded nanoe™ X and Econavi technologies to make the room air more comfortable and healthy and to increase the energy efficiency.





+ SEE PRODUCT SPECIFICATIONS

1 Improved indoor air quality with nanoe™ X and fresh air intake

- nanoe™ X technology equipped as standard for improved indoor air quality
- Internal cleaning function for the unit with nanoe™ X
- High external fresh air intake volume with optional kit (CZ-FDU3 + CZ-ATU2)

2 Superior energy efficiency and comfort

- High seasonal efficiency both in heating and cooling, maximum SEER: 8,9 A+++ / SCOP: 5,1 A+++*
- Econavi: Intelligent sensors to increase energy savings and comfort
- Super quiet operation down to 27 dB(A)

* For 3,6 kW model.

3 Easy installation

- Light weight, easy piping and integrated drain pump for quick installation
- Wired remote controller CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®

Always fresh and clean air with nanoe™ X

The 4 way 90x90 cassette with nanoe™ X, when tested, has shown to inhibit hazardous substances by 92%, when compared to natural reduction*.

In addition to the 7 effects of nanoe™ X, the indoor unit can also be cleaned with a short operation of nanoe™ X + dry mode.

* Controllers (CZ-RTC5B, CZ-RTC6W/BL/BLW or CZ-RTC6/BL/BLW) are required.

After cooling / drying operation, the inside of the indoor unit is automatically dried and nanoe™ X is activated to suppress mould growth.



Operates the fan to discharge internal humidity.




Operate the fan to circulate nanoe™ X internally.

nanoe™ X effect against odour proven in large space

92% of hexadecane¹⁾ is inhibited after 8-hours exposure in room side 267 m².


Hexadecane inhabitation ratio (%).



Test ambient.

3rd party certification organization SIRIM²⁾ conducted the performance experiment of 4 way cassette equipped with nanoe X Generator Mark 1 device in inhibiting hexadecane, a chemical contaminant.


1) Hexadecane is a hazardous substance contained in gasoline and diesel exhaust gas, and considered to be one cause of oil odour. 2) SIRIM Berhad (SIRIM), a premier industrial research and technology organization in Malaysia, wholly-owned by the Ministry of Finance Incorporated.



267 m²

Optional Econavi intelligent sensor

Human activity sensor and floor temperature sensor can reduce waste energy, by optimising air conditioner operation.




Advanced Econavi functions.

2 sensors (movement and floor temperature) can provide a reduction in wasted energy by means of effective control. The floor temperature can be detected with a ceiling height of 5 m.

INTELLIGENT ECO SENSORS
ECONAVI

Econavi exclusive panel. Optional (CZ-KPU3AW)



Movement sensor.

This sensor detects the amount of human activity, and operates effectively.



Wired remote controller CZ-RTC5B, CZ-RTC6W/BL/BLW or CZ-RTC6/BL/BLW is required.

PACi NX adaptive ducted unit - PF3

The adaptive ducted units provide better flexibility with both installation possibilities, horizontal and vertical. The powerful external static pressure, maximum 150 Pa.





nanoe™ X

SEE PRODUCT SPECIFICATIONS

1 Highly flexible installation

2 installation possibilities
(horizontal / vertical).

2 installation possibilities (horizontal / vertical)

Vertical installation is available.
External static pressure 150 Pa,
sufficient for remotely installing
units away from the rooms.



2 High seasonal performance with slim body


Maximum SEER: 7,4 A++¹⁾ /
SCOP: 4,7 A++²⁾.

1) For 10,0 kW model. 2) For 7,1 kW model.

3 Comfort operation

Super quiet operation,
minimum 22 dB(A)*.

* 3,6 kW model and when operating with external
static pressure 50 Pa in low fan mode.




Selectable inlet air position

Inlet air position may be adjusted by means of a removable panel, to allow rear or bottom entry, depending on the duct installation.

Improved drain pan design

Just one drain pan for both
horizontal and vertical
installations. No need to
modify the unit.



Maximum efficiency

Energy class¹⁾ and seasonal efficiency value ($\eta_{s,c} / \eta_{s,h}$)²⁾

	kW	3,6	5,0	6,0	7,1	10,0	12,5	14,0
Elite		A++	A++	A++	A++	A++	281,7%	275,9%
		A+	A+	A++	A++	A+	170,0%	171,0%
Standard		A+	A++	A++	A++	A++	257,4%	252,2%
		A+	A+	A++	A+	A	142,6%	140,6%

1) Energy label scale from A+++ to D for models below 12,0 kW (EU regulation 626/2011). 2) $\eta_{s,c} / \eta_{s,h}$ values for models above 12,0 kW (EN 14825).

Compact body

- Only 250 mm high
- Light units from 25 to 39 kg

Conventional model	Adaptive ducted
33 kg	30 kg
290 mm	250 mm

Adaptive ducted




Better indoor air quality with nanoe™ X

The performance of nanoe™ X technology is maintained,
even with 10 m long ducts*.

The effect of improved air quality is sufficient to allow for
numerous duct shapes to fit the application.


* Panasonic internal survey.



nanoe™ X effect against odour proven in large space

In a room of 139 m², tobacco odour is reduced by a factor of 0,7 when compared to natural reduction over a period of 2 hours.


Tobacco deodorisation ratio.



Test ambient.

3rd party international testing
institute KAKEN¹⁾ conducted
the performance experiment of
Adaptive ducted equipped with
nanoe X Generator Mark 2
device removing tobacco odour.

1) KAKEN TEST CENTER General
Incorporated Foundation in Japan,
international testing institute.



PACi NX wall-mounted, 4 way 60x60 cassette and ceiling

A new era of air conditioning solutions are here, with built-in nanoe™ X technology.




PACi NX wall-mounted - PK3.

Providing a small, lightweight and low noise level design, it is ideal for small offices and other commercial applications. It also has a stylish smooth design with a washable front panel.



Air distribution is automatically altered depending on the operational mode of the unit

Air outlet angle is automatically adjusted for cooling and heating operation.



Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent dust getting into the unit and to keep the equipment clean.

PACi NX 4 way 60x60 cassette - PY3.

The PY3 not only perfectly matches with 600 x 600 mm ceiling grids but also provides an additional benefit for better indoor quality, with nanoe™ X built-in.



Industry-leading energy efficiency

- Energy class A++* with Elite outdoor range
- Energy class A++ with Standard outdoor range 2,5 kW model

* Except for 6,0 kW.

Internal cleaning function

When cooling or dry operation stopped, internal drying and nanoe™ X circulation airflow is activated in order to suppress the mould proliferation inside the unit (airflow passage, fan, heat exchanger)*.

* Depending on the installation environment or operating hours, mould proliferation or inhabitation of mould growth will be changed.

Piping outlet in six directions

Piping outlet is possible in six directions of; right, right rear, right bottom, left, left rear and left bottom, making installation flexible.



[+ SEE PRODUCT SPECIFICATIONS](#)

PACi NX ceiling - PT3.


Providing outstanding energy-saving performance, comfort and long-distance airflow distribution, these units are perfect for retail stores and schools.



Comfortable, long-distance airflow distribution

The shape of the outlet has been optimised to provide long-distance air flow distribution. Even in long rooms, air flow reaches every corner for exceptionally comfortable air conditioning.

* Results are based on specific testing conditions.



Compact looking, stylish, one-motion design

With its streamlined, one-motion form, the unit looks thin and compact when installed for a neat appearance in any room. When not operating, the louver closes to provide an elegant look while also keeping the unit clean.

Energy-saving technology delivering top-class efficiency

Optimisation of the shape of the casing and fan assures bigger air flow and higher efficiency. Energy-saving performance is top class in the industry. Thanks to new DC fan motor and large diagonal air flow fan.

[+ SEE PRODUCT SPECIFICATIONS](#)

Solutions for server rooms applications

Effectively protect your IT related spaces, 24/7, with a complete range of solutions offering redundancy control. High efficiency products provide reliable cooling all year round.



YKEA server room solution.

- Perfect solution for smaller server rooms
- Compact design
- Reaching SEER value of 9,6 (A+++)¹⁾
- High seasonal performance
- Range of capacities available
- Operation down to -25 °C ambient

1) For 3,5 kW unit.

PACi solution.

- Scalability for larger applications
- Twin, triple and double-twin options¹⁾
- Increased piping lengths of up to 90 m²⁾
- Increased sensible capacity options available
- Flexible and adaptable control options


1) Compatible with PAW-PACR4 only. 2) For Big PACi 20 kW unit.

Redundancy ensured by three different functionalities..

Computer and server rooms are very sensitive areas of application. Any downtime caused by high room temperatures must be avoided by any means. Air conditioner redundancy is one of the key points to ensure a reliable nonstop cooling operation.


1 Backup operation

When an air conditioner fails for whatever reason, another one will awake from standby mode and cover the room's cooling load.




2 Support operation

Support operation, also called cascade control, makes sure that the capacity required to cool the room is delivered by one or more units whenever required. When the capacity of 1 air conditioner is not sufficient, another one will be started to support the operation.



3 Rotation operation


Backup and support operation are key functions for a redundant operation in computer rooms. This concept implies a main system and a sub system. In order to avoid an imbalance of the operating hours of the systems, the redundancy control equalises the operation time by rotating the main and the sub systems, thus providing a "rotation operation".



Redundancy control options for 24/7/365 applications

YKEA integral solution


- Ideal solution for small server rooms, providing full redundancy functionality integrated in YKEA's remote controller (requires optional CZ-RCC5 cable set)
- Up to 2 YKEA systems connectable to 1 remote controller
- Individual alarm display for each system
- Operation can be monitored by H&C Controls App (via WLAN)
- No digital inputs/outputs



Optional interface for YKEA units

PAW-SERVER-PKEA


- Ideal solution for small server rooms, providing full redundancy functionality
- Up to 2 YKEA systems connectable to PAW-SERVER-PKEA
- Additional benefits: Operation and alarm outputs for each system, ON / OFF inputs for each system for connection to external BMS



PACi integral solution

CZ-RTC5B / CZ-RTC6W / CZ-RTC6 / CZ-RTC6WBL / CZ-RTC6BL / CZ-RTC6WBLW / CZ-RTC6BLW


- Full redundancy functionality
- Quick and easy installation using PACi group control
- Up to 2 PACi systems connectable to 1 remote controller
- Delta T setting for support operation selectable from 4 to 10 K
- Connectable to Panasonic centralised control systems
- Optional interfaces for connection to external BMS (Modbus, BACnet, KNX)



NEW Optional interface up to 4 indoor units PACi or VRF

PAW-PACR4

- Redundancy control up to 4 indoor unit groups
- Actual unit operation / alarm status can be displayed
- Common digital alarm / operation status output
- For each support operation level, individual temperature thresholds can be set (cascade control)
- Room temperature display (by device's own temperature sensor)
- Modbus connection (up to 4 PAW-RC2-MBS-1)
- Available external inputs (ON / OFF, heating/cooling change, fire prevention contact)




Commercial units range

Page	Indoor units	2,5 kW	3,6 kW	4,5 kW ¹⁾	5,0 kW	6,0 kW
P. 178	Wall-mounted Professional · R32 ²⁾					
P. 180	PACi NX wall-mounted · R32					
P. 184	PACi NX 4 way 60x60 cassette · R32					
P. 186	PACi NX 4 way 90x90 cassette · R32					
P. 190	PACi NX ceiling · R32					
P. 194	PACi NX adaptive ducted · R32					
P. 198	High static pressure hide-away 20-25 kW · R32					
Outdoor units	2,5 kW	3,6 kW		5,0 kW	6,0 kW	
PACi NX Elite · R32						
		U-36PZH3E5		U-50PZH3E5	U-60PZH3E5	
PACi NX Standard · R32						
		U-25PZ3E5	U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A	

1) The 4,5 kW indoor capacity options are only available only for twin, triple and double-twin combinations. 2) Not compatible with PACi NX outdoors and accessories. Domestic range sales conditions may apply. Check with your sales representative. 3) These two units are not in PACi NX range but part of Big PACi range. * U-__E5 Single phase / U-__E8 Three phase.

+ OPTIONAL UNITS ON VENTILATION SECTION

7,1 kW**10,0 kW****12,5 kW****14,0 kW****20,0 kW****25,0 kW**

CS-Z71YKEA



S-6010PK3E



S-6010PK3E



S-6071PU3E



S-1014PU3E



S-1014PU3E



S-1014PU3E



S-6071PT3E



S-1014PT3E



S-1014PT3E



S-1014PT3E



S-6071PF3E



S-1014PF3E



S-1014PF3E



S-1014PF3E



S-200PE3E5B



S-250PE3E5B

7,1 kW**10,0 kW****12,5 kW****14,0 kW****20,0 kW****25,0 kW**

U-71PZH4E5 / U-71PZH4E8



U-100PZH4E5 / U-100PZH4E8



U-125PZH4E5 / U-125PZH4E8



U-140PZH4E5 / U-140PZH4E8

U-200PZH2E8³⁾U-250PZH2E8³⁾

U-71PZ3E5A



U-100PZ3E5 / U-100PZ3E8



U-125PZ3E5 / U-125PZ3E8



U-140PZ3E5 / U-140PZ3E8

YKEA series for server rooms

High efficiency products for 24/7 applications. Panasonic has developed a complete range of solutions for server rooms which efficiently protect your servers, keeping them at an appropriate temperature even when the outdoor temperature is below -25 °C.



1 Designed for 24h/7d a week operation


High efficiency all year round. This wall-mounted air conditioner is designed for professional, critical applications such as computer rooms where reliable cooling inside the room is necessary even with extreme ambient conditions.

3 Highest energy rating in cooling


The SEER and SCOP of the Server room unit has been further improved to achieve top class energy efficiency. The 3,5 kW unit reaches now the SEER value of 9,6 (A+++).

4 Built-in Wi-Fi and compatible with Voice Assistant

The unit is ready to connect to the internet and to be controlled by smartphone with Panasonic Comfort Cloud App. Control, monitor energy consumption statistics and easily identify errors in case of failure.




Not compatible with PACi NX outdoors and accessories. Domestic range sales conditions may apply. Check with your sales representative.



Wall-mounted Professional -25 °C · R32

- Designed for 24h/7d a week operation
- Wired remote controller, with optional duty rotation mode
- Improved SEER / SCOP to achieve top class energy efficiency
- Aerowings 2.0, for a better control of the airflow
- Built-in Wi-Fi for instant connectivity via Panasonic Comfort Cloud App
- Compatible with Google Assistant and Amazon Alexa
- Chassis and parts designed for easier installation



Kit		KIT-Z25-YKEA	KIT-Z35-YKEA	KIT-Z42-YKEA	KIT-Z50-YKEA	KIT-Z71-YKEA
Cooling capacity	Nominal (Min - Max)	kW	2,50 [0,85 - 3,50]	3,50 [0,85 - 4,20]	4,20 [0,85 - 5,00]	5,00 [0,98 - 6,00]
EER ¹⁾	Nominal (Min - Max)	W/W	4,90 [4,72 - 3,98]	4,12 [4,72 - 3,68]	3,82 [4,72 - 3,25]	3,68 [3,92 - 3,16]
SEER ²⁾			9,5 A+++	9,6 A+++	8,6 A+++	8,6 A+++
Pdesign		kW	2,50	3,50	4,20	5,00
Input power	Nominal (Min - Max)	kW	0,51 [0,18 - 0,88]	0,85 [0,18 - 1,14]	1,10 [0,18 - 1,54]	1,36 [0,25 - 1,90]
Annual energy consumption ³⁾		kWh/a	92	128	171	203
Heating capacity	Nominal (Min - Max)	kW	3,40 [0,85 - 5,00]	4,00 [0,85 - 5,80]	5,30 [0,85 - 6,80]	5,80 [0,98 - 8,00]
Heating capacity at -7 °C		kW	3,05	3,40	4,11	4,80
COP ¹⁾	Nominal (Min - Max)	W/W	4,86 [4,72 - 3,97]	4,44 [4,72 - 3,87]	3,93 [4,72 - 3,66]	4,08 [4,26 - 3,35]
SCOP ²⁾			4,6 A++	4,6 A++	4,5 A+	4,6 A++
Pdesign at -10 °C		kW	2,70	3,20	3,60	4,20
Input power	Nominal (Min - Max)	kW	0,70 [0,18 - 1,26]	0,90 [0,18 - 1,50]	1,35 [0,18 - 1,86]	1,42 [0,23 - 2,39]
Annual energy consumption ³⁾		kWh/a	822	974	1120	1278
Indoor unit		CS-Z25YKEA	CS-Z35YKEA	CS-Z42YKEA	CS-Z50YKEA	CS-Z71YKEA
Power supply	V	230	230	230	230	230
Recommended fuse	A	16	16	16	16	20
Connection indoor / outdoor	mm ²	4x1,5	4x1,5	4x1,5	4x2,5	4x2,5
Air flow	Cool / Heat	m ³ /min	11,4/13,8	12,7/14,8	13,2/15,2	17,4/19,1
Moisture removal volume		L/h	1,5	2,0	2,4	2,8
Sound pressure ⁴⁾	Cool (Hi / Lo / Q-Lo)	dB(A)	39/25/21	42/28/21	43/32/29	44/37/30
	Heat (Hi / Lo / Q-Lo)	dB(A)	41/27/22	43/30/22	44/35/29	44/37/30
Sound power	Cool / Heat (Hi)	dB(A)	55/57	58/59	59/60	60/60
Dimension	HxWxD	mm	295x870x229	295x870x229	295x870x229	295x1040x244
Net weight	kg	11	11	11	12	13
Outdoor unit		CU-Z25YKEA	CU-Z35YKEA	CU-Z42YKEA	CU-Z50YKEA	CU-Z71YKEA
Air flow	Cool / Heat	m ³ /min	27,6/27,6	29,8/29,8	29,8/31,0	39,8/36,9
Sound pressure ⁴⁾	Cool / Heat (Hi)	dB(A)	46/48	48/50	48/51	48/50
Sound power	Cool / Heat (Hi)	dB(A)	61/63	63/65	63/66	63/65
Dimension ⁵⁾	HxWxD	mm	542x780x289	542x780x289	542x780x289	695x875x320
Net weight	kg	30	30	30	40	45
Piping diameter	Liquid	Inch [mm]	1/4 [6,35]	1/4 [6,35]	1/4 [6,35]	1/4 [6,35]
	Gas	Inch [mm]	3/8 [9,52]	3/8 [9,52]	1/2 [12,70]	1/2 [12,70]
Pipe length range		m	3~20	3~20	3~20	3~30
Elevation difference (in / out)		m	15	15	15	20
Pre-charged pipe length		m	7,5	7,5	7,5	7,5
Additional gas amount	g/m	10	10	10	15	25
Refrigerant (R32) / CO ₂ Eq.	kg / T	0,89/0,60	0,89/0,60	0,97/0,65	1,13/0,76	1,35/0,91
Operating range	Cool Min ~ Max	°C	-25 ~ +43	-25 ~ +43	-25 ~ +43	-25 ~ +43
	Heat Min ~ Max	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24

1) EER and COP calculation is based in accordance to EN16511. 2) Energy Label Scale from A+++ to D. 3) The annual energy consumption is calculated in accordance to EU/626/2011. 4) The sound pressure of the indoor unit shows the value measured of a position 1 m in front of the main body and 0,8 m below the unit. For outdoor unit 1 m in front and 1 m in rear side of main body. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) Add 70 mm for piping port. * Not compatible with PACi NX outdoors and accessories. Domestic range sales conditions may apply. Check with your sales representative.

Accessories

CZ-RCC5	CN-CNT cables x2 for server room application, control of 2 units, rotation, backup, etc.
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform

Accessories

PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm



SEER: For KIT-Z35-YKEA. SCOP: For KIT-Z25-YKEA, KIT-Z35-YKEA and KIT-Z50-YKEA. SUPER QUIET: For KIT-Z25-YKEA. INTERNET CONTROL: Built-in Wi-Fi.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Elite wall-mounted - PK3 · R32

The wall-mounted units with stylish matt color can be offered for many applications such as studios, gyms, high ceiling areas and even computer server rooms.

The compact design and flat face ensure discreet installation, even in a small space.



nanoe™ X as a standard.

Single phase					
	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW
Kit	KIT-36PK3ZH5	KIT-50PK3ZH5	KIT-60PK3ZH5	KIT-71PK3ZH45	KIT-100PK3ZH45
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity	Nominal (Min - Max) kW	3,6 (1,2 - 4,0)	5,0 (1,2 - 5,6)	6,1 (1,2 - 7,1)	7,1 (2,2 - 9,0)
EER ¹⁾	Nominal (Min - Max) W/W	4,93 (4,49 - 5,45)	4,24 (3,61 - 5,45)	3,86 (3,02 - 5,45)	3,50 (2,69 - 5,79)
SEER ²⁾		8,4 A++	8,0 A++	7,2 A++	6,8 A++
Pdesign	kW	3,6	5,0	6,1	7,1
Input power	Nominal (Min - Max) kW	0,73 (0,22 - 0,89)	1,18 (0,22 - 1,55)	1,58 (0,22 - 2,35)	2,03 (0,38 - 3,35)
Annual energy consumption ³⁾	kWh/a	150	219	297	365
Heating capacity	Nominal (Min - Max) kW	4,0 (1,2 - 5,0)	5,6 (1,2 - 6,5)	7,0 (1,2 - 8,0)	8,0 (2,0 - 9,0)
COP ¹⁾	Nominal (Min - Max) W/W	4,82 (4,17 - 5,45)	4,15 (3,55 - 5,45)	4,19 (3,40 - 5,45)	4,00 (3,16 - 5,56)
SCOP ²⁾		4,9 A++	4,7 A++	4,8 A++	4,7 A++
Pdesign at -10 °C	kW	3,6	4,5	4,6	5,2
Input power	Nominal (Min - Max) kW	0,83 (0,22 - 1,20)	1,35 (0,22 - 1,83)	1,67 (0,22 - 2,35)	2,00 (0,36 - 2,85)
Annual energy consumption ³⁾	kWh/a	1029	1341	1342	1549
Indoor unit	S-3650PK3E	S-3650PK3E	S-6010PK3E	S-6010PK3E	S-6010PK3E
Air flow	Hi / Med / Lo	m³/min	13,0 / 11,0 / 9,0	16,0 / 13,5 / 11,0	20,0 / 17,5 / 14,5
Moisture removal volume		L/h	0,9	1,8	2,0
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	35/31/27	40/36/32	47/44/40
Sound power	Hi / Med / Lo	dB(A)	51/47/43	56/52/48	63/60/56
Dimension	HxWxD	mm	302 x 1120 x 236	302 x 1120 x 236	302 x 1120 x 236
Net weight	kg	13	13	14	14
nanoe™ X Generator		Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZH3E5	U-50PZH3E5	U-60PZH3E5	U-71PZH4E5	U-100PZH4E5
Power supply	V	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240
Current	Cool Heat	A	3,60 - 3,45 - 3,30 4,05 - 3,90 - 3,70	5,60 - 5,35 - 5,10 6,40 - 6,10 - 5,85	7,40 - 7,10 - 6,80 7,75 - 7,40 - 7,10
Air flow	Cool / Heat	m³/min	34,1 / 36,4	42,0 / 42,0	42,0 / 42,0
Sound pressure	Cool / Heat (Hi)	dB(A)	43/44	46/48	47/50
Sound power	Cool / Heat (Hi)	dB(A)	62/64	64/67	65/69
Dimension	HxWxD	mm	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370
Net weight	kg	42	42	43	66
Piping diameter	Liquid Gas	Inch (mm)	1/4 (6,35) 1/2 (12,70)	1/4 (6,35) 1/2 (12,70)	3/8 (9,52) 5/8 (15,88)
Pipe length range		m	3 ~ 40	3 ~ 40	5 ~ 60
Elevation difference (in / out) ⁷⁾	m		15/30	15/30	15/30
Pre-charged pipe length	m		30	30	30
Additional gas amount	g/m		15	15	30
Refrigerant (R32) / CO ₂ Eq.	kg / T		1,13/0,76	1,13/0,76	1,95/1,32
Operating range	Cool Min - Max Heat Min - Max	°C	-15 ~ +46 -20 ~ +24	-15 ~ +46 -20 ~ +24	-15 ~ +52 -20 ~ +24

Technical focus

- Modern design with flat face and compact size
- DC fan for better efficiency and control
- Six directional piping outlet
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent dust getting into the unit and to keep the equipment clean.

Quiet operation

These units are among the quietest in the industry, making them ideal for hotels and hospitals.

Piping outlet in six directions

Piping outlet is possible in six directions of right, right rear, right bottom, left, left rear and left bottom, making the installation work more flexible.



CZ-RTC5B

New
2023

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:**CONEX**

CONEX wired remote controller, white.

CZ-RTC6W/
BL/BLW**CONEX**

CONEX wired remote controller, black.

CZ-RTC6/BL/
BLWInfrared remote controller.
CZ-RWS3Econavi sensor.
CZ-CENSC1**Three phase****7,1 kW****KIT-71PK3ZH48****10,0 kW****KIT-100PK3ZH48**

Kit			
Remote controller			
Cooling capacity	Nominal [Min - Max]	kW	7,1[2,2 - 9,0]
EER ¹⁾	Nominal [Min - Max]	W/W	3,50[2,69 - 5,79]
SEER ²⁾			6,7 A++
Pdesign		kW	7,1
Input power	Nominal [Min - Max]	kW	2,03[0,38 - 3,35]
Annual energy consumption ³⁾		kWh/a	370
Heating capacity	Nominal [Min - Max]	kW	8,0[2,0 - 9,0]
COP ¹⁾	Nominal [Min - Max]	W/W	4,00[3,16 - 5,56]
SCOP ²⁾			4,7 A++
Pdesign at -10 °C		kW	5,2
Input power	Nominal [Min - Max]	kW	2,00[0,36 - 2,85]
Annual energy consumption ³⁾		kWh/a	1549
Indoor unit			S-6010PK3E
Air flow	Hi / Med / Lo	m ³ /min	20,0/17,5/14,5
Moisture removal volume		L/h	3,0
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	47/44/40
Sound power	Hi / Med / Lo	dB(A)	63/60/56
Dimension	HxWxD	mm	302 x 1120 x 236
Net weight		kg	14
nanoe X Generator			Mark 2
Outdoor unit			U-71PZH4E8
Power supply		V	380-400-415
Current	Cool	A	3,45-3,25-3,15
	Heat	A	3,40-3,20-3,10
Air flow	Cool / Heat	m ³ /min	62,0/66,0
Sound pressure	Cool / Heat (Hi)	dB(A)	48/50
Sound power	Cool / Heat (Hi)	dB(A)	65/67
Dimension	HxWxD	mm	996 x 980 x 370
Net weight		kg	66
Piping diameter	Liquid	Inch (mm)	3/8[9,52]
	Gas	Inch (mm)	5/8[15,88]
Pipe length range		m	5 ~ 60
Elevation difference (in / out) ⁷⁾		m	15/30
Pre-charged pipe length		m	30
Additional gas amount		g/m	30
Refrigerant (R32) / CO ₂ Eq.		kg / T	1,95/1,32
Operating range	Cool Min ~ Max	°C	-15 ~ +52
	Heat Min ~ Max	°C	-20 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the $\eta_{e,h} / \eta_{n,h}$ values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1 m in front of the main body and 1 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. 8) Pipe length up to 30 m. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3	Infrared remote controller

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400 x 900 x 400 mm
CZ-CENSC1	Econavi energy saving sensor



R32



A++



A++



INVERTER+

-15 °C
COOLING MODE

-20 °C
HEATING MODE



nanoe X



DC FAN



R410A / R32



OPTIONAL WI-FI



BMS CONNECTIVITY



5 YEARS COMPRESSOR WARRANTY

SEER and SCOP: For S-3650PK3E + U-36PZH3E5. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Standard wall-mounted - PK3 · R32

The wall-mounted units with stylish matt color can be offered for many applications such as studios, gyms, high ceiling areas and even computer server rooms.

The compact design and flat face ensure discreet installation, even in a small space.



Single phase						
	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	
Kit	KIT-36PK3Z5	KIT-50PK3Z5	KIT-60PK3Z5	KIT-71PK3Z5	KIT-100PK3Z5	
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	
Cooling capacity	Nominal (Min - Max) kW	3,6(1,5 - 4,0)	5,0(1,5 - 5,6)	6,1(2,0 - 7,1)	7,1(2,6 - 7,7)	9,0(3,0 - 9,7)
EER ¹⁾	Nominal (Min - Max) W/W	4,14(3,74 - 5,88)	3,52(3,03 - 6,25)	3,67(3,01 - 6,90)	3,16(2,77 - 5,00)	3,47(3,13 - 5,36)
SEER ²⁾	7,6 A++	7,4 A++	7,0 A++	5,8 A+	6,5 A++	
Pdesign	kW	3,6	5,0	6,1	7,1	9,0
Input power	Nominal (Min - Max) kW	0,87(0,26 - 1,07)	1,42(0,24 - 1,85)	1,66(0,29 - 2,36)	2,25(0,52 - 2,78)	2,59(0,56 - 3,10)
Annual energy consumption ³⁾	kWh/a	166	237	3,05	429	485
Heating capacity	Nominal (Min - Max) kW	3,6(1,5 - 4,6)	5,0(1,5 - 6,4)	6,1(1,8 - 7,0)	7,1(2,1 - 8,1)	9,0(3,0 - 10,5)
COP ¹⁾	Nominal (Min - Max) W/W	4,62(4,11 - 6,52)	4,20(3,17 - 7,50)	4,39(3,18 - 7,50)	4,23(3,38 - 6,36)	3,93(3,56 - 5,36)
SCOP ²⁾	4,5 A+	4,4 A+	4,7 A++	4,4 A+	3,9 A	
Pdesign at -10 °C	kW	2,8	4,0	4,6	5,2	9,0
Input power	Nominal (Min - Max) kW	0,78(0,23 - 1,12)	1,19(0,20 - 2,02)	1,39(0,24 - 2,20)	1,68(0,33 - 2,40)	2,29(0,56 - 2,95)
Annual energy consumption ³⁾	kWh/a	872	1273	1370	1653	3231
Indoor unit	S-3650PK3E	S-3650PK3E	S-6010PK3E	S-6010PK3E	S-6010PK3E	
Air flow	Hi / Med / Lo	m³/min	13,0/11,0/9,0	16,0/13,5/11,0	20,0/17,5/14,5	22,0/18,5/15,0
Moisture removal volume		L/h	0,9	1,8	2,0	3,0
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	35/31/27	40/36/32	47/44/40	47/44/40
Sound power	Hi / Med / Lo	dB(A)	51/47/43	56/52/48	63/60/56	65/61/57
Dimension	HxWxD	mm	302x1120x236	302x1120x236	302x1120x236	302x1120x236
Net weight	kg	13	13	14	14	14
nanoe™ X Generator		Mark 2	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A	U-71PZ3E5A	U-100PZ3E5	
Power supply	V	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240
Current	Cool Heat	A	4,05 - 3,85 - 3,70 3,65 - 3,50 - 3,35	6,60 - 6,30 - 6,05 5,60 - 5,35 - 5,10	7,70 - 7,35 - 7,05 6,45 - 6,15 - 5,90	10,4 - 10,00 - 9,55 7,80 - 7,45 - 7,15
Air flow	Cool / Heat	m³/min	33,6/34,0	32,7/31,9	42,6/41,5	44,7/45,9
Sound pressure	Cool / Heat (Hi)	dB(A)	46/47	46/46	47/48	48/49
Sound power	Cool / Heat (Hi)	dB(A)	64/66	64/64	64/65	66/68
Dimension	HxWxD	mm	619x824x299	619x824x299	695x875x320	695x875x320
Net weight	kg	32	35	42	50	83
Piping diameter	Liquid Gas	Inch (mm)	1/4 (6,35) 1/2 (12,70)	1/4 (6,35) 1/2 (12,70)	1/4 (6,35) ⁵⁾ 1/2 (12,70) ⁶⁾	3/8 (9,52) 5/8 (15,88) ⁶⁾
Pipe length range		m	3 ~ 15	3 ~ 20	3 ~ 40	5 ~ 50
Elevation difference (in / out) ⁷⁾	m	15/15	15/15	15/30	20/30	15/30
Pre-charged pipe length	m	7,5	7,5	30	30	30
Additional gas amount	g/m	10	15	15	17	45
Refrigerant (R32) / CO ₂ Eq.	kg / T	0,87/0,59	1,14/0,77	1,15/0,78	1,32/0,89	2,4/1,62
Operating range	Cool Min - Max Heat Min - Max	°C	-10 ~ +43 -15 ~ +24	-10 ~ +43 -15 ~ +24	-10 ~ +43 -15 ~ +24	-10 ~ +43 -15 ~ +24

Technical focus

- Modern design with flat face and compact size
- DC fan for better efficiency and control
- Six directional piping outlet
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent dust getting into the unit and to keep the equipment clean.

Quiet operation

These units are among the quietest in the industry, making them ideal for hotels and hospitals.

Piping outlet in six directions

Piping outlet is possible in six directions of right, right rear, right bottom, left, left rear and left bottom, making the installation work more flexible.



CZ-RTC5B

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:			
	CONEX CONEX wired remote controller, white. CZ-RTC6W/BL/BLW		
	CONEX CONEX wired remote controller, black. CZ-RTC6/BL/BLW		
	Infrared remote controller. CZ-RWS3	Econavi sensor. CZ-CENSC1	
		Three phase 10,0 kW	
		KIT-100PK3Z8	
Kit	CZ-RTC5B		
Remote controller			
Cooling capacity	Nominal (Min - Max) kW	9,0(3,0 - 9,7)	
EER ¹⁾	Nominal (Min - Max) W/W	3,47(5,36 - 3,13)	
SEER ²⁾		6,5 A++	
Pdesign	kW	9,0	
Input power	Nominal (Min - Max) kW	2,59[0,56 - 3,10]	
Annual energy consumption ³⁾	kWh/a	485	
Heating capacity	Nominal (Min - Max) kW	9,0(3,0 - 10,5)	
COP ¹⁾	Nominal (Min - Max) W/W	3,93(5,36 - 3,56)	
SCOP ²⁾		3,9 A	
Pdesign at -10 °C	kW	9,0	
Input power	Nominal (Min - Max) kW	2,29[0,56 - 2,95]	
Annual energy consumption ³⁾	kWh/a	3231	
Indoor unit		S-6010PK3E	
Air flow	Hi / Med / Lo m ³ /min	22,0/18,5/15,0	
Moisture removal volume	L/h	4,3	
Sound pressure ⁴⁾	Hi / Med / Lo dB(A)	49/45/41	
Sound power	Hi / Med / Lo dB(A)	65/61/57	
Dimension	HxWxD mm	302x1120x236	
Net weight	kg	14	
nanoe X Generator		Mark 2	
Outdoor unit		U-100PZ3E8	
Power supply	V	380-400-415	
Current	Cool A	4,30-4,10-3,95	
	Heat A	3,80-3,65-3,50	
Air flow	Cool / Heat m ³ /min	73,0/73,0	
Sound pressure	Cool / Heat (Hi) dB(A)	52/52	
Sound power	Cool / Heat (Hi) dB(A)	70/70	
Dimension	HxWxD mm	996x980x370	
Net weight	kg	83	
Piping diameter	Liquid Inch (mm)	3/8[9,52]	
	Gas Inch (mm)	5/8[15,88]	
Pipe length range	m	5~50	
Elevation difference (in / out) ⁷⁾	m	15/30	
Pre-charged pipe length	m	30	
Additional gas amount	g/m	45	
Refrigerant (R32) / CO ₂ Eq.	kg / T	2,4/1,62	
Operating range	Cool Min ~ Max °C	-10 ~ +43	
	Heat Min ~ Max °C	-15 ~ +24	
1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η _{h,c} / η _{h,b} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1 m in front of the main body and 1 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.			
Accessories		Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white	CZ-CAPWFC1	Commercial Wi-Fi Adaptor
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white	PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white	PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
CZ-RTC6	CONEX wired remote controller (non-wireless), black	PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black	PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black	CZ-CENSC1	Econavi energy saving sensor
CZ-RTC5B	Wired remote controller with Econavi function and datanavi		
CZ-RWS3	Infrared remote controller		



SEER: For S-3650PK3E + U-36PZ3E5. SCOP: For S-6010PK3E + U-60PZ3E5A. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Elite and Standard 4 way 60x60 cassette - PY3 · R32

- From 2,5 to 6,0 kW (4 capacity sizes)
- Maximum SEER: 7,3 A++ / SCOP: 4,7 A++*
- Built-in drain pump
- DC drain pump and float switch to reduce the noise
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality

* For Elite 3,6 kW model.



nanoe™ X as a standard.

		Single phase		
		3,6 kW	5,0 kW	6,0 kW
Kit		KIT-36PY3ZH5	KIT-50PY3ZH5	KIT-60PY3ZH5
Remote controller		CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity	Nominal (Min - Max)	kW	3,6 (1,2 - 4,0)	5,0 (1,2 - 5,6)
EER ¹⁾	Nominal (Min - Max)	W/W	4,50 (4,04 - 5,45)	3,76 (3,41 - 5,45)
SEER ²⁾		7,3 A++	7,0 A++	6,7 A++
Pdesign		kW	3,6	5,0
Input power	Nominal (Min - Max)	kW	0,80 (0,22 - 0,99)	1,33 (0,22 - 1,64)
Annual energy consumption ³⁾		kWh/a	400	685
Heating capacity	Nominal (Min - Max)	kW	4,0 (1,2 - 5,0)	5,6 (1,2 - 6,5)
COP ¹⁾	Nominal (Min - Max)	W/W	4,12 (3,45 - 5,45)	3,37 (2,95 - 5,45)
SCOP ²⁾		4,7 A++	4,6 A++	4,3 A+
Pdesign at -10 °C		kW	3,6	4,5
Input power	Nominal (Min - Max)	kW	0,97 (0,22 - 1,45)	1,66 (0,22 - 2,20)
Annual energy consumption ³⁾		kWh/a	1073	1370
Indoor unit		S-36PY3E	S-50PY3E	S-60PY3E
Air flow	Hi / Med / Lo	m³/min	9,5 / 7,5 / 6,0	12,0 / 9,5 / 6,5
Moisture removal volume		L/h	1,5	2,5
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	34 / 30 / 25	39 / 34 / 27
Sound power	Hi / Med / Lo	dB(A)	49 / 45 / 40	54 / 49 / 42
Dimension	Indoor (H x W x D)	mm	243 x 575 x 575	243 x 575 x 575
	Panel (H x W x D)	mm	30 x 625 x 625	30 x 625 x 625
Net weight	Indoor / Panel	kg	15 / 2,8	15 / 2,8
nanoe X Generator		Mark 2	Mark 2	Mark 2
Outdoor unit		U-36PZH3E5	U-50PZH3E5	U-60PZH3E5
Power supply	V	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240
Current	Cool	A	3,95 - 3,60 - 3,60	5,30 - 5,00 - 5,75
	Heat	A	4,75 - 4,55 - 4,35	7,85 - 7,50 - 7,20
Air flow	Cool / Heat	m³/min	34,1 / 36,4	42,0 / 42,0
Sound pressure	Cool / Heat (Hi)	dB(A)	43 / 44	46 / 48
Sound power	Cool / Heat (Hi)	dB(A)	62 / 64	64 / 67
Dimension	H x W x D	mm	695 x 875 x 320	695 x 875 x 320
Net weight	kg	42	42	43
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)	1/4 (6,35) ⁵⁾
	Gas	Inch (mm)	1/2 (12,70)	1/2 (12,70) ⁶⁾
Pipe length range	m		3 ~ 40	3 ~ 40
Elevation difference (in / out) ⁷⁾	m		15 / 30	15 / 30
Pre-charged pipe length	m		30	30
Additional gas amount	g/m		15	15
Refrigerant (R32) / CO ₂ Eq.	kg / T		1,13 / 0,76	1,13 / 0,76
Operating range	Cool Min ~ Max	°C	-15 ~ +46	-15 ~ +46
	Heat Min ~ Max	°C	-20 ~ +24	-20 ~ +24


Compact and stylish design

- Required ceiling depth of only 250 mm
- Exposed area is only 30 mm

Individual flap control

Better control of the air flow with 4 motors, providing individual flap control.

Perfect air distribution without direct airflow, to reduce the feeling of cold drafts.



SEER and SCOP: For S-36PY3E + U-36PZH3E5. ECONAVI and INTERNET CONTROL: Optional.



Panel.
CZ-KPY4

CZ-RTC5B

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION



Optional:



Standard		Single phase			
Kit		2,5 kW	3,6 kW	5,0 kW	6,0 kW
Remote controller		KIT-25PY3Z5	KIT-36PY3Z5	KIT-50PY3Z5	KIT-60PY3Z5
Cooling capacity	Nominal [Min - Max]	kW	2,5[1,5 - 3,9]	3,6[1,5 - 4,0]	5,0[1,5 - 5,6]
EER ¹⁾	Nominal [Min - Max]	W/W	4,46[3,55 - 5,88]	3,96[3,57 - 5,88]	3,50[3,03 - 6,25]
SEER ²⁾			6,5 A++	6,7 A++	7,3 A++
Pdesign		kW	2,5	3,6	5,0
Input power	Nominal [Min - Max]	kW	0,56[0,26 - 1,10]	0,91[0,26 - 1,12]	1,43[0,24 - 1,85]
Annual energy consumption ³⁾		kWh/a	134	188	238
Heating capacity	Nominal [Min - Max]	kW	3,2[1,5 - 4,6]	3,6[1,5 - 4,6]	5,0[1,5 - 6,4]
COP ¹⁾	Nominal [Min - Max]	W/W	4,44[3,41 - 6,52]	4,29[3,38 - 6,52]	3,94[2,91 - 7,50]
SCOP ²⁾			4,6 A++	4,3 A+	4,4 A+
Pdesign at -10 °C		kW	2,8	2,8	4,0
Input power	Nominal [Min - Max]	kW	0,72[0,23 - 1,35]	0,84[0,23 - 1,36]	1,27[0,20 - 2,20]
Annual energy consumption ³⁾		kWh/a	850	912	1264
Indoor unit	S-25PY3E		S-36PY3E	S-50PY3E	S-60PY3E
Air flow	Hi / Med / Lo	m ³ /min	8,5/7,0/6,0	9,5/7,0/6,0	12,0/9,5/6,5
Moisture removal volume		L/h	0,7	1,5	2,3
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	31/28/25	34/30/25	39/34/27
Sound power	Hi / Med / Lo	dB(A)	46/43/40	49/45/40	54/49/42
Dimension	Indoor [HxWxD]	mm	243x575x575	243x575x575	243x575x575
	Panel [HxWxD]	mm	30x625x625	30x625x625	30x625x625
Net weight	Indoor / Panel	kg	15/2,8	15/2,8	15/2,8
nanoe X Generator			Mark 2	Mark 2	Mark 2
Outdoor unit	U-25PZ3E5		U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A
Power supply	V		220 - 230 - 240	220 - 230 - 240	220 - 230 - 240
Current	Cool	A	2,65 - 2,55 - 2,45	4,20 - 4,05 - 3,85	6,65 - 6,35 - 6,10
	Heat	A	3,40 - 3,25 - 3,10	3,95 - 3,75 - 3,60	5,695 - 5,70 - 5,45
Air flow	Cool / Heat	m ³ /min	33,6/34,0	32,6/34,0	32,7/31,9
Sound pressure	Cool / Heat [Hi]	dB(A)	46/47	46/47	46/48
Sound power	Cool / Heat [Hi]	dB(A)	64/66	64/66	64/65
Dimension	HxWxD	mm	619x824x299	619x824x299	695x875x320
Net weight	kg	32	32	35	46
Piping diameter	Liquid	Inch (mm)	1/4 [6,35]	1/4 [6,35]	1/4 [6,35] ⁵⁾
	Gas	Inch (mm)	1/2 [12,70]	1/2 [12,70]	1/2 [12,70] ⁶⁾
Pipe length range	m		3 ~ 15	3 ~ 15	3 ~ 20
Elevation difference [in / out] ⁷⁾	m		15/15	15/15	15/15
Pre-charged pipe length	m		7,5	7,5	7,5
Additional gas amount	g/m		10	10	15
Refrigerant (R32) / CO ₂ Eq.	kg / T		0,87/0,59	0,87/0,59	1,14/0,77
Operating range	Cool Min ~ Max	°C	-10 ~ +43	-10 ~ +43	-10 ~ +43
	Heat Min ~ Max	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the $\eta_{a,c} / \eta_{a,b}$ values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRY3	Infrared remote controller and receiver

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-CENSC1	Econavi energy saving sensor



SEER: For S-50PY3E + U-50PZ3E5. SCOP: For S-25PY3E + U-25PZ3E5. ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Elite 4 way 90x90 cassette - PU3 · R32

4 way 90x90 cassette - PU3.

Powerful turbo fan and intelligent Econavi sensor ensure high energy efficiency, and nanoe™ X, which is equipped as standard, provides an exceptional level of indoor air quality.




Single phase							
Kit	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller	KIT-36PU3ZH5	KIT-50PU3ZH5	KIT-60PU3ZH5	KIT-71PU3ZH45	KIT-100PU3ZH45	KIT-125PU3ZH45	KIT-140PU3ZH45
Cooling capacity Nominal [Min - Max]	kW	3,6[1,2 - 4,0]	5,0[1,2 - 5,6]	6,0[1,2 - 7,1]	7,1[2,2 - 9,0]	9,5[3,1 - 12,5]	12,5[3,2 - 14,0]
EER ¹⁾ Nominal [Min - Max]	W/W	5,45[4,60 - 5,45]	4,31[3,86 - 5,45]	4,05[3,02 - 5,45]	4,06[2,69 - 5,79]	4,42[3,42 - 5,34]	3,80[3,08 - 5,33]
SEER / η _{s,c} ²⁾		8,9 A+++	8,6 A+++	8,0 A++	7,7 A++	7,8 A++	304,3%
Pdesign	kW	3,6	5,0	6,0	7,1	9,5	12,5
Input power Nominal [Min - Max]	kW	0,66[0,22 - 0,87]	1,16[0,22 - 1,45]	1,48[0,22 - 2,35]	1,75[0,38 - 3,35]	2,15[0,58 - 3,65]	3,29[0,60 - 4,55]
Annual energy consumption ³⁾	kWh/a	142	203	263	323	426	—
Heating capacity Nominal [Min - Max]	kW	4,0[1,2 - 5,0]	5,6[1,2 - 6,5]	7,0[1,2 - 8,0]	8,0[2,0 - 9,0]	11,2[3,1 - 14,0]	14,0[3,2 - 16,0]
COP ¹⁾ Nominal [Min - Max]	W/W	5,41[4,55 - 5,45]	4,24[4,19 - 5,45]	4,02[3,40 - 5,45]	4,30[3,16 - 5,56]	5,00[3,64 - 5,54]	4,61[3,37 - 5,52]
SCOP / η _{s,h} ²⁾		5,1 A+++	4,9 A++	4,8 A++	4,8 A++	4,9 A++	186,0%
Pdesign at -10 °C	kW	3,6	4,5	4,7	5,2	8,0	9,5
Input power Nominal [Min - Max]	kW	0,74[0,22 - 1,10]	1,32[0,22 - 1,55]	1,74[0,22 - 2,35]	1,86[0,36 - 2,85]	2,24[0,56 - 3,85]	3,04[0,58 - 4,75]
Annual energy consumption ³⁾	kWh/a	988	1286	1371	1517	2286	—
Indoor unit	S-3650PU3E	S-3650PU3E	S-6071PU3E	S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E
Air flow Hi / Med / Lo	m³/min	14,5/13,0/11,5	16,5/13,5/11,5	21,0/16,0/13,0	22,0/16,0/13,0	36,0/26,0/18,0	37,0/27,0/19,0
Moisture removal volume	L/h	0,7	1,6	1,7	2,5	1,9	4,8
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	30/28/27	32/29/27	36/31/28	37/31/28	45/38/32
Sound power	Hi / Med / Lo	dB(A)	45/43/42	47/44/42	51/46/43	52/46/43	60/53/47
Dimension Indoor [H x W x D]	mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840
Panel [H x W x D]	mm	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950
Net weight	Indoor / Panel	kg	19/5	19/5	20/5	20/5	25/5
nanoe X Generator		Mark 1	Mark 1	Mark 1	Mark 1	Mark 1	Mark 1
Outdoor unit	U-36PZH3E5	U-50PZH3E5	U-60PZH3E5	U-71PZH4E5	U-100PZH4E5	U-125PZH4E5	U-140PZH4E5
Power supply	V	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240
Current Cool	A	3,25 - 3,10 - 3,00	5,50 - 5,25 - 5,05	6,95 - 6,65 - 6,35	8,85 - 8,45 - 8,10	10,06 - 10,02 - 9,75	16,10 - 15,40 - 14,70
Heat	A	3,60 - 3,45 - 3,30	6,25 - 6,00 - 5,75	8,05 - 7,70 - 7,40	9,40 - 9,00 - 8,60	10,90 - 10,60 - 10,10	14,90 - 14,20 - 13,60
Air flow Cool / Heat	m³/min	34,1/36,4	42,0/42,0	42,0/42,0	62,0/66,0	76,0/70,0	86,0/78,0
Sound pressure Cool / Heat [Hi]	dB(A)	43/44	46/48	47/50	48/50	52/52	55/55
Sound power Cool / Heat [Hi]	dB(A)	62/64	64/67	65/69	65/67	69/69	73/73
Dimension H x W x D	mm	695 x 875 x 320	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net weight	kg	42	42	43	66	84	86
Piping diameter Liquid	Inch [mm]	1/4 [6,35]	1/4 [6,35]	1/4 [6,35] ⁵⁾	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]
Gas	Inch [mm]	1/2 [12,70]	1/2 [12,70]	1/2 [12,70] ⁶⁾	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]
Pipe length range	m	3 ~ 40	3 ~ 40	3 ~ 40	5 ~ 60	5 ~ 100	5 ~ 100
Elevation difference [in / out] ⁷⁾	m	15/30	15/30	15/30	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30	30	30	30
Additional gas amount	g/m	15	15	15	30	40	40
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,13/0,76	1,13/0,76	1,15/0,78	1,95/1,32	2,70/1,82	3,00/2,03
Operating range Cool Min ~ Max	°C	-15 ~ +46	-15 ~ +46	-15 ~ +46	-15 ~ +52	-20 ⁸⁾ ~ +52	-20 ⁸⁾ ~ +52
Heat Min ~ Max	°C	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24

Technical focus

- High performance turbo fan
- Econavi: An optional intelligent sensor to reduce waste of energy
- nanoe™ X (Generator Mark 1= 4,8 trillion hydroxyl radicals/sec) as standard for better indoor air quality, indoor unit internal cleaning with nanoe™ X plus dry operation
- Lower noise in low fan operation
- Light weight, easy piping and integrated drain pump for quick installation
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- High volume fresh air input with optional air-intake plenum and chamber (CZ-FDU3+CZ-ATU2)

Standard panel
CZ-KPU3WOptional Econavi panel
(CZ-RTC5B is required).
CZ-KPU3AW

CZ-RTC5B

New
2023

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:

CONEX

CONEX wired
remote
controller,
white.CONEX wired
remote
controller,
black.Infrared
remote
controller.
CZ-RWS3 +
CZ-RWRU3W

Three phase					
Kit		7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller		KIT-71PU3ZH48	KIT-100PU3ZH48	KIT-125PU3ZH48	KIT-140PU3ZH48
Cooling capacity	Nominal (Min - Max)	kW	7,1[2,2 - 9,0]	9,5[3,1 - 12,5]	12,5[3,2 - 14,0]
EER ¹⁾	Nominal (Min - Max)	W/W	4,06[2,69 - 5,79]	4,42[3,42 - 5,34]	3,80[3,08 - 5,33]
SEER / η _{s,c} ²⁾			7,7 A++	7,2 A++	303,0%
Pdesign		kW	7,1	9,5	12,5
Input power	Nominal (Min - Max)	kW	1,75[0,38 - 3,35]	2,15[0,58 - 3,65]	3,29[0,60 - 4,55]
Annual energy consumption ³⁾		kWh/a	323	426	—
Heating capacity	Nominal (Min - Max)	kW	8,0[2,0 - 9,0]	11,2[3,1 - 14,0]	14,0[3,2 - 16,0]
COP ¹⁾	Nominal (Min - Max)	W/W	4,30[3,16 - 5,56]	5,00[3,64 - 5,54]	4,61[3,37 - 5,52]
SCOP / η _{s,h} ²⁾			4,8 A++	4,9 A++	186,0%
Pdesign at -10 °C		kW	5,2	8,0	9,5
Input power	Nominal (Min - Max)	kW	1,86[0,36 - 2,85]	2,24[0,56 - 3,85]	3,04[0,58 - 4,75]
Annual energy consumption ³⁾		kWh/a	1517	2286	—
Indoor unit		S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E
Air flow	Hi / Med / Lo	m ³ /min	22,0/16,0/13,0	36,0/26,0/18,0	37,0/27,0/19,0
Moisture removal volume		L/h	2,5	1,9	4,8
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	37/31/28	45/38/32	46/39/33
Sound power	Hi / Med / Lo	dB(A)	52/46/43	60/53/47	61/54/48
Dimension	Indoor [HxWxD]	mm	256x840x840	319x840x840	319x840x840
	Panel [HxWxD]	mm	33,5x950x950	33,5x950x950	33,5x950x950
Net weight	Indoor / Panel	kg	20/5	25/5	25/5
nanoe X Generator		Mark 1	Mark 1	Mark 1	Mark 1
Outdoor unit		U-71PZH4E8	U-100PZH4E8	U-125PZH4E8	U-140PZH4E8
Power supply	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Current	Cool	A	2,95 - 2,80 - 2,70	3,60 - 3,40 - 3,25	5,45 - 5,15 - 5,00
	Heat	A	3,15 - 3,00 - 2,90	3,75 - 3,55 - 3,40	5,10 - 4,80 - 4,65
Air flow	Cool / Heat	m ³ /min	62,0/66,0	76,0/70,0	86,0/78,0
Sound pressure	Cool / Heat [Hi]	dB(A)	48/50	52/52	55/55
Sound power	Cool / Heat [Hi]	dB(A)	65/67	69/69	73/73
Dimension	HxWxD	mm	996x980x370	996x980x370	996x980x370
Net weight	kg	66	82	84	84
Piping diameter	Liquid	Inch (mm)	3/8[9,52]	3/8[9,52]	3/8[9,52]
	Gas	Inch (mm)	5/8[15,88]	5/8[15,88]	5/8[15,88]
Pipe length range	m	5 ~ 60	5 ~ 100	5 ~ 100	5 ~ 100
Elevation difference (in / out) ⁷⁾	m	15/30	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30	30
Additional gas amount	g/m	30	40	40	40
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,95/1,32	2,70/1,82	3,00/2,03	3,00/2,03
Operating range	Cool Min ~ Max	°C	-15 ~ +52	-20 ⁸⁾ ~ +52	-20 ⁸⁾ ~ +52
	Heat Min ~ Max	°C	-20 ~ +24	-20 ~ +24	-20 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35 - Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70 - Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. 8) Pipe length up to 30 m. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRU3W	Infrared remote controller and receiver

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
CZ-KPU3AW	Econavi exclusive panel
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400 x 900 x 400 mm
CZ-FDU3+CZ-ATU2	Fresh air-intake kit



8,9 SEER



5,1 SCOP



28%



INVERTER+



-15 °C



-20 °C



DC FAN

R22
R410A
RENEWAL

OPTIONAL WI-FI

BMS
CONNECTIVITY5
YEARS
COMPRESSOR
WARRANTY

SEER and SCOP: For S-3650PU3E + U-36PZH3E5. ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Standard 4 way 90x90 cassette - PU3 · R32**4 way 90x90 cassette - PU3.**

Powerful turbo fan and intelligent Econavi sensor ensure high energy efficiency, and nanoe™ X, which is equipped as standard, provides an exceptional level of indoor air quality.



Single phase							
Kit	3,6 kW KIT-36PU3Z5	5,0 kW KIT-50PU3Z5	6,0 kW KIT-60PU3Z5	7,1 kW KIT-71PU3Z5	10,0 kW KIT-100PU3Z5	12,5 kW KIT-125PU3Z5	14,0 kW KIT-140PU3Z5
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity Nominal [Min - Max]	kW 3,6 [1,5 - 4,0]	kW 5,0 [1,5 - 5,6]	kW 6,0 [2,0 - 7,1]	kW 7,1 [2,6 - 7,7]	kW 10,0 [3,0 - 11,5]	kW 12,5 [3,2 - 13,5]	kW 14,0 [3,3 - 15,0]
EER ¹⁾ Nominal [Min - Max]	W/W 4,34 [5,88-3,81]	W/W 3,91 [6,25-3,20]	W/W 3,73 [6,90-3,01]	W/W 3,27 [5,00-2,77]	W/W 3,82 [2,88-5,36]	W/W 3,58 [2,81-5,33]	W/W 3,23 [2,73-5,32]
SEER / η _{s,c} ²⁾	8,1 A++	8,0 A++	7,8 A++	6,8 A++	6,8 A++	267,0%	257,0%
Pdesign	kW 3,6	kW 5,0	kW 6,0	kW 7,1	kW 10,0	kW 12,5	kW 14,0
Input power Nominal [Min - Max]	kW 0,83 [0,25-1,05]	kW 1,28 [0,24-1,75]	kW 1,61 [0,29-2,36]	kW 2,17 [0,52-2,78]	kW 2,62 [0,56-4,00]	kW 3,49 [0,60-4,80]	kW 4,34 [0,62-5,50]
Annual energy consumption ³⁾	kWh/a 156	kWh/a 219	kWh/a 269	kWh/a 365	kWh/a 515	kWh/a —	kWh/a —
Heating capacity Nominal [Min - Max]	kW 3,6 [1,5 - 4,6]	kW 5,0 [1,5 - 6,4]	kW 6,0 [1,8 - 7,0]	kW 7,1 [2,1 - 8,1]	kW 10,0 [3,0 - 14,0]	kW 12,5 [3,3 - 15,0]	kW 14,0 [3,4 - 16,0]
COP ¹⁾ Nominal [Min - Max]	W/W 5,07 [4,32-6,52]	W/W 4,63 [3,48-7,50]	W/W 4,48 [3,18-7,50]	W/W 4,23 [3,38-6,36]	W/W 4,93 [3,59-5,36]	W/W 4,43 [3,57-5,50]	W/W 4,18 [3,33-5,48]
SCOP / η _{s,h} ²⁾	4,8 A++	4,7 A++	4,9 A++	4,6 A++	4,4 A+	157,0%	152,2%
Pdesign at -10 °C	kW 2,8	kW 4,0	kW 4,6	kW 5,2	kW 10,0	kW 12,5	kW 14,0 [at -7 °C]
Input power Nominal [Min - Max]	kW 0,71 [0,23-1,06]	kW 1,08 [0,20-1,84]	kW 1,34 [0,24-2,20]	kW 1,68 [0,33-2,40]	kW 2,03 [0,56-3,90]	kW 2,82 [0,60-4,20]	kW 3,35 [0,62-4,80]
Annual energy consumption ³⁾	kWh/a 817	kWh/a 1191	kWh/a 1314	kWh/a 1583	kWh/a 3182	kWh/a —	kWh/a —
Indoor unit	S-3650PU3E	S-3650PU3E	S-6071PU3E	S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E
Air flow Hi / Med / Lo	m³/min 14,5/13,0/11,5	m³/min 16,5/13,5/11,5	m³/min 21,0/16,0/13,0	m³/min 22,0/16,0/13,0	m³/min 36,0/26,0/18,0	m³/min 37,0/27,0/19,0	m³/min 38,0/29,0/20,0
Moisture removal volume	L/h 0,7	L/h 1,6	L/h 1,7	L/h 2,5	L/h 2,7	L/h 4,8	L/h 6,0
Sound pressure ⁴⁾	Hi / Med / Lo dB(A) 30/28/27	dB(A) 32/29/27	dB(A) 36/31/28	dB(A) 37/31/28	dB(A) 45/38/32	dB(A) 46/39/33	dB(A) 47/40/34
Sound power	Hi / Med / Lo dB(A) 45/43/42	dB(A) 47/44/42	dB(A) 51/46/43	dB(A) 52/46/43	dB(A) 60/53/47	dB(A) 61/54/48	dB(A) 62/55/49
Dimension Indoor (H x W x D)	mm 256 x 840 x 840	mm 256 x 840 x 840	mm 256 x 840 x 840	mm 256 x 840 x 840	mm 319 x 840 x 840	mm 319 x 840 x 840	mm 319 x 840 x 840
Panel (H x W x D)	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950	mm 33,5 x 950 x 950
Net weight Indoor / Panel	kg 19/5	kg 19/5	kg 20/5	kg 20/5	kg 25/5	kg 25/5	kg 25/5
nanoe X Generator	Mark 1	Mark 1	Mark 1	Mark 1	Mark 1	Mark 1	Mark 1
Outdoor unit	U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A	U-71PZ3E5A	U-100PZ3E5	U-125PZ3E5	U-140PZ3E5
Power supply	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240
Current Cool	A 3,85-3,70-3,55	A 5,95-5,70-5,45	A 7,45-7,15-6,85	A 10,00-9,65-9,25	A 13,10-12,50-12,00	A 16,90-16,10-15,40	A 21,00-20,00-19,20
Heat	A 3,35-3,20-3,05	A 5,05-4,85-4,65	A 6,20-5,95-5,70	A 7,80-7,45-7,15	A 10,10-9,70-9,30	A 13,60-13,00-12,50	A 16,20-15,50-14,80
Air flow Cool / Heat	m³/min 33,6/34,0	m³/min 32,7/31,9	m³/min 42,6/41,5	m³/min 44,7/45,9	m³/min 73,0/73,0	m³/min 82,0/80,0	m³/min 84,0/82,0
Sound pressure Cool / Heat (Hi)	dB(A) 46/47	dB(A) 46/46	dB(A) 47/48	dB(A) 48/49	dB(A) 52/52	dB(A) 55/55	dB(A) 56/56
Sound power Cool / Heat (Hi)	dB(A) 64/66	dB(A) 64/64	dB(A) 64/65	dB(A) 66/68	dB(A) 70/70	dB(A) 73/73	dB(A) 74/74
Dimension H x W x D	mm 619 x 824 x 299	mm 619 x 824 x 299	mm 695 x 875 x 320	mm 695 x 875 x 320	mm 996 x 980 x 370	mm 996 x 980 x 370	mm 996 x 980 x 370
Net weight	kg 32	kg 35	kg 42	kg 50	kg 83	kg 87	kg 87
Piping diameter Liquid	Inch (mm) 1/4 [6,35]	Inch (mm) 1/4 [6,35]	Inch (mm) 1/4 [6,35] ⁵⁾	Inch (mm) 1/4 [6,35] ⁵⁾	Inch (mm) 3/8 [9,52]	Inch (mm) 3/8 [9,52]	Inch (mm) 3/8 [9,52]
Gas	Inch (mm) 1/2 [12,70]	Inch (mm) 1/2 [12,70]	Inch (mm) 1/2 [12,70] ⁶⁾	Inch (mm) 1/2 [12,70] ⁶⁾	Inch (mm) 5/8 [15,88]	Inch (mm) 5/8 [15,88]	Inch (mm) 5/8 [15,88]
Pipe length range	m 3~15	m 3~20	m 3~40	m 3~40	m 5~50	m 5~50	m 5~50
Elevation difference (in / out) ⁷⁾	m 15/15	m 15/15	m 15/30	m 20/30	m 15/30	m 15/30	m 15/30
Pre-charged pipe length	m 7,5	m 7,5	m 30	m 30	m 30	m 30	m 30
Additional gas amount	g/m 10	g/m 15	g/m 15	g/m 17	g/m 45	g/m 45	g/m 45
Refrigerant (R32) / CO ₂ Eq.	kg / T 0,87/0,59	kg / T 1,14/0,77	kg / T 1,15/0,78	kg / T 1,32/0,89	kg / T 2,40/1,62	kg / T 2,80/1,89	kg / T 2,80/1,89
Operating range Cool Min ~ Max	°C -10 ~ +43	°C -10 ~ +43	°C -10 ~ +43	°C -10 ~ +43	°C -10 ~ +43	°C -10 ~ +43	°C -10 ~ +43
Heat Min ~ Max	°C -15 ~ +24	°C -15 ~ +24	°C -15 ~ +24	°C -15 ~ +24	°C -15 ~ +24	°C -15 ~ +24	°C -15 ~ +24

Technical focus

- High performance turbo fan
- Econavi: An optional intelligent sensor to reduce waste of energy
- nanoe™ X (Generator Mark 1= 4,8 trillion hydroxyl radicals/sec) as standard for better indoor air quality, indoor unit internal cleaning with nanoe™ X plus dry operation
- Lower noise in low fan operation
- Light weight, easy piping and integrated drain pump for quick installation
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- High volume fresh air input with optional air-intake plenum and chamber (CZ-FDU3+CZ-ATU2)

Standard panel.
CZ-KPU3WOptional Econavi panel
(CZ-RTC5B is required).
CZ-KPU3AW

CZ-RTC5B

COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION



Optional:

CONEX

CONEX wired
remote
controller,
white.

CONEX

CONEX wired
remote
controller,
black.Infrared
remote
controller.
CZ-RWS3 +
CZ-RWRU3W

			Three phase	
Kit	KIT-100PU3Z8	KIT-125PU3Z8	KIT-140PU3Z8	
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	
Cooling capacity	Nominal [Min - Max] kW	10,0[3,0 - 11,5]	12,5[3,2 - 13,5]	14,0[3,3 - 15,0]
EER ¹⁾	Nominal [Min - Max] W/W	3,82[2,88 - 5,36]	3,58[2,81 - 5,33]	3,23[2,73 - 5,32]
SEER / η _{s,c} ²⁾		6,7 A++	265,8%	256,2%
Pdesign	kW	10,0	12,5	14,0
Input power	Nominal [Min - Max] kW	2,62[0,56 - 4,00]	3,49[0,60 - 4,80]	4,34[0,62 - 5,50]
Annual energy consumption ³⁾	kWh/a	521	—	—
Heating capacity	Nominal [Min - Max] kW	10,0[3,0 - 14,0]	12,5[3,3 - 15,0]	14,0[3,4 - 16,0]
COP ¹⁾	Nominal [Min - Max] W/W	4,93[3,59 - 5,36]	4,43[3,57 - 5,50]	4,18[3,33 - 5,48]
SCOP / η _{s,h} ²⁾		4,4 A+	157,0%	152,2%
Pdesign at -10 °C	kW	10,0	12,5	14,0 (at -7 °C)
Input power	Nominal [Min - Max] kW	2,03[0,56 - 3,90]	2,82[0,60 - 4,20]	3,35[0,62 - 4,80]
Annual energy consumption ³⁾	kWh/a	3182	—	—
Indoor unit	S-1014PU3E	S-1014PU3E	S-1014PU3E	
Air flow	Hi / Med / Lo m ³ /min	36,0/26,0/18,0	37,0/27,0/19,0	38,0/29,0/20,0
Moisture removal volume	L/h	2,7	4,8	6,0
Sound pressure ⁴⁾	Hi / Med / Lo dB(A)	45/38/32	46/39/33	47/40/34
Sound power	Hi / Med / Lo dB(A)	60/53/47	61/54/48	62/55/49
Dimension	Indoor [HxWxD] mm	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
	Panel [HxWxD] mm	33,5 x 950 x 950	33,5 x 950 x 950	33,5 x 950 x 950
Net weight	Indoor / Panel kg	25/5	25/5	25/5
nanoe X Generator		Mark 1	Mark 1	Mark 1
Outdoor unit	U-100PZ3E8	U-125PZ3E8	U-140PZ3E8	
Power supply	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Current	Cool A	4,35 - 4,15 - 4,00	5,65 - 5,35 - 5,15	7,00 - 6,65 - 6,40
	Heat A	3,40 - 3,20 - 3,10	4,55 - 4,35 - 4,15	5,40 - 5,15 - 4,95
Air flow	Cool / Heat m ³ /min	73,0/73,0	82,0/80,0	84,0/82,0
Sound pressure	Cool / Heat [Hi] dB(A)	52/52	55/55	56/56
Sound power	Cool / Heat [Hi] dB(A)	70/70	73/73	74/74
Dimension	HxWxD mm	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net weight	kg	83	87	87
Piping diameter	Liquid Inch (mm)	3/8[9,52]	3/8[9,52]	3/8[9,52]
	Gas Inch (mm)	5/8[15,88]	5/8[15,88]	5/8[15,88]
Pipe length range	m	5 ~ 50	5 ~ 50	5 ~ 50
Elevation difference (in / out) ⁷⁾	m	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30
Additional gas amount	g/m	45	45	45
Refrigerant (R32) / CO ₂ Eq.	kg / T	2,40/1,62	2,80/1,89	2,80/1,89
Operating range	Cool Min ~ Max °C	-10 ~ +43	-10 ~ +43	-10 ~ +43
	Heat Min ~ Max °C	-15 ~ +24	-15 ~ +24	-15 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35 - Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70 - Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRU3W	Infrared remote controller and receiver

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
CZ-KPU3AW	Econavi exclusive panel
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400 x 900 x 400 mm
CZ-FDU3+CZ-ATU2	Fresh air-intake kit



SEER: For S-3650PU3E + U-36PZ3E5. SCOP: For S-6071PU3E + U-60PZ3E5A. ECONAVI and INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Elite ceiling - PT3 · R32

Ceiling mounted units provide large and wide air distribution which is ideal for large rooms.

The height and depth of all capacities are the same for unified appearance in mixed installations.



Single phase							
Kit	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller	KIT-36PT3ZH5	KIT-50PT3ZH5	KIT-60PT3ZH5	KIT-71PT3ZH45	KIT-100PT3ZH45	KIT-125PT3ZH45	KIT-140PT3ZH45
Cooling capacity	Nominal [Min - Max] kW	3,5[1,2 - 4,0]	5,0[1,2 - 5,6]	6,0[1,2 - 7,1]	6,8[2,2 - 9,0]	9,5[3,1 - 12,5]	12,1[3,2 - 14,0]
EER ¹⁾	Nominal [Min - Max] W/W	4,86(4,55-5,45)	4,03(3,57-5,45)	3,82(3,02-5,45)	3,91(2,69-5,79)	4,06(3,29-5,34)	3,46(3,01-5,33)
SEER / η _{s,c} ²⁾		7,7 A++	7,4 A++	7,5 A++	7,3 A++	7,3 A++	278,4%
Pdesign	kW	3,5	5,0	6,0	6,8	9,5	12,1
Input power	Nominal [Min - Max] kW	0,72[0,22-0,88]	1,24[0,22-1,57]	1,57[0,22-2,35]	1,74[0,38-3,35]	2,34[0,58-3,80]	3,50[0,60-4,65]
Annual energy consumption ³⁾	kWh/a	160	237	280	326	456	—
Heating capacity	Nominal [Min - Max] kW	4,0[1,2 - 5,0]	5,6[1,2 - 6,5]	7,0[1,2 - 8,0]	8,0[2,0 - 9,0]	11,2[3,1 - 14,0]	14,0[3,2 - 16,0]
COP ¹⁾	Nominal [Min - Max] W/W	5,00(4,17-5,45)	4,03(3,94-5,45)	4,14(3,40-5,45)	3,96(3,16-5,56)	4,00(3,54-5,54)	3,78(3,20-5,52)
SCOP / η _{s,h} ²⁾		4,9 A++	4,8 A++	4,8 A++	4,7 A++	4,5 A+	175,6%
Pdesign at -10 °C	kW	3,1	4,0	4,6	4,7	7,8	9,5
Input power	Nominal [Min - Max] kW	0,80[0,22-1,20]	1,39[0,22-1,65]	1,69[0,22-2,35]	2,02[0,36-2,85]	2,80[0,56-3,95]	3,70[0,58-5,00]
Annual energy consumption ³⁾	kWh/a	886	1167	1342	1400	2426	—
Indoor unit	S-3650PT3E	S-3650PT3E	S-6071PT3E	S-6071PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E
Air flow	Hi / Med / Lo m³/min	14,0/12,0/10,5	15,0/12,5/10,5	20,0/17,0/14,5	21,0/18,0/15,5	30,0/25,0/23,0	34,0/28,0/24,0
Moisture removal volume	L/h	0,8	2,0	2,1	2,7	3,6	5,4
Sound pressure ⁴⁾	Hi / Med / Lo dB(A)	36/32/28	37/33/28	38/34/29	39/35/30	42/37/34	46/40/35
Sound power	Hi / Med / Lo dB(A)	54/50/46	55/51/46	56/52/47	57/53/48	60/55/52	64/58/53
Dimension	HxWxD mm	235x960x690	235x960x690	235x1275x690	235x1275x690	235x1590x690	235x1590x690
Net weight	kg	26	26	34	34	40	40
nanoe X Generator		Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZH3E5	U-50PZH3E5	U-60PZH3E5	U-71PZH4E5	U-100PZH4E5	U-125PZH4E5	U-140PZH4E5
Power supply	V	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240
Current	Cool A	3,55-3,40-3,25	5,85-5,60-5,40	7,35-7,05-6,75	8,80-8,40-8,05	11,60-11,10-10,60	17,10-16,40-15,70
	Heat A	3,90-3,75-3,60	6,60-6,30-6,05	7,85-7,50-7,20	10,20-9,75-9,35	13,70-13,20-12,70	18,10-17,30-16,60
Air flow	Cool / Heat m³/min	34,1/36,4	42,0/42,0	42,0/42,0	62,0/66,0	76,0/70,0	86,0/78,0
Sound pressure	Cool / Heat [Hi] dB(A)	43/44	46/48	47/50	48/50	52/52	55/55
Sound power	Cool / Heat [Hi] dB(A)	62/64	64/67	65/69	65/67	69/69	73/73
Dimension	HxWxD mm	695x875x320	695x875x320	695x875x320	996x980x370	996x980x370	996x980x370
Net weight	kg	42	42	43	66	84	86
Piping diameter	Liquid Inch [mm]	1/4 [6,35]	1/4 [6,35]	1/4 [6,35] ⁵⁾	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]
	Gas Inch [mm]	1/2 [12,70]	1/2 [12,70]	1/2 [12,70] ⁶⁾	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]
Pipe length range	m	3~40	3~40	3~40	5~60	5~100	5~100
Elevation difference (in / out) ⁷⁾	m	15/30	15/30	15/30	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30	30	30	30
Additional gas amount	g/m	15	15	15	30	40	40
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,13/0,76	1,13/0,76	1,15/0,78	1,95/1,32	2,70/1,82	3,00/2,03
Operating range	Cool Min ~ Max °C	-15~+46	-15~+46	-15~+52	-20 ⁸⁾ ~+52	-20 ⁸⁾ ~+52	-20 ⁸⁾ ~+52
	Heat Min ~ Max °C	-20~+24	-20~+24	-20~+24	-20~+24	-20~+24	-20~+24

Technical focus

- Wide air distribution for large rooms
- Horizontal air flow reaches maximum 9,5 m
- Fresh air connection available on the unit
- Slim design with 235 mm height fits narrow space
- Silent operation
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Twin, Triple and Double-twin split options
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Further comfort improvement with air flow distribution

Horizontal air flow reaches maximum 9,5 m. This is ideal for wide rooms.

The wide air discharge opening expands the air flow to the left and right. The unpleasant feeling caused when the air flow directly hits the human body is prevented by the "Draft prevention position", which changes the swing width, increasing the degree of comfort.



CZ-RTC5B

New
2023

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:

CONEX wired remote controller, white.
CZ-RTC6W/BL/BLWCONEX wired remote controller, black.
CZ-RTC6/BL/BLWInfrared remote controller.
CZ-RWS3 +
CZ-RWRT3Econavi sensor.
CZ-CENSC1

Three phase

Kit	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity Nominal [Min - Max]	kW	6,8 [2,2 - 9,0]	9,5 [3,1 - 12,5]	12,1 [3,2 - 14,0]
EER ¹⁾ Nominal [Min - Max]	W/W	3,91 [2,69 - 5,79]	4,06 [3,29 - 5,34]	3,46 [3,01 - 5,33]
SEER / η _{s,c} ²⁾		7,2 A++	7,2 A++	277,3%
Pdesign	kW	6,8	9,5	12,1
Input power Nominal [Min - Max]	kW	1,74 [0,38 - 3,35]	2,34 [0,58 - 3,80]	3,50 [0,60 - 4,65]
Annual energy consumption ³⁾	kWh/a	331	462	—
Heating capacity Nominal [Min - Max]	kW	8,0 [2,0 - 9,0]	11,2 [3,1 - 14,0]	14,0 [3,2 - 16,0]
COP ¹⁾ Nominal [Min - Max]	W/W	3,96 [3,16 - 5,56]	4,00 [3,54 - 5,54]	3,78 [3,20 - 5,52]
SCOP / η _{s,h} ²⁾		4,7 A++	4,5 A+	175,6%
Pdesign at -10 °C	kW	4,7	7,8	9,5
Input power Nominal [Min - Max]	kW	2,02 [0,36 - 2,85]	2,80 [0,56 - 3,95]	3,70 [0,58 - 5,00]
Annual energy consumption ³⁾	kWh/a	1400	2427	—
Indoor unit	S-6071PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E
Air flow Hi / Med / Lo	m ³ /min	21,0 / 18,0 / 15,5	30,0 / 25,0 / 23,0	34,0 / 28,0 / 24,0
Moisture removal volume	L/h	2,7	3,6	5,4
Sound pressure ⁴⁾ Hi / Med / Lo	dB(A)	39 / 35 / 30	42 / 37 / 34	46 / 40 / 35
Sound power Hi / Med / Lo	dB(A)	57 / 53 / 48	60 / 55 / 52	64 / 58 / 53
Dimension HxWxD	mm	235 x 1275 x 690	235 x 1590 x 690	235 x 1590 x 690
Net weight	kg	34	40	40
nanoe X Generator		Mark 2	Mark 2	Mark 2
Outdoor unit	U-71PZH4E8	U-100PZH4E8	U-125PZH4E8	U-140PZH4E8
Power supply	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Current Cool	A	2,95 - 2,80 - 2,70	3,60 - 3,40 - 3,25	5,45 - 5,15 - 5,00
Heat	A	3,15 - 3,00 - 2,90	3,75 - 3,55 - 3,40	5,10 - 4,80 - 4,65
Air flow Cool / Heat	m ³ /min	62,0 / 66,0	76,0 / 70,0	86,0 / 78,0
Sound pressure Cool / Heat [Hi]	dB(A)	48 / 50	52 / 52	55 / 55
Sound power Cool / Heat [Hi]	dB(A)	65 / 67	69 / 69	73 / 73
Dimension HxWxD	mm	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net weight	kg	66	82	84
Piping diameter Liquid	Inch (mm)	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]
Gas	Inch (mm)	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]
Pipe length range	m	5 ~ 60	5 ~ 100	5 ~ 100
Elevation difference (in / out) ⁷⁾	m	15 / 30	15 / 30	15 / 30
Pre-charged pipe length	m	30	30	30
Additional gas amount	g/m	30	40	40
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,95 / 1,32	2,70 / 1,82	3,00 / 2,03
Operating range Cool Min ~ Max	°C	-15 ~ +52	-20 ⁸⁾ ~ +52	-20 ⁸⁾ ~ +52
Heat Min ~ Max	°C	-20 ~ +24	-20 ~ +24	-20 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1 m in front of the main body and 1 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. 8) Pipe length up to 30 m. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRT3	Infrared remote controller

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400 x 900 x 400 mm
CZ-CENSC1	Econavi energy saving sensor



SEER and SCOP: For S-3650PT3E + U-36PZH3E5. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Standard ceiling - PT3 · R32

Ceiling mounted units provide large and wide air distribution which is ideal for large rooms.

The height and depth of all capacities are the same for unified appearance in mixed installations.



nanoe™ X as a standard.

Single phase							
Kit	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller	KIT-36PT3Z5	KIT-50PT3Z5	KIT-60PT3Z5	KIT-71PT3Z5	KIT-100PT3Z5	KIT-125PT3Z5	KIT-140PT3Z5
Cooling capacity Nominal [Min - Max]	kW 3,5[1,5 - 4,0]	5,0[1,5 - 5,2]	6,0[2,0 - 7,1]	6,8[2,6 - 7,7]	10,0[3,0 - 11,5]	12,5[3,2 - 13,5]	14,0[3,3 - 15,0]
EER ¹⁾ Nominal [Min - Max]	W/W 4,14[3,69 - 5,17]	3,03[2,86 - 5,00]	3,59[2,90 - 6,90]	3,24[2,75 - 4,91]	3,64[2,80 - 5,36]	3,32[2,77 - 5,33]	2,98[2,73 - 5,32]
SEER / η _{s,c} ²⁾	7,2 A++	6,7 A++	7,3 A++	5,9 A+	6,6 A++	241,7%	228,8%
Pdesign	kW 3,5	5,0	6,0	6,8	10,0	12,5	14,0
Input power Nominal [Min - Max]	kW 0,85[0,29 - 1,10]	1,65[0,30 - 1,82]	1,67[0,29 - 2,45]	2,10[0,53 - 2,80]	2,75[0,56 - 4,10]	3,76[0,60 - 4,88]	4,70[0,62 - 5,50]
Annual energy consumption ³⁾	kWh/a 171	262	288	404	531	—	—
Heating capacity Nominal [Min - Max]	kW 3,5[1,5 - 4,6]	5,0[1,5 - 6,4]	6,0[1,8 - 7,0]	6,8[2,1 - 8,1]	10,0[3,0 - 14,0]	12,5[3,3 - 15,0]	14,0[3,4 - 16,0]
COP ¹⁾ Nominal [Min - Max]	W/W 4,61[3,51 - 5,70]	3,73[3,12 - 6,25]	4,11[2,92 - 6,67]	4,20[3,06 - 5,68]	4,24[3,30 - 5,36]	3,89[3,41 - 4,52]	3,70[3,08 - 5,48]
SCOP / η _{s,h} ²⁾	4,4 A+	4,1 A+	4,6 A++	4,3 A+	4,2 A+	147,4%	145,3%
Pdesign at -10 °C	kW 2,8	4,0	4,6	4,7	10,0	12,5	13,6
Input power Nominal [Min - Max]	kW 0,76[0,26 - 1,31]	1,34[0,24 - 2,05]	1,46[0,27 - 2,40]	1,62[0,37 - 2,65]	2,36[0,56 - 4,00]	3,21[0,73 - 4,40]	3,78[0,62 - 5,20]
Annual energy consumption ³⁾	kWh/a 891	1365	1399	1529	3331	—	—
Indoor unit	S-3650PT3E	S-3650PT3E	S-6071PT3E	S-6071PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E
Air flow Hi / Med / Lo	m³/min 14,0/12,0/10,5	15,0/12,5/10,5	20,0/17,0/14,5	21,0/18,0/15,5	30,0/25,0/23,0	34,0/28,0/24,0	35,0/29,0/25,0
Moisture removal volume	L/h 0,8	2,0	2,1	2,7	4,1	5,7	6,9
Sound pressure ⁴⁾	Hi / Med / Lo dB(A) 36/32/28	37/33/28	38/34/29	39/35/30	42/37/34	46/40/35	47/41/36
Sound power	Hi / Med / Lo dB(A) 54/50/46	55/51/46	56/52/47	57/53/48	60/55/52	64/58/53	65/59/54
Dimension HxWxD	mm 235x960x690	235x960x690	235x1275x690	235x1275x690	235x1590x690	235x1590x690	235x1590x690
Net weight	kg 26	26	34	34	40	40	40
nanoe X Generator	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A	U-71PZ3E5A	U-100PZ3E5	U-125PZ3E5	U-140PZ3E5
Power supply	V 220-230-240	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240
Current Cool	A 3,90-3,75-3,60	7,65-7,30-7,00	7,75-7,40-7,10	9,75-9,30-8,95	13,70-13,10-12,60	18,20-17,40-16,70	22,70-21,70-20,80
Heat	A 3,55-3,40-3,25	6,30-6,00-5,75	6,75-6,50-6,20	7,50-7,20-6,90	11,80-11,30-10,80	15,50-14,80-14,20	18,30-17,50-16,80
Air flow Cool / Heat	m³/min 33,6/34,0	32,7/31,9	42,6/41,5	44,7/45,9	73,0/73,0	82,0/80,0	84,0/82,0
Sound pressure Cool / Heat [Hi]	dB(A) 46/47	46/46	47/48	48/49	52/52	55/55	56/56
Sound power Cool / Heat [Hi]	dB(A) 64/66	64/64	64/65	66/68	70/70	73/73	74/74
Dimension HxWxD	mm 619x824x299	619x824x299	695x875x320	695x875x320	996x980x370	996x980x370	996x980x370
Net weight	kg 32	35	42	50	83	87	87
Piping diameter Liquid	Inch [mm] 1/4 [6,35]	1/4 [6,35]	1/4 [6,35] ⁵⁾	1/4 [6,35] ⁵⁾	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]
Gas	Inch [mm] 1/2 [12,70]	1/2 [12,70]	1/2 [12,70] ⁴⁾	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]
Pipe length range	m 3~15	3~20	3~40	3~40	5~50	5~50	5~50
Elevation difference [in / out] ⁷⁾	m 15/15	15/15	15/30	20/30	15/30	15/30	15/30
Pre-charged pipe length	m 7,5	7,5	30	30	30	30	30
Additional gas amount	g/m 10	15	15	17	45	45	45
Refrigerant [R32] / CO ₂ Eq.	kg / T 0,87/0,59	1,14/0,77	1,15/0,78	1,32/0,89	2,40/1,62	2,80/1,89	2,80/1,89
Operating range Cool Min ~ Max	°C -10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43
Heat Min ~ Max	°C -15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24

Technical focus

- Wide air distribution for large rooms
- Horizontal air flow reaches maximum 9,5 m
- Fresh air connection available on the unit
- Slim design with 235 mm height fits narrow space
- Silent operation
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for better indoor air quality
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®
- Twin, Triple and Double-twin split options
- Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be controlled by the remote control of the Panasonic indoor unit

Further comfort improvement with air flow distribution

Horizontal air flow reaches maximum 9,5 m. This is ideal for wide rooms.

The wide air discharge opening expands the air flow to the left and right. The unpleasant feeling caused when the air flow directly hits the human body is prevented by the "Draft prevention position", which changes the swing width, increasing the degree of comfort.



CZ-RTC5B

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

**Optional:**

CONEX
wired
remote
controller,
white.
CZ-RTC6W/
BL/BLW



CONEX
wired
remote
controller,
black.
CZ-RTC6/BL/
BLW



Infrared
remote
controller.
CZ-RWS3 +
CZ-RWRT3



Econavi
sensor.
CZ-CENSC1

Three phase

Kit	10,0 kW	12,5 kW	14,0 kW
Remote controller	KIT-100PT3Z8	KIT-125PT3Z8	KIT-140PT3Z8
Cooling capacity	Nominal [Min - Max] kW	10,0[3,0 - 11,5]	12,5[3,2 - 13,5]
EER ¹⁾	Nominal [Min - Max] W/W	3,64[3,50 - 5,36]	3,32[2,77 - 5,33]
SEER / η_{s,c} ²⁾	6,5 A++	241,7%	228,8%
Pdesign	kW	10,0	12,5
Input power	Nominal [Min - Max] kW	2,75[0,56 - 4,10]	3,76[0,60 - 4,88]
Annual energy consumption ³⁾	kWh/a	537	—
Heating capacity	Nominal [Min - Max] kW	10,0[3,0 - 14,0]	12,5[3,3 - 15,0]
COP ⁴⁾	Nominal [Min - Max] W/W	4,24[3,50 - 5,36]	3,89[3,41 - 4,52]
SCOP / η_{s,h} ²⁾	4,2 A+	147,4%	145,3%
Pdesign at -10 °C	kW	10,0	12,5
Input power	Nominal [Min - Max] kW	2,36[0,56 - 4,00]	3,21[0,73 - 4,40]
Annual energy consumption ³⁾	kWh/a	3331	—
Indoor unit	S-1014PT3E	S-1014PT3E	S-1014PT3E
Air flow	Hi / Med / Lo	m ³ /min	30,0/25,0/23,0
Moisture removal volume		L/h	4,1
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)	42/37/34
Sound power	Hi / Med / Lo	dB(A)	60/55/52
Dimension	HxWxD	mm	235x1590x690
Net weight	kg	40	40
nanoe X Generator		Mark 2	Mark 2
Outdoor unit	U-100PZ3E8	U-125PZ3E8	U-140PZ3E8
Power supply	V	380-400-415	380-400-415
Current	Cool A	4,60-4,35-4,20	6,10-5,75-5,55
	Heat A	3,95-3,75-3,60	5,20-4,95-4,75
Air flow	Cool / Heat m ³ /min	73,0/73,0	82,0/80,0
Sound pressure	Cool / Heat (Hi) dB(A)	52/52	55/55
Sound power	Cool / Heat (Hi) dB(A)	70/70	73/73
Dimension	HxWxD mm	996x980x370	996x980x370
Net weight	kg	83	87
Piping diameter	Liquid Inch (mm)	3/8[9,52]	3/8[9,52]
	Gas Inch (mm)	5/8[15,88]	5/8[15,88]
Pipe length range	m	5~50	5~50
Elevation difference (in / out) ⁷⁾	m	15/30	15/30
Pre-charged pipe length	m	30	30
Additional gas amount	g/m	45	45
Refrigerant (R32) / CO ₂ Eq.	kg / T	2,40/1,62	2,8/1,89
Operating range	Cool Min ~ Max °C	-10~+43	-10~+43
	Heat Min ~ Max °C	-15~+24	-15~+24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1 m in front of the main body and 1 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 6) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 7) Outdoor unit located lower / outdoor unit located higher. * Recommended fuse for the indoor 3 A. ** Above values are in the case of nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRT3	Infrared remote controller

Accessories

CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-CENSC1	Econavi energy saving sensor



SEER and SCOP: For S-6071PT3E + U-60PZ3E5A. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Elite adaptive ducted unit - PF3 · R32

Adaptive ducted unit - PF3.

2 installation possibilities (horizontal / vertical) with high ESP 150Pa allows flexible installation.



Single phase							
	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Kit	KIT-36PF3ZH5	KIT-50PF3ZH5	KIT-60PF3ZH5	KIT-71PF3ZH45	KIT-100PF3ZH45	KIT-125PF3ZH45	KIT-140PF3ZH45
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity Nominal [Min - Max]	kW 3,6[1,2 - 4,0]	kW 5,0[1,2 - 5,6]	kW 5,7[1,2 - 6,3]	kW 6,8[2,2 - 7,8]	kW 9,5[3,1 - 11,4]	kW 12,1[3,2 - 13,6]	kW 13,4[3,3 - 15,3]
EER ¹⁾ Nominal [Min - Max]	W/W 4,24[3,57 - 5,45]	W/W 3,42[3,11 - 5,45]	W/W 3,68[3,15 - 5,45]	W/W 3,74[2,41 - 5,64]	W/W 4,09[2,82 - 5,08]	W/W 3,53[3,00 - 5,00]	W/W 3,38[2,59 - 4,18]
SEER / η_{s,c} ²⁾	6,8 A++	6,1 A++	7,1 A++	7,1 A++	7,4 A++	281,7%	275,9%
Pdesign	kW 3,6	kW 5,0	kW 5,7	kW 6,8	kW 9,5	kW 12,1	kW 13,4
Input power Nominal [Min - Max]	kWh/a 0,85[0,22 - 1,12]	kWh/a 1,46[0,22 - 1,80]	kWh/a 1,55[0,22 - 2,00]	kWh/a 1,82[0,39 - 3,24]	kWh/a 3,23[0,61 - 4,04]	kWh/a 3,43[0,64 - 4,54]	kWh/a 3,96[0,79 - 5,90]
Annual energy consumption ³⁾	kWh/a 185	kWh/a 287	kWh/a 281	kWh/a 332	kWh/a 447	kWh/a —	kWh/a —
Heating capacity Nominal [Min - Max]	kW 4,0[1,2 - 5,0]	kW 5,6[1,2 - 6,5]	kW 7,0[1,2 - 8,0]	kW 7,5[2,0 - 9,0]	kW 10,8[3,1 - 13,5]	kW 13,5[3,2 - 15,4]	kW 15,5[3,3 - 17,4]
COP ¹⁾ Nominal [Min - Max]	W/W 4,17[3,23 - 5,45]	W/W 3,61[2,97 - 5,45]	W/W 3,74[3,33 - 5,45]	W/W 4,03[3,16 - 5,41]	W/W 3,88[3,07 - 5,25]	W/W 3,46[3,06 - 5,16]	W/W 3,33[3,14 - 4,29]
SCOP / η_{s,h} ²⁾	4,5 A+	4,2 A+	4,4 A+	4,7 A++	4,3 A+	165,0%	162,6%
Pdesign at -10 °C	kW 3,6	kW 4,0	kW 4,7	kW 4,7	kW 7,8	kW 9,3	kW 9,5
Input power Nominal [Min - Max]	kWh/a 0,96[0,22 - 1,55]	kWh/a 1,55[0,22 - 2,19]	kWh/a 1,87[0,22 - 2,40]	kWh/a 1,86[0,37 - 2,85]	kWh/a 2,78[0,59 - 4,40]	kWh/a 3,90[0,62 - 5,04]	kWh/a 4,65[0,77 - 5,55]
Annual energy consumption ³⁾	kWh/a 1120	kWh/a 1333	kWh/a 1495	kWh/a 1393	kWh/a 2540	kWh/a —	kWh/a —
Indoor unit	S-3650PF3E	S-3650PF3E	S-6071PF3E	S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
External static pressure ⁴⁾ Nominal [Min - Max]	Pa 30[10 - 150]	Pa 30[10 - 150]	Pa 30[10 - 150]	Pa 30[10 - 150]	Pa 40[10 - 150]	Pa 50[10 - 150]	Pa 50[10 - 150]
Air flow Hi / Med / Lo	m³/min 14,0/13,0/10,0	m³/min 16,0/15,0/12,0	m³/min 21,0/19,0/15,0	m³/min 21,0/19,0/15,0	m³/min 20,0/26,0/21,0	m³/min 34,0/29,0/23,0	m³/min 36,0/32,0/25,0
Moisture removal volume	L/h 0,9	L/h 1,9	L/h 1,7	L/h 2,7	L/h 3,2	L/h 4,1	L/h 4,9
Sound pressure ⁵⁾ Hi / Med / Lo	dB(A) 30/27/22	dB(A) 34/30/25	dB(A) 30/26/23	dB(A) 30/26/23	dB(A) 33/29/25	dB(A) 35/31/27	dB(A) 39/35/29
Sound power	dB(A) 53/50/45	dB(A) 57/53/48	dB(A) 53/49/46	dB(A) 53/49/46	dB(A) 56/52/48	dB(A) 58/54/50	dB(A) 62/58/52
Dimension HxWxD	mm 250×800×730	mm 250×800×730	mm 250×1000×730	mm 250×1000×730	mm 250×1400×730	mm 250×1400×730	mm 250×1400×730
Net weight	kg 25	kg 25	kg 30	kg 30	kg 39	kg 39	kg 39
nanoe X Generator	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZH3E5	U-50PZH3E5	U-60PZH3E5	U-71PZH4E5	U-100PZH4E5	U-125PZH4E5	U-140PZH4E5
Power supply	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240	V 220-230-240
Current Cool	A 4,20-4,00-3,85	A 6,90-6,60-6,35	A 7,25-6,95-6,65	A 9,20-8,80-8,45	A 11,50-11,00-10,50	A 16,80-16,00-15,40	A 19,40-18,50-17,70
Heat	A 4,70-4,50-4,30	A 7,35-7,00-6,75	A 8,65-8,30-7,95	A 9,40-9,00-8,60	A 13,60-13,10-12,60	A 19,10-18,20-17,50	A 22,70-21,70-20,80
Air flow Cool / Heat	m³/min 34,1/36,4	m³/min 42,0/42,0	m³/min 42,0/42,0	m³/min 62,0/66,0	m³/min 76,0/70,0	m³/min 86,0/78,0	m³/min 89,0/83,0
Sound pressure Cool / Heat [Hi]	dB(A) 43/44	dB(A) 46/48	dB(A) 47/50	dB(A) 48/50	dB(A) 52/52	dB(A) 55/55	dB(A) 56/56
Sound power Cool / Heat [Hi]	dB(A) 62/64	dB(A) 64/67	dB(A) 65/69	dB(A) 65/67	dB(A) 69/69	dB(A) 73/73	dB(A) 74/74
Dimension HxWxD	mm 695×875×320	mm 695×875×320	mm 695×875×320	mm 996×980×370	mm 996×980×370	mm 996×980×370	mm 996×980×370
Net weight	kg 42	kg 42	kg 43	kg 66	kg 84	kg 86	kg 86
Piping diameter Liquid	Inch (mm) 1/4 [6,35]	Inch (mm) 1/4 [6,35]	Inch (mm) 1/4 [6,35] ⁶⁾	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]	3/8 [9,52]
Gas	Inch (mm) 1/2 [12,70]	Inch (mm) 1/2 [12,70]	Inch (mm) 1/2 [12,70] ⁷⁾	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]	5/8 [15,88]
Pipe length range	m 3~40	m 3~40	m 3~40	m 5~60	m 5~100	m 5~100	m 5~100
Elevation difference [in / out] ⁸⁾	m 15/30	m 15/30	m 15/30	m 15/30	m 15/30	m 15/30	m 15/30
Pre-charged pipe length	m 30	m 30	m 30	m 30	m 30	m 30	m 30
Additional gas amount	g/m 15	g/m 15	g/m 15	g/m 30	g/m 40	g/m 40	g/m 40
Refrigerant (R32) / CO ₂ Eq.	kg / T 1,13/0,76	kg / T 1,13/0,76	kg / T 1,15/0,78	kg / T 1,95/1,32	kg / T 2,70/1,82	kg / T 3,00/2,03	kg / T 3,00/2,03
Operating range Cool Min ~ Max	°C -15 ~ +46	°C -15 ~ +46	°C -15 ~ +46	°C -15 ~ +52	°C -20 ⁹⁾ ~ +52	°C -20 ⁹⁾ ~ +52	°C -20 ⁹⁾ ~ +52
Heat Min ~ Max	°C -20 ~ +24	°C -20 ~ +24	°C -20 ~ +24	°C -20 ~ +24	°C -20 ~ +24	°C -20 ~ +24	°C -20 ~ +24

Technical focus

- 2 installation possibilities (horizontal / vertical)
- Maximum external static pressure: 150 Pa
- Selectable inlet air position (rear / bottom entry)
- Improved drain pan suitable for both horizontal / vertical installation
- Drain pump included
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for the long duct piping case*
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®

* The performance of nanoe™ X air can be expected even by 10 m long duct by Panasonic internal survey.


2 installation possibilities (horizontal / vertical)

Vertical installation is available.
ESP 150Pa, sufficient for remotely installing units away from the rooms.



Improved drain pan design

Drain pan is shared in both cases horizontal and vertical installation.
No need to modify the unit.





CZ-RTC5B

New
2023

Optional:

CONEX



CONEX wired remote controller, white.



CONEX wired remote controller, black.

Econavi sensor.
CZ-CENSC1

Three phase

Kit	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Remote controller	KIT-71PF3ZH48	KIT-100PF3ZH48	KIT-125PF3ZH48	KIT-140PF3ZH48
Cooling capacity Nominal (Min - Max)	kW 6,8[2,2 - 7,8]	kW 9,5[3,1 - 11,4]	kW 12,1[3,2 - 13,6]	kW 13,4[3,3 - 15,3]
EER ¹⁾ Nominal (Min - Max)	W/W 3,74[2,41 - 5,64]	W/W 4,09[2,82 - 5,08]	W/W 3,53[3,00 - 5,00]	W/W 3,38[2,59 - 4,18]
SEER / η _{s,c} ²⁾	7,1 A++	7,4 A++	281,0%	275,2%
Pdesign	kW 6,8	kW 9,5	kW 12,1	kW 13,4
Input power Nominal (Min - Max)	kW 1,82[0,39 - 3,24]	kW 2,32[0,61 - 4,04]	kW 3,43[0,64 - 4,54]	kW 3,96[0,79 - 5,90]
Annual energy consumption ³⁾	kWh/a 332	kWh/a 447	kWh/a —	kWh/a —
Heating capacity Nominal (Min - Max)	kW 7,5[2,0 - 9,0]	kW 10,8[3,1 - 13,5]	kW 13,5[3,2 - 15,4]	kW 15,5[3,3 - 17,4]
COP ¹⁾ Nominal (Min - Max)	W/W 4,03[3,16 - 5,41]	W/W 3,88[3,07 - 5,25]	W/W 3,46[3,06 - 5,16]	W/W 3,33[3,14 - 4,29]
SCOP / η _{s,h} ²⁾	4,7 A++	4,3 A+	165,0%	162,6%
Pdesign at -10 °C	kW 4,7	kW 7,8	kW 9,3	kW 9,5
Input power Nominal (Min - Max)	kW 1,86[0,37 - 2,85]	kW 2,78[0,59 - 4,40]	kW 3,90[0,62 - 5,04]	kW 4,65[0,77 - 5,55]
Annual energy consumption ³⁾	kWh/a 1394	kWh/a 2540	kWh/a —	kWh/a —
Indoor unit	S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
External static pressure ⁴⁾ Nominal (Min - Max)	Pa 30[10 - 150]	Pa 40[10 - 150]	Pa 50[10 - 150]	Pa 50[10 - 150]
Air flow Hi / Med / Lo	m ³ /min 21,0/19,0/15,0	m ³ /min 32,0/26,0/21,0	m ³ /min 34,0/29,0/23,0	m ³ /min 36,0/32,0/25,0
Moisture removal volume	L/h 2,7	L/h 3,2	L/h 4,1	L/h 4,9
Sound pressure ⁵⁾ Hi / Med / Lo	dB(A) 30/26/23	dB(A) 33/29/25	dB(A) 35/31/27	dB(A) 39/35/29
Sound power Hi / Med / Lo	dB(A) 53/49/46	dB(A) 56/52/48	dB(A) 58/54/50	dB(A) 62/58/52
Dimension HxWxD	mm 250x1000x730	mm 250x1400x730	mm 250x1400x730	mm 250x1400x730
Net weight	kg 30	kg 39	kg 39	kg 39
nanoe X Generator	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-71PZH4E8	U-100PZH4E8	U-125PZH4E8	U-140PZH4E8
Power supply	V 380 - 400 - 415			
Current Cool	A 3,05 - 2,90 - 2,80	A 3,85 - 3,70 - 3,50	A 5,65 - 5,40 - 5,20	A 6,55 - 6,20 - 6,00
Heat	A 3,15 - 3,00 - 2,90	A 4,65 - 4,40 - 4,20	A 6,50 - 6,20 - 5,95	A 7,75 - 7,40 - 7,05
Air flow Cool / Heat	m ³ /min 62,0/66,0	m ³ /min 76,0/70,0	m ³ /min 86,0/78,0	m ³ /min 89,0/83,0
Sound pressure Cool / Heat (Hi)	dB(A) 48/50	dB(A) 52/52	dB(A) 55/55	dB(A) 56/56
Sound power Cool / Heat (Hi)	dB(A) 65/67	dB(A) 69/69	dB(A) 73/73	dB(A) 74/74
Dimension HxWxD	mm 996x980x370	mm 996x980x370	mm 996x980x370	mm 996x980x370
Net weight	kg 66	kg 82	kg 84	kg 84
Piping diameter Liquid	Inch (mm) 3/8[9,52]	Inch (mm) 3/8[9,52]	Inch (mm) 3/8[9,52]	Inch (mm) 3/8[9,52]
Gas	Inch (mm) 5/8[15,88]	Inch (mm) 5/8[15,88]	Inch (mm) 5/8[15,88]	Inch (mm) 5/8[15,88]
Pipe length range	m 5 ~ 60	m 5 ~ 100	m 5 ~ 100	m 5 ~ 100
Elevation difference (in / out) ⁸⁾	m 15/30	m 15/30	m 15/30	m 15/30
Pre-charged pipe length	m 30	m 30	m 30	m 30
Additional gas amount	g/m 30	g/m 40	g/m 40	g/m 40
Refrigerant (R32) / CO ₂ Eq.	kg / T 1,95/1,32	kg / T 2,70/1,82	kg / T 3,00/2,03	kg / T 3,00/2,03
Operating range Cool Min ~ Max	°C -15 ~ +52	°C -20 ⁹⁾ ~ +52	°C -20 ⁹⁾ ~ +52	°C -20 ⁹⁾ ~ +52
Heat Min ~ Max	°C -20 ~ +24			

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) Medium external static pressure setting from factory. 5) The sound pressure of the units shows the value measured at the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/004-97 specification. 6) Connect the liquid socket tube [Ø6,35-Ø9,52] to the liquid tubing side indoor unit. 7) Connect the gas socket tube [Ø12,70-Ø15,88] to the gas tubing side indoor unit. 8) Outdoor unit located lower / outdoor unit located higher. 9) Pipe length up to 30 m. * Recommended fuse for the indoor 3 A. ** Above values are in the case of standard installation(horizontal installation in the ceiling, rear side air intake) and nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
CZ-CAPWFC1	Commercial Wi-Fi Adaptor

Accessories

PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-CENSC1	Econavi energy saving sensor
CZ-56DAF2	Air outlet plenum for S-3650PF3E
CZ-90DAF2	Air outlet plenum for S-6071PF3E
CZ-160DAF2	Air outlet plenum for S-1014PF3E



SEER and SCOP: For S-6071PF3E + U-71PZH4E5. SUPER QUIET: For S-3650PF3E + U-36PZH3E5. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

PACi NX Series Standard adaptive ducted unit - PF3 · R32

Adaptive ducted unit - PF3.

2 installation possibilities (horizontal / vertical) with high ESP 150Pa allows flexible installation.



Single phase							
	3,6 kW	5,0 kW	6,0 kW	7,1 kW	10,0 kW	12,5 kW	14,0 kW
Kit	KIT-36PF3Z5	KIT-50PF3Z5	KIT-60PF3Z5	KIT-71PF3Z5	KIT-100PF3Z5	KIT-125PF3Z5	KIT-140PF3Z5
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B
Cooling capacity Nominal [Min - Max]	kW	3,4[1,5 - 4,0]	5,0[1,5 - 5,3]	5,7[2,0 - 6,3]	6,8[2,6 - 7,7]	9,5[3,0 - 11,4]	12,1[3,2 - 13,5]
EER ¹⁾ Nominal [Min - Max]	W/W	3,78[3,51 - 5,00]	2,78[2,76 - 4,63]	3,54[2,63 - 5,88]	3,18[2,69 - 4,56]	3,57[2,36 - 5,08]	3,40[2,76 - 5,08]
SEER / η_{s,c} ²⁾	6,0 A+	6,5 A++	6,4 A++	6,0 A+	6,6 A++	257,4%	252,2%
Pdesign	kW	3,4	5,0	5,7	6,8	9,5	12,1
Input power Nominal [Min - Max]	kW	0,90[0,30 - 1,14]	1,80[0,32 - 1,92]	1,61[0,34 - 2,40]	2,14[0,57 - 2,86]	2,66[0,59 - 4,84]	3,56[0,63 - 4,90]
Annual energy consumption ³⁾	kWh/a	198	267	310	391	502	—
Heating capacity Nominal [Min - Max]	kW	3,4[1,5 - 4,6]	5,0[1,5 - 5,9]	5,7[1,8 - 7,0]	6,8[2,1 - 8,1]	9,5[3,0 - 13,5]	12,1[3,3 - 15,0]
COP ¹⁾ Nominal [Min - Max]	W/W	4,15[3,51 - 5,36]	3,62[3,06 - 5,36]	4,04[2,82 - 6,21]	4,00[3,03 - 5,68]	4,09[3,00 - 5,08]	3,56[3,16 - 5,24]
SCOP / η_{s,h} ²⁾	4,0 A+	4,0 A+	4,4 A+	4,1 A+	3,9 A	142,6%	140,6%
Pdesign at -10 °C	kW	2,4	3,8	4,4	4,7	7,8	9,3
Input power Nominal [Min - Max]	kW	0,82[0,28 - 1,31]	1,38[0,28 - 1,73]	1,41[0,29 - 2,48]	1,70[0,37 - 2,67]	2,32[0,59 - 4,50]	3,40[0,63 - 4,74]
Annual energy consumption ³⁾	kWh/a	839	1303	1376	1591	2795	—
Indoor unit	S-3650PF3E	S-3650PF3E	S-6071PF3E	S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
External static pressure ⁴⁾ Nominal [Min - Max]	Pa	30[10 - 150]	30[10 - 150]	30[10 - 150]	30[10 - 150]	40[10 - 150]	50[10 - 150]
Air flow Hi / Med / Lo	m³/min	14,0/13,0/10,0	16,0/15,0/12,0	21,0/19,0/15,0	21,0/19,0/15,0	32,0/26,0/21,0	34,0/29,0/23,0
Moisture removal volume	L/h	0,9	1,9	1,7	2,7	3,2	4,1
Sound pressure ⁵⁾ Hi / Med / Lo	dB(A)	30/27/22	34/30/25	30/26/23	30/26/23	33/29/25	35/31/27
Sound power	dB(A)	53/50/45	57/53/48	53/49/46	53/49/46	56/52/48	58/54/50
Dimension	HxWxD	mm	250x800x730	250x800x730	250x1000x730	250x1000x730	250x1400x730
Net weight	kg	25	25	30	30	39	39
nanoe X Generator		Mark 2	Mark 2	Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit	U-36PZ3E5	U-50PZ3E5	U-60PZ3E5A	U-71PZ3E5A	U-100PZ3E5	U-125PZ3E5	U-140PZ3E5
Power supply	V	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240	220-230-240
Current Cool	A	4,15-4,00-3,85	8,35-8,00-7,65	7,45-7,15-6,85	9,95-9,50-9,10	13,30-12,70-12,20	17,20-16,40-15,80
Heat	A	3,85-3,70-3,50	6,45-6,20-5,95	6,55-6,25-6,00	7,90-7,55-7,25	11,60-11,10-10,60	16,40-15,70-15,00
Air flow Cool / Heat	m³/min	33,6/34,0	32,7/31,9	42,6/41,5	44,7/45,9	73,0/73,0	82,0/80,0
Sound pressure Cool / Heat [Hi]	dB(A)	46/47	46/46	47/48	48/49	52/52	55/55
Sound power Cool / Heat [Hi]	dB(A)	64/66	64/64	64/65	66/68	70/70	73/73
Dimension	HxWxD	mm	619x824x299	619x824x299	695x875x320	695x875x320	996x980x370
Net weight	kg	32	35	42	50	83	87
Piping diameter Liquid	Inch [mm]	1/4[06,35]	1/4[06,35]	1/4[06,35] ⁶⁾	1/4[06,35] ⁶⁾	3/8[9,52]	3/8[9,52]
Gas	Inch [mm]	1/2[012,7]	1/2[012,7]	1/2[012,7] ⁷⁾	5/8[015,88]	5/8[015,88]	5/8[015,88]
Pipe length range	m	3 - 15	3 - 20	3 - 40	3 - 40	5 - 50	5 - 50
Elevation difference [in / out] ⁸⁾	m	15/15	15/15	15/30	20/30	15/30	15/30
Pre-charged pipe length	m	7,5	7,5	30	30	30	30
Additional gas amount	g/m	10	15	15	17	45	45
Refrigerant (R32) / CO ₂ Eq.	kg / T	0,87/0,59	1,14/0,77	1,15/0,78	1,32/0,89	2,40/1,62	2,80/1,89
Operating range Cool Min ~ Max	°C	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43
Heat Min ~ Max	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24

Technical focus

- 2 installation possibilities (horizontal / vertical)
- Maximum external static pressure: 150 Pa
- Selectable inlet air position (rear / bottom entry)
- Improved drain pan suitable for both horizontal / vertical installation
- Drain pump included
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for the long duct piping case*
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®

* The performance of nanoe™ X air can be expected even by 10 m long duct by Panasonic internal survey.


2 installation possibilities (horizontal / vertical)

Vertical installation is available.
ESP 150Pa, sufficient for remotely installing units away from the rooms.



Improved drain pan design

Drain pan is shared in both cases horizontal and vertical installation.
No need to modify the unit.





CZ-RTC5B



+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:**CONEX**

CONEX
wired
remote
controller,
white.
CZ-RTC6W/
BL/BLW

CONEX

CONEX
wired
remote
controller,
black.
CZ-RTC6/BL/
BLW



Infrared
remote
controller.
CZ-RWS3 +
CZ-RWRG3



Econavi
sensor.
CZ-CENSC1

Three phase

10,0 kW 12,5 kW 14,0 kW

KIT-100PF3Z8 KIT-125PF3Z8 KIT-140PF3Z8

CZ-RTC5B CZ-RTC5B CZ-RTC5B

Nominal (Min - Max) kW 9,5[3,0 - 11,4] 12,1[3,2 - 13,5] 13,4[3,3 - 15,0]

Nominal (Min - Max) W/W 3,57[2,36 - 5,08] 3,40[2,76 - 5,08] 3,16[2,56 - 5,08]

SEER / η_{s,c}²⁾ 6,5 A++ 256,2% 251,4%

Pdesign kW 9,5 12,1 13,4

Input power Nominal (Min - Max) kW 2,66[0,59 - 4,84] 3,56[0,63 - 4,90] 4,24[0,65 - 5,86]

Annual energy consumption³⁾ kWh/a 508 — —

Heating capacity Nominal (Min - Max) kW 9,5[3,0 - 13,5] 12,1[3,3 - 15,0] 13,4[3,4 - 16,0]

Nominal (Min - Max) W/W 4,09[3,00 - 5,08] 3,56[3,16 - 5,24] 3,76[3,03 - 5,23]

SCOP / η_{s,h}²⁾ 3,9 A 142,6% 140,6%

Pdesign at -10 °C kW 7,8 9,3 9,5

Input power Nominal (Min - Max) kW 2,32[0,59 - 4,50] 3,40[0,63 - 4,74] 3,56[0,65 - 5,28]

Annual energy consumption³⁾ kWh/a 2795 — —

Indoor unit S-1014PF3E S-1014PF3E S-1014PF3E

External static pressure⁴⁾ Nominal (Min - Max) Pa 40[10 - 150] 50[10 - 150] 50[10 - 150]Air flow Hi / Med / Lo m³/min 32,0/26,0/21,0 34,0/29,0/23,0 36,0/32,0/25,0

Moisture removal volume L/h 3,2 4,1 4,9

Sound pressure⁵⁾ Hi / Med / Lo dB(A) 33/29/25 35/31/27 39/35/29

Sound power Hi / Med / Lo dB(A) 56/52/48 58/54/50 62/58/52

Dimension HxWxD mm 250 x 1400 x 730 250 x 1400 x 730 250 x 1400 x 730

Net weight kg 39 39 39

nanoe X Generator Mark 2 Mark 2 Mark 2

Outdoor unit U-100PZ3E8 U-125PZ3E8 U-140PZ3E8

Power supply V 380 - 400 - 415 380 - 400 - 415 380 - 400 - 415

Current Cool A 4,45 - 4,20 - 4,05 5,75 - 5,45 - 5,25 6,85 - 6,50 - 6,30

Heat A 3,85 - 3,70 - 3,55 5,50 - 5,20 - 5,05 5,75 - 5,45 - 5,25

Air flow Cool / Heat m³/min 73,0/73,0 82,0/80,0 84,0/82,0

Sound pressure Cool / Heat (Hi) dB(A) 52/52 55/55 56/56

Sound power Cool / Heat (Hi) dB(A) 70/70 73/73 74/74

Dimension HxWxD mm 996 x 980 x 370 996 x 980 x 370 996 x 980 x 370

Net weight kg 83 87 87

Piping diameter Liquid Inch (mm) 3/8[9,52] 3/8[9,52] 3/8[9,52]

Gas Inch (mm) 5/8[15,88] 5/8[15,88] 5/8[15,88]

Pipe length range m 5 ~ 50 5 ~ 50 5 ~ 50

Elevation difference (in / out)⁸⁾ m 15/30 15/30 15/30

Pre-charged pipe length m 30 30 30

Additional gas amount g/m 45 45 45

Refrigerant (R32) / CO₂ Eq. kg / T 2,40/1,62 2,80/1,89 2,80/1,89

Operating range Cool Min ~ Max °C -10 ~ +43 -10 ~ +43 -10 ~ +43

Heat Min ~ Max °C -15 ~ +24 -15 ~ +24 -15 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) Medium external static pressure setting from factory. 5) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/004-97 specification. 6) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 7) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 8) Outdoor unit located lower / outdoor unit located higher. * Recommended fuse for the indoor 3 A. ** Above values are in the case of standard installation(horizontal installation in the ceiling, rear side air intake) and nanoe™ X OFF.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
CZ-CAPWFC1	Commercial Wi-Fi Adaptor

Accessories

PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400 x 900 x 400 mm
CZ-CENSC1	Econavi energy saving sensor
CZ-56DAF2	Air outlet plenum for S-3650PF3E
CZ-90DAF2	Air outlet plenum for S-6071PF3E
CZ-160DAF2	Air outlet plenum for S-1014PF3E



SEER: For S-1014PF3E + U-100PZ3E5. SCOP: For S-6071PF3E + U-60PZ3E5A. SUPER QUIET: For S-3650PF3E + U-36PZ3E5. INTERNET CONTROL: Optional.


Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

Panasonic Big PACi, not only environmentally friendly but also a groundbreaking product.

Big PACi with R32 has been introduced with full renewal of its indoor unit, also offering hydronic application by PACi Water heat exchanger.

1 Compact and light indoor body

Compact and light indoor body, keeping the high efficiency, has a split-able design for easy installation within a limited narrow space. Plus ease of maintenance due to the simplified disassembly design.



2 Easy pipe work with split-able hide-away indoor design

Heat exchanger and fan elements (fan + casing) can be separated during installation. The hide-away indoor unit is easily reassembled and will fit through a narrow space.

3 High external static pressure, maximum 200 Pa* setting

A high static pressure enables the use of long ducts for installation in a wide range of spaces.

* S-250PE3E5B.

Compact and light indoor body, keeping high efficiency

15% lighter weight vs conventional model drastically improves installation work.

	Conventional model	Panasonic model
20,0 kW	100 kg	86 kg
25,0 kW	104 kg	88 kg

4 Panasonic Comfort Cloud App control

Smartphone ready to control of PACi systems with Panasonic Comfort Cloud App*.

* Panasonic Wi-Fi Adaptor CZ-CAPWFC1 is required.

Depth was reduced by
230 mm



Maximum 200 Pa* static pressure setting

A high static pressure enables the use of long ducts for installation in a wide range of spaces.

3-step static pressure set up.

Selectable of static pressure modes can change 200 Pa / 130 Pa / 75 Pa for extra installation flexibility.

* In case of S-250PE3E5B.

Easy installation with light components

Indoor unit can easily be split into 3 components, the heaviest of which weighs only 48 kg.



Dimensions of each component (lightweight design for easy disassembly).



The weight is for S-200PE3E5B model.

Panasonic Big PACi high static pressure hide-away 20,0-25,0 kW · R32

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:



Three phase

Kit	20,0 kW	25,0 kW
Remote controller	KIT-200PE3ZH8	KIT-250PE3ZH8
Cooling capacity	Nominal [Min - Max] kW	19,5[5,7 - 21,0]
EER ¹⁾	Nominal [Min - Max] W/W	3,22[3,09 - 4,52]
SEER / η_{s,c} ²⁾	207,0%	190,6%
Pdesign	kW	19,5
Input power	Nominal [Min - Max] kW	6,06[1,26 - 6,80]
Heating capacity	Nominal [Min - Max] kW	22,4[5,0 - 25,0]
COP ¹⁾	Nominal [Min - Max] W/W	3,61[3,16 - 4,76]
SCOP / η_{s,h} ²⁾	141,3%	142,7%
Pdesign at -10 °C	kW	17,0
Input power	Nominal [Min - Max] kW	6,21[1,05 - 7,90]
Indoor unit	S-200PE3E5B	S-250PE3E5B
Power supply	V / ph / Hz	220 - 230 - 240 / 1 / 50
External static pressure at shipment (adjustable)	Pa	75 ³⁾ - 120 - 180
Air flow	Hi / Med / Lo	m ³ /min
Sound pressure ⁴⁾	Hi / Med / Lo	dB(A)
Dimension / Net weight	HxWxD	mm / kg
Outdoor unit	U-200PZH2E8	U-250PZH2E8
Power supply	V / ph / Hz	380 - 400 - 415 / 3 / 50
Recommended fuse	A	30
Air flow	Cool / Heat	m ³ /min
Sound pressure	Cool / Heat (Hi)	dB(A)
Sound power	Cool / Heat (Hi)	dB(A)
Dimension ⁵⁾ / Net weight	HxWxD	mm / kg
Piping diameter	Liquid / Gas	Inch (mm)
Pipe length range / Elevation difference (in / out)	m / m	5 ~ 90 / 30
Pre-charged pipe length / Additional gas amount	m / g/m	30 / 60
Refrigerant (R32) / CO ₂ Eq.	kg / T	4,20 / 2,835
Operating range	Cool Min ~ Max	°C
	Heat Min ~ Max	°C

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/626/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 5) Add 100 mm for indoor unit or 70 mm for outdoor unit for piping port. * No filter included.

Accessories

CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver

Accessories


CZ-CAPDC3	Demand control for Mini ECOi and PACi outdoor units
CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-CENSC1	Econavi energy saving sensor

Demand response compliant as a standard function

CZ-CAPDC3. This terminal allows demand control of the outdoor unit.

Several setting levels are available:

- Level-1, 2, 3: 75 / 50 / 0%
 - Level-1, 2 can be set in 40 - 100% (40, 45, 50...95, 100: each 5%)
- CZ-CAPDC3 also allows for forced stop which can be used for fire-alarm connection on LV3.




INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

Commercial twin, triple and double-twin systems · R32

With this system, a single outdoor unit can split its capacity simultaneously across up to 4 indoor units, for better distribution within the space. This makes the system particularly apt for common areas. It reduces noise concentration and enables the same temperature to be reached around the room. A wide variety of the same type of indoor units can be connected in multi combinations (including wall-mounted, cassette, hide-away and ceiling).





1 PACi NX Elite from 7,1 to 14,0 kW

Up to 4 indoor units can be connected to the same outdoor unit. Panasonic's Elite units 7,1, 10,0, 12,0 and 14,0 can be installed as twin, triple and double-twin systems. The indoor units can be combined as per the selection table. The operation will always be simultaneous. All the indoor units will work with the same settings.

2 PACi NX Standard from 10,0 to 14,0 kW

Up to 2 indoor units connectable on the same outdoor. Panasonic's Standard units can be installed as single and twin systems. The indoor units can be combined following the selection table. The operation will always be simultaneous. All the indoor units will work with the same settings.

3 Big PACi Elite from 20,0 to 25,0 kW

Up to 4 indoor units can be connected to the same outdoor unit. Panasonic's PACi units 20,0 and 25,0 can be installed as twin, triple and double-twin systems. The indoor units can be combined as per the selection table. The operation will always be simultaneous. All the indoor units will work with the same settings.

Commercial twin, triple and double-twin systems · R32

New
2023



PACi Elite outdoor units · R32

	7,1 kW	10,0 kW	12,5 kW	14,0 kW	20,0 kW	Big PACi 25,0 kW
Outdoor unit single phase	U-71PZH4E5	U-100PZH4E5	U-125PZH4E5	U-140PZH4E5	—	—
Outdoor unit three phase	U-71PZH4E8	U-100PZH4E8	U-125PZH4E8	U-140PZH4E8	U-200PZH2E8	U-250PZH2E8
Cooling capacity ¹⁾	Nominal (Min - Max) kW	7,1(2,2 - 9,0)	9,5(3,1 - 12,5)	12,5(3,2 - 14,0)	13,4(3,3 - 16,0)	20,0(5,7 - 22,4)
Heating capacity ¹⁾	Nominal (Min - Max) kW	8,0(2,0 - 9,0)	11,2(3,1 - 14,0)	14,0(3,2 - 16,0)	16,0(3,3 - 18,0)	22,4(5,0 - 25,0)
Power supply	Single phase V	220 - 230 - 240	220 - 230 - 240	220 - 230 - 240	—	—
	Three phase V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Connection indoor / outdoor	mm ²	2x1,5 or 2,5	2x1,5 or 2,5	2x1,5 or 2,5	2x1,5 or 2,5	—
Air flow	Cool / Heat m ³ /min	62,0/66,0	76,0/70,0	86,0/78,0	89,0/83,0	164/164
Sound pressure	Cool / Heat (Hi) dB(A)	48/50	52/52	55/55	56/56	59/61
Sound power	Cool / Heat (Hi) dB(A)	65/67	69/69	73/73	74/74	77/79
Dimension	H x W x D mm	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	1500 x 980 x 370
Net weight	1ph / 3ph kg	66	84/82	86/84	86/84	117
Piping diameter	Liquid Inch (mm)	3/8(9,52)	3/8(9,52)	3/8(9,52)	3/8(9,52)	1/2(12,70)
	Gas Inch (mm)	5/8(15,88)	5/8(15,88)	5/8(15,88)	5/8(15,88)	1(25,40)
Pipe length range	Min ~ Max m	5 ~ 60	5 ~ 100	5 ~ 100	5 ~ 100	5 ~ 60
Elevation difference (in / out)	Max m	15/30 ²⁾	15/30 ²⁾	15/30 ²⁾	15/30 ²⁾	30
Pre-charged pipe length	m	30	30	30	30	30
Additional gas amount	g/m	30	40	40	40	60
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,95/1,32	2,70/1,82	3,00/2,03	3,00/2,03	4,20/2,835
Operating range	Cool Min ~ Max °C	-15 ~ +52	-20 ³⁾ ~ +52	-20 ³⁾ ~ +52	-20 ³⁾ ~ +52	-15 ~ +46
	Heat Min ~ Max °C	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24

1) With 4 way 90x90 cassette. 2) Outdoor unit located lower / outdoor unit located higher. 3) Pipe length up to 30 m.



PACi NX Standard outdoor units · R32

	10,0 kW	12,5 kW	14,0 kW	
Outdoor unit single phase	U-100PZ3E5	U-125PZ3E5	U-140PZ3E5	
Outdoor unit three phase	U-100PZ3E8	U-125PZ3E8	U-140PZ3E8	
Cooling capacity ¹⁾	Nominal (Min - Max) kW	10,0(3,0 - 11,5)	12,5(3,2 - 13,5)	14,0(3,3 - 15,0)
Heating capacity ¹⁾	Nominal (Min - Max) kW	10,0(3,0 - 14,0)	12,5(3,3 - 15,0)	14,0(3,4 - 16,0)
Power supply	Single phase V	220-230-240	220-230-240	220-230-240
	Three phase V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Connection indoor / outdoor	mm ²	2x1,5 or 2,5	2x1,5 or 2,5	2x1,5 or 2,5
Air flow	Cool / Heat m ³ /min	73,0/73,0	82,0/80,0	84,0/82,0
Sound pressure	Cool / Heat (Hi) dB(A)	52/52	55/55	56/56
Sound power	Cool / Heat (Hi) dB(A)	70/70	73/73	74/74
Dimension	H x W x D mm	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net weight	kg	83	87	87
Piping diameter	Liquid Inch (mm)	3/8(9,52)	3/8(9,52)	3/8(9,52)
	Gas Inch (mm)	5/8(15,88)	5/8(15,88)	5/8(15,88)
Pipe length range	Min ~ Max m	5 ~ 50	5 ~ 50	5 ~ 50
Elevation difference (in / out) ²⁾	Max m	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30
Additional gas amount	g/m	45	45	45
Refrigerant (R32) / CO ₂ Eq.	kg / T	2,4/1,62	2,8/1,89	2,8/1,89
Operating range	Cool Min ~ Max °C	-10 ~ +43	-10 ~ +43	-10 ~ +43
	Heat Min ~ Max °C	-15 ~ 24	-15 ~ 24	-15 ~ 24

1) With 4 way 90x90 cassette. 2) Outdoor unit located lower / outdoor unit located higher.

Compatible indoor units for multi combinations

Optional:

PANASONIC AC SMART CLOUD and AC SERVICE CLOUD: Optional.				

Wall-mounted	Indoor unit	Cooling capacity	Heating capacity	Dimension	Sound pressure ¹⁾	Air flow ²⁾
		kW	kW	HxWxD mm	Hi / Med / Lo dB(A)	Hi / Med / Lo m³/min
3,6 - 5,0 kW	S-3650PK3E	3,6 - 5,0	4,0 - 5,6	302x1120x236	35/31/27 - 40/36/32	13,0/11,0/9,0 - 16,0/13,5/11,0
6,0 - 7,1 kW	S-6010PK3E	6,1 - 7,1	7,0 - 8,0	302x1120x236	47/44/40 - 47/44/40	20,0/17,5/14,5 - 20,0/17,5/14,5
10,0 kW	S-6010PK3E	9,5	9,5	302x1120x236	49/45/41	22,0/18,5/15,0

PANASONIC AC SMART CLOUD and AC SERVICE CLOUD: Optional.										

4 way 60x60 cassette	Indoor unit (panel CZ-KPY4)	Cooling capacity	Heating capacity	Dimension indoor / panel	Sound pressure ¹⁾	Air flow ²⁾
		kW	kW	HxWxD mm	Hi / Med / Lo dB(A)	Hi / Med / Lo m³/min
2,5 kW	S-25PY3E	2,5	3,2	243x575x575 / 30x625x625	31/28/25	8,5/7,0/6,0
3,6 kW	S-36PY3E	3,6	4,0	243x575x575 / 30x625x625	34/30/25	9,5/7,5/6,0
5,0 kW	S-50PY3E	5,0	5,6	243x575x575 / 30x625x625	39/34/27	12,0/9,5/6,5
6,0 kW	S-60PY3E	6,0	7,0	243x575x575 / 30x625x625	43/37/31	14,0/10,5/8,0

PANASONIC AC SMART CLOUD and AC SERVICE CLOUD: Optional.										

4 way 90x90 cassette	Indoor unit (panels CZ-KPU3W/3AW)	Cooling capacity	Heating capacity	Dimension indoor / panel	Sound pressure ¹⁾	Air flow ²⁾
		kW	kW	HxWxD mm	Hi / Med / Lo dB(A)	Hi / Med / Lo m³/min
3,6 - 5,0 kW	S-3650PU3E	3,6 - 5,0	4,0 - 5,6	256x840x840 / 33,5x950x950	30/28/27 - 32/29/27	14,5/13,0/11,5 - 16,5/13,5/11,5
6,0 - 7,1 kW	S-6071PU3E	6,0 - 7,1	7,0 - 8,0	256x840x840 / 33,5x950x950	36/31/28 - 37/31/28	21,0/16,0/13,0 - 22,0/16,0/13,0
10,0 - 12,5 kW	S-1014PU3E	10,0 - 12,5	11,2 - 14,0	319x840x840 / 33,5x950x950	45/38/32 - 46/39/33	36,0/26,0/18,0 - 37,0/27,0/19,0
14,0 kW	S-1014PU3E	14,0	16,0	319x840x840 / 33,5x950x950	47/40/34	38,0/29,0/20,0

PANASONIC AC SMART CLOUD and AC SERVICE CLOUD: Optional.										

Ceiling	Indoor unit	Cooling capacity	Heating capacity	Dimension	Sound pressure ¹⁾	Air flow ²⁾
		kW	kW	HxWxD mm	Hi / Med / Lo dB(A)	Hi / Med / Lo m³/min
3,6 - 5,0 kW	S-3650PT3E	3,5 - 5,0	4,0 - 5,6	235x960x690	36/32/28 - 37/33/28	14,0/12,0/10,5 - 15,0/12,5/10,5
6,0 - 7,1 kW	S-6071PT3E	6,0 - 6,8	7,0 - 8,0	235x1275x690	38/34/29 - 39/35/30	20,0/17,0/14,5 - 21,0/18,0/15,5
10,0 - 12,5 kW	S-1014PT3E	9,5 - 12,1	11,2 - 14,0	235x1590x690	42/37/34 - 46/40/35	30,0/25,0/23,0 - 34,0/28,0/24,0
14,0 kW	S-1014PT3E	13,4	16,0	235x1590x690	47/41/36	35,0/29,0/25,0

PANASONIC AC SMART CLOUD and AC SERVICE CLOUD: Optional.										

Adaptive ducted unit	Indoor unit	Cooling capacity	Heating capacity	Dimension	External static pressure	Sound pressure ¹⁾	Air flow ²⁾
		kW	kW	HxWxD mm	Nominal (Min - Max) Pa	Hi / Med / Lo dB(A)	Hi / Med / Lo m³/min
3,6 - 5,0 kW	S-3650PF3E	3,6 - 5,0	4,0 - 5,6	250x800x730	30(10 - 150) - 30(10 - 150)	30/27/22 - 34/30/25	14,0/13,0/10,0 - 16,0/15,0/12,0
6,0 - 7,1 kW	S-6071PF3E	5,7 - 6,8	7,0 - 7,5	250x1000x730	30(10 - 150) - 30(10 - 150)	30/26/23 - 30/26/23	21,0/19,0/15,0 - 21,0/19,0/15,0
10,0 - 12,5 kW	S-1014PF3E	9,5 - 12,1	10,8 - 13,5	250x1400x730	40(10 - 150) - 50(10 - 150)	33/29/25 - 35/31/27	32,0/26,0/21,0 - 34,0/29,0/23,0
14,0 kW	S-1014PF3E	13,4	15,5	250x1400x730	50(10 - 150)	39/35/29	36,0/32,0/25,0

* The data shown in these tables are based on PACI NX Elite combinations. 1) The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 2) Factory setting.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB. Cooling outdoor 35 °C DB / 24 °C WB. Heating indoor 20 °C DB. Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.

Simultaneous operation system combinations

PACi NX Elite from 7,1 to 14,0 kW simultaneous operation system combinations - R32

Capacity	Indoor	Outdoor			
		7,1 kW	10,0 kW	12,5 kW	14,0 kW
2,5 kW	S-25PY3E	Triple U-71 [2,5, 2,5, 2,5]	Double-twin U-100 [2,5, 2,5, 2,5]		
3,6 kW	S-36PY3E S-3650PF3E S-3650PK3E S-3650PT3E S-3650PU3E	Twin U-71 [3,6, 3,6]	Triple U-100 [3,6, 3,6, 3,6]	Double-twin U-125 [3,6, 3,6, 3,6]	
4,5 kW	S-3650PF3E S-3650PK3E S-3650PT3E S-3650PU3E			Triple U-125 [4,5, 4,5, 4,5]	
5,0 kW	S-50PY3E S-3650PF3E S-3650PK3E S-3650PT3E S-3650PU3E	Twin U-100 [5,0, 5,0]			Triple U-140 [5,0, 5,0, 5,0]
6,0 kW	S-60PY3E S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E			Twin U-125 [6,0, 6,0]	
7,1 kW	S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E				Twin U-140 [7,1, 7,1]




PACi NX Standard from 10,0 to 14,0 kW simultaneous operation system combinations - R32

Capacity	Indoor	Outdoor		
		10,0 kW	12,5 kW	14,0 kW
5,0 kW	S-50PY3E S-3650PF3E S-3650PK3E S-3650PT3E S-3650PU3E	Twin U-100 [5,0, 5,0]		
6,0 kW	S-60PY3E S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E		Twin U-125 [6,0, 6,0]	
7,1 kW	S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E			Twin U-140 [7,1, 7,1]


Big PACi Elite from 20,0 to 25,0 kW simultaneous operation system combinations - R32

Capacity	Indoor	Outdoor	
		20,0 kW	25,0 kW
5,0 kW	S-50PY3E S-3650PF3E S-3650PK3E S-3650PT3E S-3650PU3E	Double-twin U-200 [5,0, 5,0, 5,0, 5,0]	
6,0 kW	S-60PY3E S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E		Double-twin U-250 [6,0, 6,0, 6,0, 6,0]
7,1 kW	S-6071PF3E S-6010PK3E S-6071PT3E S-6071PU3E	Triple U-200 [7,1, 7,1, 7,1]	
10,0 kW	S-1014PF3E S-6010PK3E S-1014PT3E S-1014PU3E	Twin U-200 [10,0, 10,0]	
12,5 kW	S-1014PF3E S-1014PT3E S-1014PU3E		Twin U-250 [12,5, 12,5]

Refrigerant piping arrangements



Double-twin



PACi NX Elite twin, triple and double-twin system from 7,1 to 14,0 kW

Joint distribution (sold separately)

A= CZ-P224BK2BM

B= CZ-P3 HPC2BM

C= CZ-P224BK2BM

PACi NX Standard twin system from 10,0 to 14,0 kW

Joint distribution (sold separately)

A= CZ-P224BK2BM

PACi Elite twin, triple and double-twin system from 20,0 to 25,0 kW

Joint distribution (sold separately)

A= CZ-P680BK2BM

B= CZ-P3 HPC2BM

C= CZ-P224BK2BM

Twin System	PACi NX Standard single and twin system from 7,1 to 14,0 kW		PACi NX Elite and PACi Elite twin, triple and double-twin system from 7,1 to 25 kW							
	Indoor unit combinations (see examples above)	Equivalent lengths and height differences (m) for outdoor unit sizes...	Indoor unit combinations (see examples above)				Equivalent lengths and height differences (m) for outdoor unit sizes from 7,1 to 14,0 kW		Equivalent lengths and height differences (m) for outdoor unit sizes from 20,0 to 25,0 kW	
			Single	Twin	Triple	Double-Twin				
Total pipe length	L	L + L1 + L2 ≤ 50 m	L	L + L1 + L2	L + L1 + L2 + L3	L + L1 + L2 + L3 + L4 + L5 + L6	U-60/U-71: ≤ 50 m U-100/125/140: ≤ 75 m	U-200: ≤ 100 m U-250: ≤ 80 m	U-200: ≤ 100 m U-250: ≤ 80 m	
Maximum pipe length from outdoor unit to most distant indoor unit	-	-	-	-	L + L1 or L + L2 or L + L3	L + L1 + L3 or L + L1 + L4 or L + L2 + L5 or L + L2 + L6	-	U-200: 90 m U-250: 60 m	U-200: 90 m U-250: 60 m	
Maximum branch pipe length	-	L1 L2 ≤ 15	-	L1 or L2	L1 or L2 or L3	L1 + L3 or L1 + L4 or L2 + L5 or L2 + L6	≤ 15 m	≤ 20 m	≤ 20 m	
Maximum branch pipe length differences	-	L1 > L2 L1 - L2 ≤ 10	-	L1 > L2: L1 - L2	L1 > L2 > L3: L1 - L2 L2 - L3 L1 - L3	L2 + L6 (Max.) L1 + L3 (Min.): (L2 + L6) - (L1 + L3)	≤ 10 m	≤ 10 m	≤ 10 m	
Maximum pipe length differences after first branch [Double-Twin]	-	-	-	-	-	L2 > L1: L2 - L1	≤ 10 m	≤ 10 m	≤ 10 m	
Maximum pipe length differences after second branch [Double-Twin]	-	-	-	-	-	L4 > L3: L4 - L3 L6 > L5: L6 - L5	≤ 10 m	≤ 10 m	≤ 10 m	
Height difference (outdoor unit located higher)	H1	H1 ≤ 30	H1	H1	H1	H1	≤ 30 m	≤ 30 m	≤ 30 m	
Height difference (outdoor unit located lower)	H1	H1 ≤ 15	H1	H1	H1	H1	≤ 15 m	≤ 15 m	≤ 15 m	
Height difference between indoor units	-	H2 ≤ 0,5	-	H2	H2 or H3 or H4	H2 or H3 or H4 or H5 or H6	≤ 0,5 m	≤ 0,5 m	≤ 0,5 m	

Twin System	PACi NX Standard single and twin system from 7,1 to 14,0 kW				PACi NX Elite twin, triple and double-twin system from 7,1 to 14,0 kW						PACi Elite twin, triple and double-twin system from 20,0 to 25,0 kW				
	Outdoor unit main piping diameter (L)	Indoor unit connection tube (L1, L2)	Outdoor unit main piping diameter (L)	Indoor unit connection piping diameter (L1, L2, L3, L4) (mm)	Outdoor unit main piping diameter (L) (mm)	Double-Twin distribution pipe (L1, L2) ¹⁾	Indoor unit connection piping diameter ²⁾								
Unit type capacity	100	125	50	60	71 - 140	36	45	50	60	71	200	250	100 - 125	50	60 - 125
Liquid (mm)	Ø 9,52	Ø 12,70	Ø 6,35	Ø 9,52	Ø 9,52	Ø 6,35	Ø 6,35	Ø 6,35	Ø 9,52	Ø 9,52	Ø 9,52	Ø 12,70	Ø 9,52	Ø 6,35	Ø 9,52
Gas (mm)	Ø 15,88	Ø 15,88	Ø 12,70	Ø 15,88	Ø 15,88	Ø 12,70	Ø 12,70	Ø 12,70	Ø 15,88	Ø 15,88	Ø 25,40	Ø 25,40	Ø 15,88	Ø 12,70	Ø 15,88
Additional gas amount (g/m)	50	50	20	50	50	20	20	20	50	50	60	80	45	20	45

1) Total capacity of indoor unit connected after the branch. 2) 4 way cassette type.

Make additional charges by adding up tube length in an order of main tube (L) > branch tube (L1 > L2 > L3 wide diameter) and then selecting the amount of refrigerant corresponding to the remaining (after charge-less tube length: 30 m) liquid tube diameter and tube length from the above table.

PRO-HT Tank Series for PACi

Enjoy an efficient DHW / heating and cooling tank.

Panasonic commercial PRO-HT Tank solutions meet all needs of your hot water applications providing 65 °C water.

Maximum 65 °C
water outlet temperature



PRO-HT Tank DHW: PAW-VP750DHW and PAW-VP1000LDHW

PRO-HT TANK

Big volume and high temperature tank for commercial application.

1 High performance and high saving

- Energy efficiency class for energy label: A+ (from A+ to F)
- High temperature hot water without booster
- Save installation time and cost by skipping additional accessories

2 Sufficient hot water production


- Maximum water outlet temperature up to 65 °C
- Big volume tanks with 750 L and 1000 L capacity
- Heat exchanger design inhibits limescale

3 Trusted quality

- Double tube heat exchanger following drinking-water regulation
- Tank and heat exchanger made with stainless steel
- Internal and external pickling

Solution example DHW tank 1000 L + PACi

- Ideal for small hotels and high-end residential
- Hot water temperature up to 65 °C



One by one system compatible list with PACi Elite

Model	Tank type	Product compatibility	Hot water outlet temperature without an electric heater
PAW-VP750LDHW-1	DHW	U-250PE2E8A	65 °C
PAW-VP1000LDHW-1	DHW	U-250PE2E8A	65 °C

PRO-HT Tank heating and cooling: PAW-VP380L

Waterborne heating and cooling for floor heating, radiators or fan coils

1 High performance and high saving

- A7 COP 3,26, heating water temperature at 50 °C
- Maximum 50 °C water outlet temperature
- Energy efficiency class: A+++ (from A+++ to D)

2 Simple waterborne heating and cooling solution


- High temperature water without any boosters
- Installation cost can be saved without additional boosters and buffer tanks

3 Trusted quality

- Tank and heat exchanger made with stainless steel
- Internal and external pickling

Heating and cooling tank 380L + PACi 20,0 kW

- Ideal offer for small offices
- Cost saving solution with simple waterborne heating and cooling
- Hot water up to 50 °C



One by one system compatible list with PACi Elite

Model	Tank type	Product compatibility	Water outlet temperature range
PAW-VP380L	Heating and cooling	U-200PZH2E8	5 °C ~ 50 °C

PRO-HT Tank DHW

PRO-HT TANK

High temperature hot water is efficiently produced without any boosters.
 Panasonic commercial PRO-HT Tank solutions can be adapted to various projects from high-end residential to gyms, and hotels.



PRO-HT Tank	PAW-VP750LDHW-1	PAW-VP1000LDHW-1
COP DHW [A +7 °C, W 10–55 °C] EN 16147 ¹⁾	4,10	3,86
COP DHW [A +15 °C, W 10–55 °C] EN 16147 ²⁾	4,79	4,79
Energy efficiency class [from A+ to F] ³⁾	A+	A+
Water volume (net)	L	726
Reference tapping cycle		2XL
Standby heat loss according to EN16147	W/h	77
Maximum water temperature	Heat pump °C	65
	Electrical heater °C	85
Dimension	H x Ø mm	1855x990
Net weight / with water	kg	179 / 905
Stainless steel 316 L tank		Yes
Connections to the water supply network		RP 1½
Average insulation thickness	mm	100
Number of electrical heaters x power	W	1x6000
Electric protection	A	16
Moisture protection (PAW-VP-RTC5B-PAC)		IP24
Heat exchanger connection	Inlet Inch (mm)	1/2(12,70)
	Outlet Inch (mm)	3/4 (19,05)
Outdoor unit	U-250PE2E8A	
Nominal electrical power - related to rated heat output	W	6670
Energy consumption by chosen cycle [A +7 °C, W 10–55 °C]	kWh	6,00
Energy consumption by chosen cycle [A +15 °C, W 10–55 °C]	kWh	5,12
	Voltage V	400
Power supply	Phase	Three phase
	Frequency Hz	50
Maximum power consumption	Without heater W	12900
	With heater W	18900
Dimension	H x W x D mm	1642x1095x529
Net weight	kg	138
Sound pressure at 1 m from outdoor unit	dB(A)	57
Refrigerant (R410A) / CO ₂ Eq.	kg / T	6,4/13,363
Piping diameter	Liquid Inch (mm)	1/2(12,70)
	Gas Inch (mm)	1 (25,40)
Pipe length range ⁴⁾	m	30
Elevation difference (in / out)	m	30 [OU above] 30 [OU below]
Pipe length for nominal capacity	m	7,5
Pre-charged pipe length	m	> 7,5
Additional gas amount	g/m	Refer to manual
Operating range - outdoor ambient	Heat Min ~ Max °C	-20 ~ +35
- 1 Heating of sanitary water up to 55 °C with inlet air temperature at 7 °C, humidity at 89% and inlet water temperature at 10 °C. According to EN16147. 2) Heating of sanitary water up to 55 °C with inlet air temperature at 15 °C, humidity at 74% and inlet water temperature at 10 °C. According to EN16147. 3) Scale from A+ to F following COMMISSION DELEGATED REGULATION (EU) No. 812/2013. 4) The pipe length range is between indoor and outdoor, but does not include additional length for coil.		

This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

* When connected as pressurised, safety valve is mandatory.

Accessories

PAW-VP-RTC5B-PAC Tank controller for PACi system

Technical focus

- Water volume 750 L and 1000 L
- Maximum hot water production 65 °C without boosters
- Heating coil 52 m (750 L) and 63 m (1000 L)
- Tank material 3 mm
- ABS external case



PRO-HT Tank heating and cooling

High temperature hot water is efficiently produced without any boosters.
 Panasonic commercial PRO-HT Tank solutions can be combined with PACi to adapt various projects from high-end residential to small offices.

PRO-HT TANK

PRO-HT Tank			PAW-VP380L
Cooling capacity at 35 °C, water outlet 7 °C	kW		12,8
Heating capacity	kW		25
Heating capacity at +7 °C, heating water temperature at 45 °C	kW		23
COP at +7 °C with heating water temperature at 45 °C	W/W		3,26
Heating energy efficiency class at 35 °C (from A+++ to D)			A+++
$\eta_{s,h}$ (LOT1) ¹⁾	%		193
Dimension	H x Ø	mm	1820 x 690
Water volume (net)	L		380
Shipping weight	kg		99
Connections to the water supply network			RP 1 1/4
Heating water flow ($\Delta T=5$ K, 35 °C)	m³/h		3,9
Water outlet	Cool Min ~ Max °C		5 ~ 15
	Heat Min ~ Max °C		25 ~ 45
Piping diameter	Liquid Inch (mm)		1/2 (12,70)
	Gas Inch (mm)		3/4 (19,05)
Outdoor unit			U-200PZH2E8
Dimension	HxWxD	mm	1500 x 980 x 370
Net weight	kg		117
Sound pressure at 1 m from outdoor unit	dB(A)		57
Refrigerant (R32) / CO ₂ Eq.	kg		4,20 / 3 510
Piping diameter	Liquid Inch (mm)		3/8 (9,52)
	Gas Inch (mm)		1 (25,40) + adapter
Pipe length range ²⁾	m		30
Elevation difference (in / out)	m		30 (OU above) 30 (OU below)
Pipe length for nominal capacity	m		7,5
Pre-charged pipe length	m		> 7,5
Additional gas amount	g/m		Refer to manual
Operating range - outdoor ambient	Cool Min ~ Max °C		-15 ~ +46
	Heat Min ~ Max °C		-20 ~ +35

1) Seasonal space cooling / heating energy efficiency following COMMISSION REGULATION (EU) 811/2013. 2) The pipe length range is between indoor and outdoor, but does not include additional length for coil.

This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

Performance calculation in agreement with Eurovent. Sound pressure measured at 1 m from the outdoor unit and at 1,5 m height.

* Flow switch and water filter are not equipped.

Accessories

PAW-VP-RTC5B-PAC	Tank controller for PACi system
PAW-IU39	Additional heater

Technical focus

- Water volume 380 L
- Maximum hot water production 50 °C
- Tank and heat exchanger made with stainless steel
- Heating coil 52 m 316 L
- Internal and external pickling
- Foam insulation 70 mm
- Tank material 2 mm 316 L
- ABS external case



Panasonic PACi with Water Heat Exchanger for chilled and hot water production


Introducing a highly-efficient Water Heat Exchanger for PACi Series.
This ground-breaking product provides further possibilities by adding hydronic options.

Water outlet temperature:
Cooling: 5 ~ 15 °C
Heating: 30 ~ 55 °C



Highly-efficient Water Heat Exchanger for PACi Series.

System example.



1 Cost saving solution

- A+++ Energy efficiency class (scale from A+++ to D)
- Cost effective water projects thanks to lower cost for PACi compared to VRF
- Reducing the amount of HFC refrigeration in the project

2 Flexible and space saving system

- 2 installation possibilities (wall-mounted / floor-standing)
- Compact, lightweight unit design, only 27 kg

3 Easy installation, maintenance

- Quick mounting process
- Flow switch kit is included as a standard
- Direct access to electrical box
- Operation down to -20 °C ambient without the need for glycol

Flexible and space saving system

Compact and light unit.


- Only 205 mm depth fits within a limited space
- Lightweight design at only 27 kg, makes it easy to maneuver and position
- Maximum total refrigerant piping length: 90 m*

* 90 m for PAW-200W5APAC-1.

Only
205 mm
depth

Light
weight
27 kg

Piping
length
90 m



2 installation options.


- Wall-mounted and floor-standing installation options are available. Free-up floor space by using the wall-mounted installation
- Quick mounting process with its lightweight compact design
Make fixing holes > Fix 2 screws > Hang the unit > Finish

Quick simple
Install



Installer
friendly

Wall-mounted.



Floor-standing.



* Support feet included.

Foodchain/Small office application

- Fulfilling R32 refrigerant needs to follow environmental perspective, Company policy
- Hydraulic system to reduce total amount of HFC refrigeration
- Water solution to substitute electric heating system



Foodchain.

Residential/Commercial retail application


- Water solution to substitute existing boiler system
- For heating projects with longer than 50 m piping



Commercial retail.

PACi Water Heat Exchanger (WHE) is the ideal solution for residential and commercial applications; the investment costs can be amortised in a short period.



Easy maintenance operation from two points of access



Integrated cascade control as standard for maximum ease and flexibility

Built-in cascade control for 2 units.

The control of 2 refrigerant systems can be combined together in a cascade. This option is included in the standard scope of delivery on the WHE. It is activated using the one of the CZ-RTC5B remote controllers on the units as master. Rotation and Backup operation modes can be selected.




PACi Water Heat Exchanger can be connected as a cascade with up to 4 groups of 8 units, reaching up to 600 kW

Optional PAW-PACR4 cascade controller allows up to three groups, with each group containing between 1-8 units, to be combined into a cascade for failure substitution or temperature assist.

- Maximum 4 groups (up to 8 units per group)
- Rotation
- Failure substitution
- Temperature assist
- Operation output signal
- Alarm output signal

Example: 4 x groups.

Maximum available capacity per group: $8 \times 25 \text{ kW} = 200 \text{ kW}$.
Total maximum available capacity: $4 \times 200 \text{ kW} = 600 \text{ kW}$.



PACi with Water Heat Exchanger for chilled and hot water production

Constant 55 °C flow available.

Short-term investment recovery.

PACi Water Heat Exchanger is ideal for small offices and retails. The investment costs can be amortised within a very short period. This solution allows investors and operators to save money.



Water Heat Exchanger	PAW-200W5APAC-1	PAW-250W5APAC-1
Cooling capacity ¹⁾	kW	20,0
EER ¹⁾	W/W	3,03
Heating capacity ²⁾	kW	26,5
COP ²⁾	W/W	3,34
Energy efficiency class (Scale A+++ to D) ³⁾	A+++	A+++
η_{s,h} (LOT1) ⁴⁾	%	178
Dimension	HxWxD	mm
Net weight	kg	27
Water pipe connector	Inch	Male Thread 1 1/4
Cooling water flow [ΔT=5 K, 35 °C]	m ³ /h	3,45
Heating water flow [ΔT=5 K, 35 °C]	m ³ /h	4,15
Flow switch		Included
Water filter		Included
Outdoor unit	U-200PZH2E8	U-250PZH2E8
Sound pressure	Cool / Heat (Hi)	dB(A)
Dimension	HxWxD	mm
Net weight	kg	117
Piping diameter	Liquid	Inch [mm]
	Gas	Inch [mm]
Pipe length range	m	5 ~ 90
Elevation difference (in / out)	m	30
Pre-charged pipe length	m	30
Additional gas amount	g/m	60
Water outlet temperature range	Cool Min ~ Max	°C
	Heat Min ~ Max	°C
Operating range	Cool Min ~ Max	°C
	Heat Min ~ Max	°C

1) Data refers to 7 °C leaving chilled water temperature and 35 °C ambient air temperature, according to EN14511 standard. 2) Data refers to 35 °C leaving warm water temperature and 7 °C ambient air temperature according to EN14511 standard. 3) Following COMMISSION REGULATION (EU) No 811/2013 for low-temperature heat pumps. Scale from A+++ to D. 4) Following COMMISSION REGULATION (EU) No 813/2013 for low-temperature heat pumps.

Professional solution


Water heat exchanger is compatible with R32 PACi.

Many air conditioning manufacturers are selling R32 systems and it is becoming the standard refrigerant for split type air conditioning, because R32 has a much lower global warming potential than R410A, and can also provide higher efficiency.

Quick installation with pre-assembled flow switch

The flow switches come pre-assembled with pipe fittings for ease of installation.

Operation down to -20 °C with no glycol as the heat exchanger is installed indoors.



R22 Renewal. Fast, easy to install and cost effective

An important drive to further reduce the potential damage to our ozone.

It is often said that legislation is ruling our lives but sometimes it is there to help save lives. R22 phase out can be described as one of these and from Jan 1st 2010 the use of Virgin R22 refrigerant was banned within the European Union.



Panasonic is doing its part.

We at Panasonic are also doing our part – recognising that all finances are under pressure at the moment. Panasonic has developed a clean and cost effective solution to enable this latest legislation to offer less financial impact on your business.

The Panasonic renewal system allows good quality existing R22 or R410A pipe work to be re-used whilst installing high efficiency R32 systems.

By bringing a simple solution to the problem Panasonic can renew all Split Systems and PACi systems; and depending upon certain restrictions we don't even limit the manufacturer's equipment we are replacing.

By installing a high efficiency Panasonic R32 system you can benefit from around 30% running cost saving compared to the R22 system.

Yes...

1. Check the capacity of the system you wish to replace
 2. Select from the Panasonic range the best system to replace it with
 3. Follow the procedure detailed in the brochure and technical data
- Simple...

Why renewal?

Unique R22 Renewal from Panasonic: Fast, easy to install and cost effective.

- Panasonic refrigerant oil doesn't react to the most common oil types used in air-conditioning systems. This ensures the mix of oil does not damage the units.

Therefore installations are easier

- All Panasonic PACi units can be installed in R22 pipings, no specific models are available
- Up to 33 Bar! When there is any doubt about the strength of the piping, the maximum working pressure can be reduced to 33 Bar with a setting in the software of the outdoor unit

Reuse of existing piping (renewal design and installation)

Notes on reuse of existing refrigerant piping.

It is possible for each series of PZH and PZ series outdoor unit to reuse the existing refrigerant piping without cleaning when obtained under certain conditions. Make sure that the requirements under the section "Notes on reuse of existing refrigerant piping", "Measurement procedure for renewal" and "Refrigerant piping size and allowable piping length" will be satisfied in order to carry out.

Also, check the items with regard to section "Safety" and "Cleaning".

1. Prerequisite.

- If the refrigerant used for the existing unit is other than R22, R407C and R410A / R32, the existing refrigerant piping cannot be used.
- If the existing unit has another use than air conditioning, then existing refrigerant piping cannot be used.

2. Safety.

- If there is a hollow, crack or corrosion on the piping, make sure to install new piping.
- If the existing piping is other than capable of reuse of piping as shown in the flowchart, make sure to install new piping.
- In case of multiple operation, use our genuine branch piping for refrigerant R32.

A local supplier shall assume responsibility for the defects and hollows on the reuse of existing piping surface and recognition of reliability of the piping strength. There is no guarantee that we take responsibility for such damages.

The operational pressure of the refrigerant R32 becomes higher compared to R22 or R410A. In the worst case, a lack of compressive strength may lead to piping explosion.

3. Cleaning.

- When the refrigerant oil used for the existing unit is other than the listed below, make sure to install new piping or wash it thoroughly before reusing it.
[Mineral Oil] SUNISO, FIORE S, MS
[Synthesized oil] alkyl benzene oil (HAB, parallel freeze), ester oil, ether oil (PVE only)

If the existing unit is GHP type, it is necessary to wash the piping thoroughly.

- If the existing pipes in the outdoor and indoor units remain disconnected, make sure to install a new piping or wash it thoroughly before reusing it.
- If the discoloured oil or residue remains in the existing piping, make sure to install a new piping or wash it thoroughly before reusing it. See "Deterioration Criteria for Refrigerant Oil" in table 3.
- If the compressor of the existing air conditioner has a failure history, make sure to install a new piping or wash it through thoroughly before reusing it.


When reusing the existing piping as it is without removing dirt and dust, inadequate piping could result a renewal appliance in failure.



Notes on renewal for simultaneous operation of multiple units.

Only main pipe is applicable for using the different diameter size.

In case of different diameter size for the branch pipes, a new installation work for a standard size is necessary. Be sure to use our genuine branch piping for refrigerant R32.



Notes on renewal for simultaneous operation of multiple units

Capacity class	Standard liquid pipe size	Standard gas pipe size
Type 50	Ø 6,35	Ø 12,70
Type from 60 to 140	Ø 9,52	Ø 15,88
Type 200	Ø 9,52	Ø 25,40
Type 250	Ø 12,70	Ø 25,40

- Only the main pipe L can be used among different diameter's existing piping
- Installation work as a standard size is capable for L1, L2, Ø1 - Ø4 piping
- Be sure to use our genuine branch piping for refrigerant R32

1. In case of single unit:


It is not necessary to charge with additional refrigerant until the chargeless pipe length in the table 2. If the pipe length is exceeding the charge less pipe length, charge with additional refrigerant amount per 1 m according to the equivalent length.

2. In case of simultaneous operation of multiple units:

Calculate the refrigerant charging amount according to the calculating method of the standard piping diameter. As to the additional refrigerant charging amount per 1 m, refer to the additional amount in the table 2.

Measurement procedure for renewal

Observe the following procedure when reusing the existing piping or carrying out renewal installation work.
Flowchart of existing piping measures criteria for PZH and PZ series outdoor unit.



Refrigerant piping size and allowable piping length.

Check if reuse of existing refrigerant piping is possible based on the following chart.

The standards other than this one (difference of elevation, etc.) are identical to the requirements of ordinary refrigerant piping.

Table 1 - Reusable existing piping (mm)

Material	0	1/2 H, H*						
External diameter	Ø6,35	Ø9,52	Ø12,70	Ø15,88	Ø19,05	Ø22,22	Ø25,40	Ø28,58
Thickness	0,80	0,80	0,80	1,00	1,00	1,00	1,00	1,00

* It is impossible to reuse the size of Ø19,05, Ø22,22, Ø25,4 and Ø28,58 for material O. Change to material 1/2H or material H.

Table 2 - 1 Refrigerant piping size: 2,5 - 14,0 kW type (mm)

		Tentative data							
Liquid pipe		Ø6,35		Ø9,52		Ø12,70			
Gas pipe		Ø9,52	Ø12,70	Ø15,88	Ø12,70	Ø15,88	Ø19,05	Ø15,88	Ø19,05
PZH3	Type 36 ~ 60	Additional gas 15 g/m	✗	Standard 40 m (30 m)	✗	✗	✗	✗	✗
	Type 25								
	Type 36	Additional gas 10 g/m	✗	Standard 15 m (7,5 m)	✗	✗	✗	✗	✗
PZ3	Type 50	Additional gas 15 g/m	✗	Standard 20 m (7,5 m)	✗	✗	✗	✗	✗
	Type 60	Additional gas 15 g/m	✗	Standard 30 m (7,5 m)	✗	✗	✗	✗	✗
	Type 71	Additional gas 17 g/m	✗	✗	Standard 40 m (10 m)	✗	✗	✗	✗

		Tentative data							
Liquid pipe		Ø6,35		Ø9,52		Ø12,70			
Gas pipe		Ø9,52	Ø12,70	Ø15,88	Ø12,70	Ø15,88	Ø19,05	Ø15,88	Ø19,05
PZH3	Type 71	✗	□ 10 m (10 m)	□ 10 m (10 m)	▽ 30 m (30 m)	Standard 50 m (30 m)	✗	□ 25 m (15 m)	✗
	Type 100 ~ 140	✗	✗	✗	✗	Standard 85 m (30 m)	◎ 85 m (30 m)	□ 35 m (15 m)	□ 35 m (15 m)
Additional gas		20 g/m				45 g/m		80 g/m	
PZ3	Type 100 ~ 140	✗	✗	✗	✗	Standard 50 m (30 m)	◎ 50 m (30 m)	□ 25 m (15 m)	□ 25 m (15 m)
Additional gas						45 g/m		80 g/m	
PZH2	Type 50	✗	Standard 40 m (30 m)	◎ 40 m (30 m)	□ 20 m (15 m)	□ 20 m (15 m)	✗	✗	✗
PZ2	Type 60 ~ 71	✗	▽ 10 m (10 m)	□ 10 m (10 m)	▽ 30 m (20 m)	Standard 50 m (20 m)	✗	□ 25 m (10 m)	✗
Additional refrigerant charging amount per 1 m		20 g/m				40 g/m		80 g/m	
PZH2	Type 60 ~ 71	✗	▽ 10 m (10 m)	□ 10 m (10 m)	▽ 30 m (30 m)	Standard 50 m (30 m)	✗	□ 25 m (15 m)	✗
	Type 100 ~ 140	✗	✗	✗	✗	Standard 75 m (30 m)	◎ 75 m (30 m)	□ 35 m (15 m)	□ 35 m (15 m)
PZ2	Type 100 ~ 140	✗	✗	✗	✗	Standard 50 m (30 m)	◎ 50 m (30 m)	□ 25 m (15 m)	□ 25 m (15 m)
Additional refrigerant charging amount per 1 m		20 g/m				50 g/m		80 g/m	

How to see table definition (example):

In case of type 71, standard size is liquid pipe Ø9,52 / gas pipe Ø15,88.

There is a limitation to liquid pipe Ø9,52 / gas pipe Ø12,70 and to liquid pipe Ø12,70 / gas pipe Ø15,88.

However, they are applicable for different diameter's pipes.

Table 2 - 2 Refrigerant piping size: 20,0 - 25,0 kW type (mm)

		Tentative data							
Liquid pipe		Ø9,52		Ø12,70		Ø15,88			
Gas pipe		Ø22,22	Ø25,40	Ø28,58	Ø22,22	Ø25,40	Ø28,58	Ø22,22	Ø25,40
PZH	Type 200	▽ 80 m (30 m)	Standard 100 m (30 m)	◎ 100 m (30 m)	▽ 50 m (15 m)	□ 50 m (15 m)	□ 50 m (15 m)	✗	✗
	Type 250	✗	✗	✗	▽ 80 m (30 m)	Standard 100 m (30 m)	◎ 100 m (30 m)	▽ 65 m (20 m)	□ 65 m (20 m)
Additional refrigerant charging amount per 1 m		40 g/m				80 g/m		120 g/m	

◎ Allowable

□ Limited piping length


50 m Maximum piping length

▽ Cooling capacity down

✗ Unallowable

(50 m) Charge less piping length in a single connection

Table 3 - Deterioration Criteria for Refrigerant Oil



Accessories and control

Drain kits

Drain kit to suit outdoor units from 5,0 to 7,1 kW.

CZ-50DRS1

Drain kit to suit outdoor units from 10,0 to 25 kW.

CZ-140DRS1

Branch Pipes, Header



Branch pipe.

CZ-P224BK2BM



Branch pipe (from 22,4 kW to 68 kW).

CZ-P680BK2BM



Header.

CZ-P3HPC2BM

Outdoor accessories




Tray for condenser water compatible with outdoor elevation platform.

PAW-WTRAY



Outdoor elevation platform.
Dimension (H x W x D): 400 x 900 x 400 mm

PAW-GRDSTD40



Outdoor base ground support for noise and vibration absorption.

Dimension (H x W x D): 600 x 95 x 130 mm
Safe working load: 500 kg

PAW-GRDBSE20

Panels



Panel for 4 way 60x60 cassette - PY3.

CZ-KPY4



Standard panel for 4 way 90x90 cassette.

CZ-KPU3W



Econavi panel for 4 way 90x90 cassette.

CZ-KPU3AW

Sensors



Econavi energy saving sensor.


CZ-CENSC1



Remote temperature sensor.

CZ-CSRC3

Plenums



Air outlet plenum for S-3650PF3E.

CZ-56DAF2

Air outlet plenum for S-6071PF3E.

CZ-90DAF2

Air outlet plenum for S-1014PF3E.

CZ-160DAF2

Air outlet plenum for S-200PE3E5B and S-200PE2E5.

CZ-TREMIESPW705

Air outlet plenum for S-250PE3E5B and S-250PE2E5.

CZ-TREMIESPW706

VRF Smart Connectivity+



Remote controller Panasonic Net Con, RH, No PIR, R1/R2.

SER8150R0B1194

Remote controller Panasonic Net Con, RH, PIR, R1/R2.

SER8150R5B1194

Wireless ZigBee® Pro module / Green Com card.

VCM8000V5094P



Hotel room expansion module 14 indoor units.

HRCEP14R



Hotel room controller 28 indoor units.

HRCPBG28R



Door / window wireless sensor.

SED-WDC-G-5045



Wall / ceiling (motion) wireless sensor.

SED-MTH-G-5045



CO₂ sensor.

SED-CO2-G-5045



Sensor with room temperature and humidity.

SED-TRH-G-5045



Water leakage sensor.



SED-WLS-G-5045

			
Cover frame. Silver. FAS-00	Cover frame. White. FAS-01	Cover frame. Glossy translucent white. FAS-03	Cover frame. Light tan wood. FAS-05

		
Cover frame. Dark brown wood. FAS-06	Cover frame. Dark black wood. FAS-07	Cover frame. Brushed steel finish. FAS-10

Controller and touch controllers for hotels with dry contacts



	
Modbus RS-485 touch room controller with I/O, white. PAW-RE2C4-MOD-WH	Modbus RS-485 touch room controller with I/O, black. PAW-RE2C4-MOD-BK
Touch display control with 2 digital inputs, white. PAW-RE2D4-WH	Touch display control with 2 digital inputs, black. PAW-RE2D4-BK

Hotel sensors for dry contacts

			
Wall motion sensor 24 V. PAW-WMS-DC	Ceiling motion sensor 24 V. PAW-CMS-DC	Power supply 24 V. PAW-24DC	Door or window contact. PAW-DWC
Wall motion sensor 240 V AC. PAW-WMS-AC	Ceiling motion sensor 240 V AC. PAW-CMS-AC		

Centralised controls

		
System controller for 64 indoor units with weekly timer. CZ-64ESMC3	Central ON / OFF controller, up to 16 groups, 64 indoor units. CZ-ANC3	Intelligent controller (touch screen/web server) to control up to 256 indoors with included load distribution ratio (LDR). CZ-256ESMC3

Panasonic AC Smart Cloud



+ ALL REFERENCES RELATED TO AC SMART CLOUD IS IN THE DEDICATED PAGE

Panasonic AC Smart Cloud. Cloud internet control. Up to 128 groups. Controls 128 units.

CZ-CFUSCC1

BMS interface with S-Link



Modbus RTU and TCP interface for 16 indoor units.

PAW-AC2-MBS-16P

Modbus RTU and TCP interface for 64 indoor units.

PAW-AC2-MBS-64P

Modbus RTU and TCP interface for 128 indoor units.

PAW-AC2-MBS-128P

KNX interface for 16 indoor units.

PAW-AC2-KNX-16P

KNX interface for 64 indoor units.

PAW-AC2-KNX-64P

BACnet IP and MSTP interface for 16 indoor units.

PAW-AC2-BAC-16P

BACnet IP and MSTP interface for 64 indoor units.

PAW-AC2-BAC-64P

BACnet IP and MSTP interface for 128 indoor units.

PAW-AC2-BAC-128P

Accessories interfaces



Commercial Wi-Fi Adaptor.

CZ-CAPWFC1



KNX interface (Intesis).

PAW-RC2-KNX-1i



Modbus RTU interface (Intesis).

PAW-RC2-MBS-1



Modbus RTU interface to control 4 indoor groups (Intesis).

PAW-RC2-MBS-4



BACnet IP and MSTP (Intesis).

PAW-RC2-BAC-1



NEW KNX interface (Airzone).

PAW-AZRC-KNX-1

**NEW** Modbus RTU interface (Airzone).

PAW-AZRC-MBS-1

**NEW** BACnet IP and MSTP interface (Airzone).

PAW-AZRC-BAC-1



RAC interface adapter for integration into S-Link, plus external input and alarm/status output (for YKEA units).

CZ-CAPRA1

**Centralised controls. Connection with general equipment**

Adaptor for ON / OFF control of external devices.

CZ-CAPC3



Demand control for Mini ECOi and PACi outdoor units.

CZ-CAPDC3




Mini series parallel device controlling indoor units, maximum 1 group and 8 indoor unit.

CZ-CAPBC2



Communication Adaptor. Up to 128 groups. Controls 128 units.

CZ-CFUNC2

**Individual controls****NEW** CONEX wired remote controller (non-wireless), white.CZ-RTC6W¹⁾**NEW** CONEX wired remote controller with Bluetooth®, white.CZ-RTC6WBL¹⁾**NEW** CONEX wired remote controller with Wi-Fi and Bluetooth®, white.CZ-RTC6WBLW^{1,2)}

CONEX wired remote controller (non-wireless), black.

CZ-RTC6



CONEX wired remote controller with Bluetooth®, black.

CZ-RTC6BL



CONEX wired remote controller with Wi-Fi and Bluetooth®, black.

CZ-RTC6BLW²⁾

Design wired remote controller with Econavi function and datanavi.

CZ-RTC5B



Infrared remote controller for wall-mounted.

CZ-RWS3



Infrared remote controller and receiver for 4 way 60x60 cassette - PY3 with panel.

CZ-RWS3 + CZ-RWRY3



Infrared remote controller and receiver for 4 way 90x90 cassette.

CZ-RWS3 + CZ-RWRU3W



Infrared remote controller and receiver for ceiling.

CZ-RWS3 + CZ-RWRT3




Infrared remote controller and receiver for all indoor units.

CZ-RWS3 + CZ-RWRC3



Accessories PCB



T10 interface PCB with digital and relay connections.

PAW-T10



PCB for server room application, control up to 4 indoor unit groups, redundancy, backup, etc.

PAW-PACR4



Connector to PACi NX indoor unit's PCB to provide OPT functions.

PAW-OPT-NX



Accessories cables



Cable for all the T10 functions.

CZ-T10



Cable to operate external EC fan.

PAW-FDC



Cable for all option monitoring signals.

PAW-OCT



Cable with force thermo OFF/leakage detection.

PAW-EXCT



PRO-HT Tank accessories

Tank controller for PACi system.

PAW-VP-RTC5B-PAC

Additional heater.

PAW-IU39

1) Available in Autumn 2023. 2) Only compatible with PACi NX Series.